

WATERPROOFING SIKA SOLUTIONS FOR CONCRETE BASEMENTS



BUILDING TRUST



ADVANTAGES OF OUR SOLUTIONS

Basements and below ground civil engineering structures protected with Sika waterproofing solutions have increased living comfort and wider possibilities for use, plus the total cost of ownership is reduced and the durability is increased for the entire service life of the project.

Our fully integrated and compatible system solutions are sustainably produced and well proven in practice for many decades all over the world, plus they are fully tested and certified to all leading national and international standards. This gives owners, their project specifiers and contractors the security of clearly defined performance characteristics for all of Sika's waterproofing solutions for their specific requirements.

CONTENT

4	Waterproofing Solutions		
6	Below Ground Structures - Exposure and Stress		
8	Owner's Project Requirements		
11	Basement Waterproofing – Concept and Strategy		
12	Waterproofing Technologies		
14	Excavation and Construction Procedures		
16	Sika Waterproof Mortars and Bituminous Coatings		
18	Sika White Box Concept and Watertight Concrete Systems		
20	Wet Bonded Waterproofing Membrane		
22	Fully Bonded Flexible Sheet Membrane Systems		
24	Compartmentalized Membrane Systems with Integrated Control and Injection Back-up		
26	Basement Waterproofing Solutions		
28	Repair and Refurbishment Solutions		
30	Project References		

WATERPROOFING SOLUTIONS

WATERPROOFING SYSTEMS for below ground structures are faced with more stringent requirements regarding durability, exposure and stress conditions, construction method and sequence, ease of application and total cost management. In addition, sustainable system solutions are becoming more important in order to save natural resources, energy and water, plus reduction of CO₂ etc. As the global leader in providing structural waterproofing solutions, Sika has the most complete and comprehensive range of products and systems that are designed and can be adapted to meet the specific needs and requirements of owners, architects, engineers and contractors on site.



RESIDENTIAL BUILDINGS

Basement waterproofing solutions for storage rooms, wellness and fitness areas or movie theatres in residential buildings.



COMMERCIAL OFFICE BUILDINGS

Basement waterproofing solutions for strong rooms, computer rooms or storage rooms in commercial office buildings.



ARCHIVES/LIBRARIES

Completely dry basement waterproofing solutions for humid sensitive archive rooms in libraries.



UNDERGROUND PARKING AREA

Basement waterproofing solutions for different grades of watertight underground parking areas. **Basement or any below-ground structure** that is formed by a base slab, walls and a top slab, is partially or fully exposed to the surrounding soil and groundwater, resulting in specific exposure and stress from the prevailing permanent or temporary environmental conditions. Today new building owners generally request a service life of 50 years or more, and for structures such as tunnels up to 120 years. Any lack of water-tightness severely reduces the long-term durability of a building or other below-ground structure and badly affect its planned use as water ingress will result in physical attack and deterioration of the concrete. This leads to expensive structural repair works, damage or loss of interior finishes and goods, operational downtime, or serious impact on the internal environment from damp and condensation.

The selection of the appropriate waterproofing method, the project specific design of the chosen waterproofing system and its correct installation on site are key elements in minimizing the Total Cost of Ownership. A waterproofing system typically amounts to less than 1% of the total core constructions cost, yet the selection of a high quality waterproofing solution can easily save this amount or more, in future maintenance and repair costs over the service life of the structure.

Sika provides full range of technologies and systems used for below ground waterproofing. This includes highly flexible membrane systems, liquid applied polymeric membranes, watertight concrete admixtures, joint waterproofing systems, waterproofing mortars and coatings, as well as injection sealing grouts. All of these solutions are designed to be used together to meet the specific needs and requirements of owners, architects, engineers and contractors on site.

Sika's expertise is combined with more than 100 years of experience from all around the world, in providing successful waterproofing solutions for building basements and below ground civil engineering structures, such as tunnels and water retaining structures. Sika waterproofing experts are able to support our customers throughout their projects, from initially determining the best waterproofing concept, through detailed design and detailing, to on-site support for successful installation and completion. This also includes extensive remedial solutions for waterproofing existing structures.



METRO STATIONS

Specific waterproofing solutions for metro stations build in open-cut construction method.



SERVICE ROOMS

Basement waterproofing solutions for various plant rooms and underground power stations.



RETAIL UNITS AND WAREHOUSES

Complete dry waterproofing solutions to protect goods against humidity in retail units and warehouses.



LEISURE FACILITIES

Basement waterproofing solutions for below ground leisure facilities and indoor swimming pools and other sport rooms.

BELOW GROUND STRUCTURES – EXPOSURE AND STRESS



TYPE OF EXPOSURE AND STRESS

Below ground structures can be subject to many different exposure conditions including:

- Different levels of water exposure and pressure (e.g. damp soil, percolating water or water under hydrostatic pressure, and open water)
- Aggressive ground water containing chemicals (commonly sulphates and chlorides in solution)
- Unequal static forces (due to load, settlement, or uplift, etc.)
- Dynamic forces (e.g. from settlement, earthquake, explosion, etc.)
- Temperature variations (frost during the night/winter, heat during the day/summer)
- Gases in the ground (e.g. Methane and Radon)
- Aggressive biological influences (plant roots/growth, fungal or bacterial attack)



EXPOSURE IMPACT ON BELOW GROUND STRUCTURES

These different types of exposure may adversely influence the use, watertightness and durability of a basement structure, resulting in a reduced service life of the entire structure.

Exposure		Impact on structure
Water ingress	\rightarrow	Damage to structure, finishes, contents and the internal environment (condensation and mould
		growth etc.), loss of thermal insulation, corrosion of steel reinforcement
Aggressive chemicals	\rightarrow	Concrete damage (due to sulphate attack), corrosion of steel reinforcement (due to chloride attack)
Unequal static forces	\rightarrow	Structural cracking
Dynamic forces	\rightarrow	Structural cracking
Temperature variations	\rightarrow	Condensation, scaling or cracking of concrete
Gas penetration	\rightarrow	Gas penetration and exposure for occupants
Fungal/bacterial attack	\rightarrow	Damage to the waterproofing system, finishes or contents

OWNER'S PROJECT REQUIREMENTS

To define the appropriate waterproofing strategy and type of system for a specific project, it is important to consider not only the ground conditions but also the project requirements of the owner: Functionality and future use, the service life and the total cost of ownership.



1 DEGREE OF WATERTIGHNESS REQUIRED

The future use defines the degree of watertightness and protection of a structure. The British standards describes in BS 8102-2009 different level of watertighness which can be combined with additional protection requirements.

Basic utility
Some seepage and damp
areas tolerable*

GRADE1

GRADE 2

Better utility No water penetration, some damp areas tolerable*, ventilation may be required

* Dependent on use

GRADE 3

Habitable No water penetration acceptable, ventilation and dehumidification are required

ADDITIONAL REQUIREMENTS (FORMERLY GRADE 4)

As Grade 3 plus:

- No water vapour penetration
- Totally dry environment
 Protection against chemical
 - attacks
- Gas barrier
- ∎ etc.
- Residential areas
- Computer rooms
- Archives
- Special purpose facilities and areas

* Dependent on use



- Underground car parks
- Plant rooms
- Workshops



- Underground car parks
- Storage areas
- Plant rooms
- Workshops



- Ventilated residential units and offices
- Restaurants and commercial areas
- Leisure facilities

2 SERVICE LIFE / DURABILITY

The required service life of individual concrete structure is mainly affected by water ingress and depends on the protection performance and longevity of selected waterproofing system. The graphic below shows the service life/durability of a structure depending on the grade of waterproofing system.



No Waterproofing: structure directly exposed to ground water without any waterproofing system.

System A: structure protected with low grade waterproofing system.

System B: Structure protected with a medium grade waterproofing system.

System C: Structure protected with a high grade waterproofing system.

OWNER'S PROJECT REQUIREMENTS

3 TOTAL COST OF OWNERSHIP

The total cost of ownership (TCO) for the owner and investor includes all of the building costs for the entire service life of the structure, including the initial investment, the cost of any loss or damage to interior furnishings and goods etc. due to water ingress, the cost of any repair and maintenance, plus the cost of any downtime during any such works.

The graphic below illustrates the total cost of ownership for a specific project (e.g. typical commercial building) with a required service life of at least 50 years.



BASEMENT WATERPROOFING – CONCEPT AND STRATEGY

In general there are 3 different waterproofing concepts which can take all of the relevant project requirements into consideration:

INTEGRAL WATERPROOFING SYSTEM

A waterproofing system integrated into the concrete structure. Liquid water penetration is stopped by the structure itself and cannot entirely pass through into the basement. Typical products are admixtures for watertight concrete combined with appropriate joint sealing systems for connection, construction and movement joints.

- Grade of watertightness: Grades 1–3
- Application: New construction
- Protection provided: Waterproofing
- Durability: Very high durability (for non-agressive ground water)



A waterproofing barrier applied on the external surfaces that are exposed to ground water (possitive side). The structure is protected against water ingress and also against any aggressive substances or influences. For some materials such as post applied waterproofing mortars and coatings, access to the external surfaces is required for application after concreting.

- Grade of watertightness: Grades 1–3 plus additional requirements
- Application: New construction
- Protection provided: Waterproofing & concrete protection
- Durability: Low to high durability



INTERNALLY APPLIED WATERPROOFING SYSTEM

A waterproof barrier is applied on the internal surfaces of the structure (negative side). These systems do not prevent damage to the structure from water ingress, nor concrete damage due to aggressive chemicals. Generally these systems are applied as coatings or sheet membrane linings, and is only recommended for refurbishment works in example where access to the directly exposed surfaces is not possible.

- Grade of watertightness: Grades 1–3
- Application: Generally for refurbishment only
- Protection provided: Waterproofing
- Durability: limited durability (as the structure is unprotected)



WATERPROOFING TECHNOLOGIES



Waterproofing mortars and renderings



Bitumen coatings



Sika White Box concept/Watertight concrete



Wet bonded sheet membranes



Fully bonded sheet membranes



Compartmentalized sheet membrane systems



The performance of each different waterproofing technology can generally be positioned as follows:

Durability / Reliability

Very low: <10 years/water ingress not really controlled. Low: 10 – 20 years/water ingress limited. Medium: 25 - 50 years/water ingress very limited.

High: >50 years/water ingress complete under control.

Exposure / Aggressive conditions

Low: water pressure 0 – 5 m/no settlement, no aggressive ground water.

Moderate: water pressure 5 - 10 m/no aggressive ground water, cracks <0.2 mm.

High: water pressure 10 - 20 m/aggressive ground water, settlement.

Extreme: water pressure >20 m/very aggressive ground water, earthquake, gas penetration.

EXCAVATION AND CONSTRUCTION PROCEDURES

The type and depth of excavation and construction procedure also affects the selection and installation of the waterproofing system, e.g. for some externally applied waterproofing systems, working space is required. Therefore this has to be taken into consideration at an early stage of the design phase in order to plan sufficient excavation and any temporary works required such as shoring etc.. Waterproofing systems and their use with typical excavation requirements / construction methods are shown below.

OPEN CUT EXCAVATION

WITH SLOPING SIDES

Description:

This basic excavation method using sloping sides allows an easy bottom-up construction method and has no impact on the selection or installation of the waterproofing system.

Waterproofing systems:

Integral waterproofing systems:

■ Sika White Box / Watertight Concrete System

Externally applied waterproofing systems:

- Compartmentalized membrane systems
 Pre- and post-applied fully bonded sheet
- Pre- and post-applied fully bonded sneet membranes
- Liquid applied membranes
- Waterproofing mortars and coatings (in combination with drainage systems)

WITH RETAINING WALLS

Description:

Open cut excavation using temporary shoring/ retaining walls does not influence the selection or installation of the waterproofing system when enough space (>1.0 m) can be provided between the retaining wall and the structure.

Waterproofing systems:

Integral waterproofing systems:

■ Sika White Box / Watertight Concrete System

Externally applied waterproofing systems:

- Compartmentalized membrane systems
- Pre- and post-applied fully bonded sheet membranes
- Liquid applied membranes
- Waterproofing mortars and coatings (in combination with drainage systems)





CONSTRUCTION WITH PILED / DIAPHRAGM WALLS

CONSTRUCTION INSIDE PILE WALLS

Description:

Pile walls or diaphragm walls limit the selection of the waterproofing system due to limited space and access. This is because the structure is normally built directly against this wall. Post- and externally applied, bonded waterproofing systems can therefore not be used for these structures.

Waterproofing systems:

Integral waterproofing systems: ■ Sika White Box / Watertight Concrete System

Externally applied waterproofing systems (base slab):

- Compartmentalized membrane systems
- Pre-applied fully bonded sheet membranes



PILE WALLS FORMING PART OF THE STRUCTURE

Description:

This method can be used for bottom-up as well as top-down con- struction. Unlike other methods, diaphragm walls are also used to form part of the new structure. Waterproofing of the connections and intersections between base slab / walls are key. Externally applied waterproofing can only be used below the base slab.

Waterproofing systems:

Integral waterproofing systems:

■ Sika White Box / Watertight Concrete System

Externally applied waterproofing systems (base slab):

- Compartmentalized membrane systems
- Pre-applied fully bonded sheet membranes



SIKA WATERPROOF MORTARS AND BITUMINOUS COATINGS





EXTERNALLY APPLIED SYSTEMS WITH OR WITHOUT CRACK-BRIDGING ABILITIES

Sika waterproof mortars and bitumen based coatings are rigid or semi-flexible waterproofing products. They are supplied as ready to use solutions for many basements to seal against damp soil, seepage and percolating water. They must be pre-applied on suitable substrates under new structural concrete slabs and are generally postapplied externally on new walls. They must be used in combination with appropriate joint waterproofing systems for the connection, construction and movement joints. Good external drainage with a permanent dewatering system is also necessary; normally using drainage pipes placed at or below the level of the base slabs to prevent any build-up of water pressure.

USE

MAIN ADVANTAGE

- As a waterproofing system for Grades 1 to 2
 Co
 Co
- To protect structures against percolating water
- For limited ground conditions (no settlement, less aggressive environments, low water pressure)
- Cost efficient solution (Material + Application)
 Ready to use & easy to
- apply ■ Provide additional
- concrete protection

TYPICAL PROJECTS

- Domestic applications
- Residential buildings
- Industrial buildings

SIKA PRODUCTS AND SYSTEM SOLUTIONS

SikaTop® Seal-107	2-component, polymer modified, rigid cementitious water- proofing mortar, internally and externally applied for full sur- face waterproofing and tanking.
Sikalastic®-1 KMY	1-component, fibre reinforced, flexible cementitious water- proofing compound.
Igolflex [®] R	One component, rigid, solvent-free, polystyrene-filled bitumen based coatings for use against water ingress and in contact with ground water (positive water pressure side).
Complementary products	for joint sealing and waterproofing:
Sika® Waterbars	Internally or externally applied joint waterstops, based on PVC for sealing construction and movement joints.
SikaSwell [®] / Sika [®] Hy- drotite Sealants and Profiles	Range of hydrophilic profiles and gun applied sealants, designed for the sealing and waterproofing of construction joints and penetrations (e.g. pipe entries).

SIKA WHITE BOX CONCEPT AND WATERTIGHT CONCRETE SYSTEMS





INTEGRAL, RIGID AND COST EFFICIENT SYSTEMS

The "Sika White Box Concept" involves optimum structural design and reinforcement together with an integral rigid waterproofing solution. This consists of a waterproof concrete combined with appropriate joint sealing systems for any necessary construction and movement joints. To produce concrete that is impermeable to water, special admixtures including superplasticizers and pore-blocking or crystalline agents have to be used, in order to also ensure optimum consistence, flow and ease of compaction in a dense matrix with minimal voids. For sealing the joints, many different Sika solutions can be used including hydrophilic sealants / profiles, waterbars in various material qualities, injection hoses or sealing tapes, dependent on the type and location of the joint and its requirements.

USE

- As the waterproofing solution for Grades 1 – 3
- For non-moving structures and less aggressive environments (without additional concrete protection)

MAIN ADVANTAGE

- Cost effective solution (Material + Application)
- Very durable waterproofing system
- Reduced working procedures on site

TYPICAL PROJECTS

- Underground car parks
- Commercial developments
- Residential buildings
- Industrial facilities

SIKA PRODUCTS AND SYSTEM SOLUTIONS

Sika ViscoCrete®	Mid and high range water reducing admixtures for significant reduction of water/cement ratio and improving workability.
Sika® WT-220 PMY	Water resisting and crystalline waterproofing concrete admix- ture.
Sika® Waterbars	Internal or external applied waterstops based on PVC or TPO for construction and movement joints.
SikaSwell [®] / Sika [®] Hy- drotite Sealants and Profiles	Range of hydrophilic profiles and gun applied sealants, de- signed for the sealing and waterproofing of construction joints and penetrations (e.g. pipe entries).
SikaFuko [®] Injection Hoses	Injection hoses for construction joints that can be used for sealing by injection and re-injection in the event of future movement etc.
Sikadur-Combiflex® SG System	High performance, over-banding sealing tape system for post- sealing and waterproofing of construction and movement ioints.

WET BONDED WATERPROOFING MEMBRANE





FAST AND EASY APPLIED, FULLY BONDED WATERPROOF-ING MEMBRANE SYSTEM DESIGNED TO PERFORM ON TYPICAL BASEMENT JOBSITES

SikaBit[®] W is a sheet membrane waterproofing system consisting of a cross laminated HDPE carrier film laminated with a modified bitumen based adhesive on both surfaces. Due to the double-sided structure the SikaBit[®] W system can be installed single or (partially) double layered and does not require any accessories such as tapes and pastes etc. The membrane can be both pre-applied under the slab as well as post-applied to the walls by the use of a one-component bonding mortar.

USE

- As the waterproofing solution for Grades 1 3
- For additional protection to concrete structures against aggressive influences such as chlorides, sulphates or biological attack

MAIN ADVANTAGE

- Upward bonding
- Crack-bridging ability
- Chemical and abrasion resistance
- Easy to apply, especially around complex details
- ments
 Residential buildings
 Industrial facilities
 - Civil engineering

TYPICAL PROJECTS

Underground car parks

■ Commercial develop-

structures (e.g. open-cut tunnels)

SIKA PRODUCTS AND SYSTEM SOLUTIONS

SikaBit° W-15	Wet-applied, modified bitumen waterproofing membrane, fully bonded to the structural concrete.
SikaBit® W-1	One component bonding mortar
Complementary products	for Joint Sealing and Waterproofing:
Sika® Waterbar	Externally fixed, cast-in-place waterstops based on PVC for sealing and waterproofing construction and movement joints.
SikaFuko [®] Injection hoses	Injection hoses for construction joints and other details, with or without swelling strips, which can be used for sealing by injection and re-injection in the event of future movement etc.
SikaSwell [®] / Sika [®] Hy- drotite Sealants and Profiles	Range of hydrophilic profiles and gun applied sealants, de- signed for the sealing and waterproofing of construction joints and penetrations (e.g. pipe entries).
Sikadur-Combiflex® SG System	High performance, over-banding sealing tape system for post- sealing and waterproofing of construction and movement joints.

FULLY BONDED FLEXIBLE SHEET MEMBRANE SYSTEMS





SIKA'S UNIQUE, PRE-APPLIED, FULLY BONDED AND CRACK-BRIDGING MEMBRANE SYSTEM

SikaProof[®], the fully bonded and highly flexible FPO sheet waterproofing membrane systems can permanently prevent any lateral water underflow between the waterproofing and the structural concrete in the event of local damage, even when this has occurred below the base slab.

The SikaProof[®] fully bonded sheet waterproofing membrane systems are simple and easy to use, making them fast and secure to install on site. The overlaps, butt joints and details are all connected and sealed very simply by bonding them together with sealing tapes or self-adhered strips. There are no complicated welding procedures and no special equipment is required on site.

USE

1-3+

conditions

solution for Grades

■ For aggressive ground

Radon gas etc.)

(ground water and soil,

MAIN ADVANTAGE

- As the waterproofing ■ Cost effective solution (Material + Application) High durability
 - No lateral water
 - underflow High flexibility and crack-
 - bridging ability Approved detailings

TYPICAL PROJECTS

- All types of concrete basements (residential, commercial etc.)
- Industrial facilities
- Pre-cast structures

SIKA PRODUCTS AND SYSTEM SOLUTIONS

SikaProof® A	Pre- and cold applied sheet waterproofing membrane system for application below base slabs, plus on single and double- faced formwork cast walls.
SikaProof® P	Post-applied sheet waterproofing membrane system, specially designed for roof slabs and double-faced formwork cast walls.
Complementary products	s for joint sealing and waterproofing:
Sika® Waterbars	Externally fixed, cast-in-place waterstops based on PVC for sealing and waterproofing construction and movement joints.
Sikadur-Combiflex® SG System	Over-banding sealing tape system for post-sealing and waterproofing of construction and movement joints, around penetrations and for connections.
SikaSwell® Sealants and Profiles	Range of hydrophilic profiles and gun applied sealants, designed for sealing and waterproofing of construction joints and penetrations.(e.g. pipe entries).
SikaFuko® Injection hoses	Injection hoses for construction joints and other details, with or without swelling strips, which can be used for sealing by injection and re-injection in the event of future movement etc.

COMPARTMENTALIZED MEMBRANE SYSTEMS WITH INTEGRATED CONTROL AND INJECTION BACK-UP







Sika® Waterbar plus SikaFuko®

Sikaplan[®] WP Tape Sika[®] Dilatec

HIGH PERFORMANCE, CRACK-BRIDGING AND FULLY CONTROLLED

Highly flexible waterproofing systems using Sikaplan PVC based sheet waterproofing membranes are installed externally and cover the entire basement structure in contact with the ground. The waterproofing layer is divided into 'compartments' with a network of cast in place compatible waterstops that are welded to the membrane. This allows very significant reduction of risk as in the event of any leaks (i.e. from damage to the membrane), the position of the leak is easy to locate by the control and injection sockets and remedial action (i.e. injection) can be taken to ensure continued watertightness and concrete protection of the system at any time during its service life.

USE

- As waterproofing solutions for Grades 1 - 3+
- For high demands and harsh ground conditions
- Protection against radon or methane gas
- For structures in aggressive groundwater like coastal areas

MAIN ADVANTAGE

- Watertightness is controlled and secured at any time
- Highly crack bridging
- Easily repaired in case of leaks due to direct access of compartment
- Secure full protection of concrete

TYPICAL PROJECTS

- Underground car parks
- All types of buildings residential, commercial, Public etc.)
- Industrial facilities
- Containment areas
- Civil engineering structures
 - (e.g. Metro stations)

SIKA PRODUCTS AND SYSTEM SOLUTIONS

Sikaplan® WP 1120	Homogeneous and plasticized PVC sheet waterproofing mem- branes and gas-tight barriers for general use, loose laid with the membrane overlaps connected by heat welding.	
Sika® Waterbars	Cast-in-place external waterstops, based on PVC, connected with sheet waterproofing membranes by heat welding, for compartmentalized waterproofing systems.	
Control- and Injection Sockets	Preformed pieces based on PVC, connected with flexible injec- tion pipes to allow access to compartments for the control of watertightness and injection in the event of leaks.	
Complementary sealing s	ystem solutions:	
Sikaplan® WP Tape-200	Unique modified PVC Tape with excellent adhesion proper- ties, to bond and terminate membranes at concrete and steel surfaces	
Sika® Dilatec E/ER	Adhesive sealing tapes based on plasticized PVC, compatible to Sikaplan WP sheet membranes for water proofing termina- tions of post applied compartment systems.	

BASEMENT WATERPROOFING SOLUTIONS

An overview and selection guide for new constructions

Igolflex[®] R / SikaTop[®]



Bitumen coating / Cementitious coating

Sika White Box



Watertight Concrete

Waterproofing Concept / Strategy	Externally applied	Integral	
Grade of watertightness	Grades 1-2	Grades 1 - 3 Low	
Concrete protection	Limited		
Water resistance level	 Seepage / percolating water Rising capillary water 	 High hydrostatic pressure Seepage / percolating water Rising capillary water 	
Performance characteristics	Crack-bridging: + Water vapour tighness: + Chemical resistance: + Gas barrier: + Durability: +	Crack-bridging: n.a. Water vapour tighness: + Chemical resistance: + Gas barrier: + Durability: ++	
Safety level / Reliability	Low	Low to medium	
Excavation method	Only open excavation	Open excavation and piled walls	
Repair in the event of leaks	By crack or area injection	By local injection of limited areas. Damage is easy to locate	
Conditions of application	 Controlled conditions required (temperature, water, humidity) Substrate preparation required 	 Limited to suitable temperatures for concreting works. No substrate preparation required 	
Advantages	 Very cost effective Simple & fast to application 	 Very cost effective No protection required (walls) Simple & fast construction High durability 	

Technology / Type of system

SikaBit[®] W-15

_



SikaProof®



Wet bonded Sheet membrane

Fully bonded Sheet Membrane

Sikaplan°



Compartmentalized Membrane System with integrated control- and Injection back-up

Externally applied		Externally applied	Externally applied
Grades 1–3		Grades 1–3 plus additional requirements	Grades 1–3 plus additional requirements
High		- High	Very high
 Medium hydrostatic pressure Seepage / percolating water Rising capillary water 		 High hydrostatic pressure Seepage / percolating water Rising capillary water 	 Very high hydrostatic pressure Seepage / percolating water Rising capillary water
Crack-bridging: Water vapour tighness: Chemical resistance: Gas barrier: Durability:	+++ ++ ++ + +	Crack-bridging:++Water vapour tighness:++Chemical resistance:++Gas barrier:++Durability:++	Crack-bridging:+++Water vapour tighness:+++Chemical resistance:+++Gas barrier:+++Durability:+++
Medium		Medium to high	Very high
Open excavation and pil	ed walls	Open excavation and piled walls	Open excavation and piled walls
By crack injection		By crack injection	By injection of leaking compartments trough integrated back-up system. Easy to control and locate due to control sockets or active control system. Re-injection possible.
 Controlled conditions required (temperature, water, humidity) Minimal substrate preparation Membrane to be protected before back- filling 		 Controlled conditions required (temperature, water, humidity). Substrate preparation required Limited exposure time before concreting Membrane to be cleaned before concreting 	 Substrate preparation required
 Cost effective High performance Easy application Low risk High durability 		 Highly efficient High performance Easy to apply Low risk High durability 	 High waterproofing security Very high performance Simple and fast to repair High durability / reliability Integrated system redundancy

REPAIR AND REFURBISHMENT SOLUTIONS





SIKA INJECTION SOLUTIONS FOR REPAIR AND REFURBISHMENT WORKS

In situations with water ingress due to localised damage of the waterproofing system, appropriate repairs to seal the leaking areas have to be undertaken. These can often only be done by injection, because of inadequate access to the waterproofing system itself in most basements and below ground structures.

According to the type of damage / leakage (i.e. through joints, cracks or honeycombed areas, etc.) and the waterproofing requirements, the right materials have to be used. Successful and durable repairs by injection are ensured by the combination of Sika's expert diagnosis, using Sika materials and recommended equipment, plus Sika trained installers.

USE

Sealing and repairing of:

- Cracks
- All types of joints
- Sikaplan compartments
 Sealing of leaking areas by curtain injections

MAIN ADVANTAGE

- No excavation necessary
- Localised repair works
- Durable repairs

TYPICAL PROJECTS

- Suitable for all types of basements and civil engineering projects including structural waterproofing
- SIKA PRODUCTS AND SYSTEM SOLUTIONS

Sika® Injection-101 RC	Solvent-free, 2-component, fast foaming polyurethane (PUR) foam for temporary water-stopping of high water intrusions through cracks, joints and cavities in concrete.
Sika® Injection-107	Solvent-free, 1-component, foaming polyurethane (PUR) foam for temporary and permanent water-stopping of water intrusions through cracks, joints and cavities in concrete.
Sika® Injection-201 CE	Elastic, solvent-free PUR-Injection resin for permanent seal- ing of dry, damp or water-bearing cracks and joints in con- crete.
Sika® Injection-304	Very fast reacting, elastic, very low viscous polyacrylic injec- tion resin for curtain injection, to be applied by 2-component pump.
Sika® Injection-306	Elastic, very low viscous polyacrylic injection resin for the repair of damaged waterproofing membrane compartments and injection of SikaFuko injection hoses. It can also be used for permanent sealing of water-bearing cracks, voids and joints in concrete.
Sikadur [®] -52 MY	High-strength, low viscosity epoxy resin for structural bond- ing and sealing of dry cracks.

PROJECT REFERENCES

MASJID SRI SENDAYAN, NEGERI SEMBILAN



This mosque is an iconic building that is owned and developed by Rashid Hussein, the founder of RHB Bank Berhad. The ground floor moisture barrier is absolutely critical due to the expensive finishes, so SikaBit[®] W-15 was chosen as the moisture barrier to be laid on the ground level and the vertical surface of the ground beam.

- SikaBit® W-15
- SikaBit[®] W-1
- Sika[®] SealTape-S
- Sika® Primer-11 WMY
- Sikalastic[®]-1 KMY
- SikaTop® Seal-109 MY
- Sikalastic[®]-110 Sika Reemat
- Sika® WT-220 PMY

PAR3 CONDOMINIUM, IOI RESORT CITY, PUTRAJAYA



This condominium is built on a slope with the basements partially underground, the entire retaining wall is waterproofed using SikaBit® W-15, a fully bonded modified bitumen membrane that does not allow water to travel laterally even if there is a puncture.

- SikaBit[®] W-15
- Sikalastic[®]-1 KMY
- SikaTop® Seal-107
- SikaTop® Seal-109 MY
- Sika[®] Blackseal-1500MY

PLAZA ARCADIA, DESA PARK CITY, KUALA LUMPUR



Plaza Arcadia Desa is a stylish mixed developments situated at the heart of Desa ParkCity in Kuala Lumpur. The entire basement slab and wall is waterproofed using SikaProof® A, an innovative system that prevents lateral water underflow and migration, and the grid-pattern within the membrane also creates "mini watertight compartments".

- SikaProof® A
- SikaTop® Seal-107
- SikaTop® Seal-109 MY
- Sika[®] Hydrotite CJ-Type
- SikaSwell[®] S-2
- Sikalastic®-612

FOREST CITY SALES GALLERY, JOHOR BAHRU



This mega project is the joint venture between China and Malaysia that is situated on four reclaimed islands strategically located adjacent to Singapore. The entire podium and driveway of the sales gallery on top of the sub-basement car park is waterproofed with SikaBit® W-15.

- SikaBit® W-15
- Igolflex[®] R
- Sikalastic®-612

IKEA TEBRAU, JOHOR BAHRU



This flagship outlet is the fourth in Malaysia by the Scandinavian furniture giant. Sika has been able to provide reliable and complete waterproofing solutions from basement to roof for their Damansara store, Cochrain store and now Tebrau store.

- Sika® WT-220 PMY
- Sarnafil[®] S 327 EL

I CITY PLAZA AND TOWER, SHAH ALAM



iCity is a smart city development envisions a sustainable eco-friendly, technologically advanced urban settlements that would provide Citizens with the high standards of living, better governance, quality infrastructure, and uninterrupted utility and social services. The entire basement concrete was waterproofed using Sika[®] WT-220 PMY, a water resisting and crystalline admixture.

- Sika® WT-220 PMY
- Sika[®] Waterbars
- Sika[®] Hydrotite CJ-Type
- SikaSwell[®] S-2
- Igolflex® R

SEPANGGAR PORT TUNNEL, KOTA KINABALU, SABAH



The tunnel is constructed combining environmentally friendly and high technology methods that is expected to set the standard for future road construction in the state. Sikaplan[®] PVC membrane was selected for its durability and reliability.

MRT SEMANTAN CROSS PASSAGE, KUALA LUMPUR



The cross passage is the link between two MRT tunnels. Sika provided the complete products range and solutions for the waterproofing, Sikaplan[®] PVC membrane being the main element.

■ Sikaplan® WP 1120

- Sikaplan[®] WP 1120
- Sika[®] Waterbars
- Dilatec
- SikaFuko®
- SikaSwell®

GLOBAL BUT LOCAL PARTNERSHIP



WE ARE SIKA

Sika is a specialty chemicals company with a leading position in the development and production of systems and products for bonding, sealing, damping, reinforcing and protecting in the building sector and the motor vehicle industry. Sika's product lines feature concrete admixtures, mortars, sealants and adhesives, structural strengthening systems, flooring as well as roofing and waterproofing systems.

Our most current General Sales Conditions shall apply. Please consult the Data Sheet prior to any use and processing.



SIKA KIMIA SDN BHD

No. 9, Jalan Timur, 46000 Petaling Jaya, Selangor DE, Malaysia

Contact

Phone +603 7957 0111 Fax +603 7956 7291 www.sika.com.my

BUILDING TRUST