SikaCor® VEMY Hardener Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.02.2019

 5.0
 23.04.2021
 000000612751
 Date of first issue: 20.03.2015

SECTION 1: Identification of the hazardous chemical and of the supplier

Product identifier

Product name : SikaCor® VEMY Hardener Part B

Product code : 000000612751

Manufacturer or supplier's details

Company : Sika Kimia Sdn. Bhd.

Lot 689 Nilai Industrial Estate

71800 Nilai

 Telephone
 : +60 6799 1762

 Telefax
 : +60 6799 1980

 E-mail address
 : EHS@my.sika.com

Emergency telephone num-

ber

SECTION 2: Hazards identification

Classification of the hazardous chemical

Acute toxicity (Oral) : Category 4

Skin corrosion/irritation : Category 1B

Serious eye damage/eye irri-

tation

Category 1

Label elements

Hazard pictograms :





Signal word : Danger

Hazard statements : H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

Precautionary statements : Prevention:

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT

induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/

SikaCor® VEMY Hardener Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.02.2019

 5.0
 23.04.2021
 000000612751
 Date of first issue: 20.03.2015

shower.

P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Imme-

diately call a POISON CENTER or doctor/ physician.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER or doctor/ physician.

Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
dimethyl phthalate	131-11-3	>= 60 -<= 100
2-Butanone, peroxide	1338-23-4	>= 30 -< 60
butanone	78-93-3	>= 3 -< 5

SECTION 4: First aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

SikaCor® VEMY Hardener Part B



SDS Number: Version Revision Date: Date of last issue: 08.02.2019 000000612751 Date of first issue: 20.03.2015 23.04.2021 5.0

Most important symptoms

and effects, both acute and

delayed

Health injuries may be delayed.

corrosive effects

Gastrointestinal discomfort

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms. Harmful if swallowed.

Causes serious eye damage.

Causes severe burns.

Notes to physician Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Physicochemical hazards arising from the chemical

ucts

Hazardous combustion prod- : No hazardous combustion products are known

Special protective equipment and precautions for fire-fighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

SECTION 6: Accidental release measures

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage

Handling

Precautions for safe handling

SikaCor® VEMY Hardener Part B



Version Date of last issue: 08.02.2019 **Revision Date:** SDS Number: 23.04.2021 000000612751 Date of first issue: 20.03.2015 5.0

fire and explosion

Advice on protection against : Normal measures for preventive fire protection.

Advice on safe handling Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Storage

Conditions for safe storage, including any incompatibilities

Conditions for safe storage Store in original container.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

SECTION 8: Exposure controls and personal protection

Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
dimethyl phthalate	131-11-3	TWA	5 mg/m3	MY PEL
		TWA	5 mg/m3	ACGIH
2-Butanone, peroxide	1338-23-4	CEIL	0.2 ppm 1.5 mg/m3	MY PEL
		С	0.2 ppm	ACGIH
butanone	78-93-3	TWA	200 ppm 590 mg/m3	MY PEL
		TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
butanone	78-93-3	methyl ethyl	Urine	End of	2 mg/l	ACGIH
		ketone		shift (As	_	BEI
				soon as		
				possible		
				after ex-		
				posure		
				ceases)		

Individual protection measures, such as personal protective equipment

SikaCor® VEMY Hardener Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.02.2019

 5.0
 23.04.2021
 000000612751
 Date of first issue: 20.03.2015

Eye/face protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

Appearance : liquid

Colour : colourless

Odour : very faint

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

point

No data available

Decomposition

Flash point : $> 93.3 \,^{\circ}\text{C} \, (199.9 \,^{\circ}\text{F})$

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

SikaCor® VEMY Hardener Part B



Date of last issue: 08.02.2019 Version **Revision Date:** SDS Number: 23.04.2021 000000612751 Date of first issue: 20.03.2015 5.0

Lower explosion limit / Lower : No data available

flammability limit

Vapour pressure 0.01 hPa

Relative vapour density No data available

1.18 g/cm3 (20 °C (68 °F)) Density

Solubility(ies)

Water solubility partly miscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature No data available

Decomposition temperature No data available

Self-Accelerating decomposi- :

tion temperature (SADT)

60 °C (140 °F)

Viscosity

Viscosity, dynamic 24 mPa.s (20 °C (68 °F))

Viscosity, kinematic 13.33 mm2/s (20 °C (68 °F))

Explosive properties No data available

Oxidizing properties No data available

Peroxide content 30 - 37 % Available oxygen content 8.8 - 9 %

SECTION 10: Stability and reactivity

Reactivity No dangerous reaction known under conditions of normal use.

Chemical stability The product is chemically stable.

Possibility of hazardous reac- :

Stable under recommended storage conditions.

Conditions to avoid Avoid storage temperature > 25°C.

No data available

Incompatible materials No data available

> Iron Copper Rust

SikaCor® VEMY Hardener Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.02.2019

 5.0
 23.04.2021
 000000612751
 Date of first issue: 20.03.2015

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Information on likely routes of : None known.

exposure

Acute toxicity

Harmful if swallowed.

Components:

butanone:

Acute oral toxicity : LD50 Oral (Rat): 3,300 mg/kg

Acute inhalation toxicity : LC50 (Rat): 36 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SikaCor® VEMY Hardener Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.02.2019

 5.0
 23.04.2021
 000000612751
 Date of first issue: 20.03.2015

SECTION 12: Ecological information

Ecotoxicity

Product:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): , 420 parts per

million

Exposure time: 96 h

The value is given in analogy to the following substances:

dimethyl phthalate

LC50 (Poecilia reticulata (guppy)): 44 mg/l

Exposure time: 96 h

The value is given in analogy to the following substances: 2-

Butanone, peroxide

LC50 (Lepomis macrochirus (Bluegill sunfish)): 3.22 mg/l

Exposure time: 96 h

The value is given in analogy to the following substances:

butanone

Toxicity to algae/aquatic

plants

IC50 (Selenastrum capricornutum (green algae)): 39.8 mg/l

Exposure time: 96 h

The value is given in analogy to the following substances:

dimethyl phthalate

Toxicity to microorganisms : EC50 (Bacteria): 48 mg/l

Test Type: Respiration inhibition

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

: There is no data available for this product.

mation

SECTION 13: Disposal information

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

SikaCor® VEMY Hardener Part B



Revision Date: SDS Number: Version Date of last issue: 08.02.2019 23.04.2021 000000612751 5.0 Date of first issue: 20.03.2015

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

> Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

International Regulations

UNRTDG

UN number : UN 3105

Proper shipping name : ORGANIC PEROXIDE TYPE D, LIQUID

Class

Packing group : Not assigned by regulation

Labels 5.2

IATA-DGR

UN/ID No. UN 3105

Proper shipping name Organic peroxide type D, liquid

Class 5.2

Packing group Not assigned by regulation

Organic Peroxides, Keep Away From Heat Labels

570

Packing instruction (cargo

aircraft)

Packing instruction (passen-

570

ger aircraft)

IMDG-Code

UN number UN 3105

ORGANIC PEROXIDE TYPE D, LIQUID Proper shipping name

Class 5.2

Packing group : Not assigned by regulation

Labels : 5.2 EmS Code F-J, S-R Marine pollutant ves

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

SikaCor® VEMY Hardener Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.02.2019

 5.0
 23.04.2021
 000000612751
 Date of first issue: 20.03.2015

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

SECTION 16: Other information

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)

MY PEL : Malaysia. Occupational Safety and Health (Use and Stand-

ards of Exposure of Chemicals Hazardous to Health) Regula-

tions 2000.

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

ACGIH / C : Ceiling limit

MY PEL / TWA : Eight-hour time-weighted average airborne concentration

MY PEL / CEIL : Ceiling limit airborne concentration

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road Chemical Abstracts Service

CAS : Chemical Abstracts Ser
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

SikaCor® VEMY Hardener Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 08.02.2019

 5.0
 23.04.2021
 000000612751
 Date of first issue: 20.03.2015

Changes as compared to previous version!

MY / EN