

# SAFETY DATA SHEET

## Sikadur®-52 LVMY Part B



Version  
4.0

Revision Date:  
23.04.2021

SDS Number:  
000000610916

Date of last issue: 19.03.2021  
Date of first issue: 18.03.2015

### SECTION 1: Identification of the hazardous chemical and of the supplier

#### Product identifier

Product name : Sikadur®-52 LVMY Part B

Product code : 000000610916

#### Manufacturer or supplier's details

Company : Sika Kimia Sdn. Bhd.  
Lot 689 Nilai Industrial Estate  
71800 Nilai  
Telephone : +60 6799 1762  
Telefax : +60 6799 1980  
E-mail address : EHS@my.sika.com  
Emergency telephone number : -

### SECTION 2: Hazards identification

#### Classification of the hazardous chemical

Skin corrosion/irritation : Category 1

Serious eye damage/eye irritation : Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Aspiration hazard : Category 1

Hazardous to the aquatic environment - chronic hazard : Category 2

#### Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H304 May be fatal if swallowed and enters airways.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H411 Toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

## Sikadur®-52 LVMY Part B



Version  
4.0

Revision Date:  
23.04.2021

SDS Number:  
000000610916

Date of last issue: 19.03.2021  
Date of first issue: 18.03.2015

Precautionary statements

:

### Prevention:

P264 Wash skin thoroughly after handling.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P281 Use personal protective equipment as required.

### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.  
P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/ physician.  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.  
P391 Collect spillage.

### Other hazards which do not result in classification

None known.

## SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C10-C13, aromatic, >1% Naphthalene	64742-94-5	>= 30 -< 60
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	>= 10 -< 25
3,6-diazaoctanethylenediamin	112-24-3	>= 10 -< 25
benzyl alcohol	100-51-6	>= 10 -< 30
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	>= 5 -< 10
naphthalene	91-20-3	>= 3 -< 5
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	25068-38-6	>= 3 -< 5
bis[(dimethylamino)methyl]phenol	71074-89-0	>= 1 -< 3

## SECTION 4: First aid measures

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.

# SAFETY DATA SHEET

## Sikadur®-52 LVMY Part B



Version  
4.0

Revision Date:  
23.04.2021

SDS Number:  
000000610916

Date of last issue: 19.03.2021  
Date of first issue: 18.03.2015

---

- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Health injuries may be delayed.  
Risk of serious damage to the lungs (by aspiration).  
corrosive effects  
sensitising effects  
Aspiration may cause pulmonary oedema and pneumonitis.  
Allergic reactions  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.  
May be fatal if swallowed and enters airways.  
May cause an allergic skin reaction.  
Causes serious eye damage.  
Suspected of causing cancer.  
Causes severe burns.
- Notes to physician : Treat symptomatically.
- 

### SECTION 5: Firefighting measures

#### Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### Physicochemical hazards arising from the chemical

- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

# SAFETY DATA SHEET

## Sikadur®-52 LVMY Part B



Version  
4.0

Revision Date:  
23.04.2021

SDS Number:  
000000610916

Date of last issue: 19.03.2021  
Date of first issue: 18.03.2015

---

Hazardous combustion products : No hazardous combustion products are known

### Special protective equipment and precautions for fire-fighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

### SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

---

### SECTION 7: Handling and storage

#### Handling

#### Precautions for safe handling

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products

# SAFETY DATA SHEET

## Sikadur®-52 LVMY Part B



Version  
4.0

Revision Date:  
23.04.2021

SDS Number:  
000000610916

Date of last issue: 19.03.2021  
Date of first issue: 18.03.2015

### Storage

#### Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Store in original container.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.

## SECTION 8: Exposure controls and personal protection

### Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
naphthalene	91-20-3	TWA	10 ppm 52 mg/m <sup>3</sup>	MY PEL
		TWA	10 ppm	ACGIH

### Individual protection measures, such as personal protective equipment

- Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

## SECTION 9: Physical and chemical properties

# SAFETY DATA SHEET

## Sikadur®-52 LVMY Part B



Version  
4.0

Revision Date:  
23.04.2021

SDS Number:  
000000610916

Date of last issue: 19.03.2021  
Date of first issue: 18.03.2015

---

Appearance : liquid

Colour : brown

Odour : amine-like

Odour Threshold : No data available

pH : 11.9

Melting point/range / Freezing point : No data available  
: Not applicable

Flash point : > 93.3 °C (> 199.9 °F)  
(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : 2 hPa

Relative vapour density : No data available

Density : 0.97 g/cm<sup>3</sup> (20 °C (68 °F))

Solubility(ies)

    Water solubility : No data available

    Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

    Viscosity, dynamic : No data available

    Viscosity, kinematic : > 7 mm<sup>2</sup>/s ( 40 °C (104 °F))

Explosive properties : No data available

Oxidizing properties : No data available

# SAFETY DATA SHEET

## Sikadur®-52 LVMY Part B



Version  
4.0

Revision Date:  
23.04.2021

SDS Number:  
000000610916

Date of last issue: 19.03.2021  
Date of first issue: 18.03.2015

---

### SECTION 10: Stability and reactivity

- Reactivity : No dangerous reaction known under conditions of normal use.
- Chemical stability : The product is chemically stable.
- Possibility of hazardous reactions : Stable under recommended storage conditions.
- Conditions to avoid : No data available
- Incompatible materials : No data available
- No decomposition if stored and applied as directed.

---

### SECTION 11: Toxicological information

Information on likely routes of exposure : None known.

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Acute oral toxicity : LD50 Oral (Rat): 1,030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.01 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

##### **3,6-diazaoctanethylenediamin:**

Acute oral toxicity : LD50 Oral (Rat): 1,716 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,465 mg/kg

##### **benzyl alcohol:**

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### **2,4,6-tris(dimethylaminomethyl)phenol:**

Acute oral toxicity : LD50 Oral (Rat): 2,169 mg/kg

##### **reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

# SAFETY DATA SHEET

## Sikadur®-52 LVMY Part B



Version  
4.0

Revision Date:  
23.04.2021

SDS Number:  
000000610916

Date of last issue: 19.03.2021  
Date of first issue: 18.03.2015

---

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

### **Skin corrosion/irritation**

Causes severe burns.

#### **Components:**

##### **2,4,6-tris(dimethylaminomethyl)phenol:**

Species : Rabbit  
Assessment : Corrosive  
Method : OECD Test Guideline 404

### **Serious eye damage/eye irritation**

Causes serious eye damage.

#### **Components:**

##### **2,4,6-tris(dimethylaminomethyl)phenol:**

Species : Rabbit  
Assessment : Causes serious eye damage.

### **Respiratory or skin sensitisation**

#### **Skin sensitisation**

May cause an allergic skin reaction.

#### **Respiratory sensitisation**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Suspected of causing cancer.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT - single exposure**

Not classified based on available information.

#### **STOT - repeated exposure**

Not classified based on available information.

#### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

---

## **SECTION 12: Ecological information**

### **Ecotoxicity**

#### **Components:**

##### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Toxicity to algae/aquatic : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100

---



# SAFETY DATA SHEET

## Sikadur®-52 LVMY Part B



Version  
4.0

Revision Date:  
23.04.2021

SDS Number:  
000000610916

Date of last issue: 19.03.2021  
Date of first issue: 18.03.2015

plants mg/l  
Exposure time: 72 h

### **3,6-diazaoctanethylenediamin:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 10 - 100 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): 10 -  
plants 100 mg/l  
Exposure time: 72 h

### **benzyl alcohol:**

Toxicity to fish : LC50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
aquatic invertebrates Exposure time: 48 h

### **2,4,6-tris(dimethylaminomethyl)phenol:**

Toxicity to algae/aquatic : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10  
plants - 100 mg/l  
Exposure time: 72 h

### **naphthalene:**

M-Factor (Acute aquatic tox- : 1  
icity)

M-Factor (Chronic aquatic : 1  
toxicity)

### **reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l  
aquatic invertebrates Exposure time: 48 h

### **Persistence and degradability**

No data available

### **Bioaccumulative potential**

No data available

### **Mobility in soil**

No data available

### **Other adverse effects**

### **Product:**

Additional ecological infor- : An environmental hazard cannot be excluded in the event of  
mation unprofessional handling or disposal.

# SAFETY DATA SHEET

## Sikadur®-52 LVMY Part B



Version  
4.0

Revision Date:  
23.04.2021

SDS Number:  
000000610916

Date of last issue: 19.03.2021  
Date of first issue: 18.03.2015

Toxic to aquatic life with long lasting effects.

---

### SECTION 13: Disposal information

#### Disposal methods

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

---

### SECTION 14: Transport information

#### International Regulations

##### UNRTDG

- UN number : UN 2735  
Proper shipping name : POLYAMINES, LIQUID, CORROSIVE, N.O.S.  
Class : 8  
Packing group : III  
Labels : 8

##### IATA-DGR

- UN/ID No. : UN 2735  
Proper shipping name : Polyamines, liquid, corrosive, n.o.s.  
Class : 8  
Packing group : III  
Labels : Corrosive  
Packing instruction (cargo aircraft) : 856  
Packing instruction (passenger aircraft) : 852

##### IMDG-Code

- UN number : UN 2735  
Proper shipping name : POLYAMINES, LIQUID, CORROSIVE, N.O.S.  
Class : 8  
Packing group : III  
Labels : 8  
EmS Code : F-A, S-B  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# SAFETY DATA SHEET

## Sikadur®-52 LVMY Part B



Version  
4.0

Revision Date:  
23.04.2021

SDS Number:  
000000610916

Date of last issue: 19.03.2021  
Date of first issue: 18.03.2015

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### SECTION 15: Regulatory information

#### Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

### SECTION 16: Other information

Date format : dd.mm.yyyy

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
MY PEL : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.  
ACGIH / TWA : 8-hour, time-weighted average  
MY PEL / TWA : Eight-hour time-weighted average airborne concentration  
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road  
CAS : Chemical Abstracts Service  
DNEL : Derived no-effect level  
EC50 : Half maximal effective concentration  
GHS : Globally Harmonized System  
IATA : International Air Transport Association  
IMDG : International Maritime Code for Dangerous Goods  
LD50 : Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)  
LC50 : Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)  
MARPOL : International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978  
OEL : Occupational Exposure Limit  
PBT : Persistent, bioaccumulative and toxic  
PNEC : Predicted no effect concentration  
REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

# SAFETY DATA SHEET

## Sikadur®-52 LVMY Part B



Version  
4.0

Revision Date:  
23.04.2021

SDS Number:  
000000610916

Date of last issue: 19.03.2021  
Date of first issue: 18.03.2015

---

SVHC : Substances of Very High Concern  
vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

MY / EN