

PRODUCT DATA SHEET

SikaLatex®-98

Additive for cement-sand slurry and cement-based tile adhesive

DESCRIPTION

SikaLatex®-98 is a flexible polymer additive designed for use with SikaCeram® cement-based tile adhesives, ideal for fixing ceramic tiles, marble and natural stones onto concrete, cement render, rendered brickwork surfaces or over existing tiles.

USES

- When mixed with SikaCeram® cement-based tile adhesives, it can be used for fixing ceramic tiles, pavers, marble, slate and natural stones onto concrete, cement render, blockwork, rendered brickwork surfaces or over existing tiles, for wet area eg. bathroom, kitchens, swimming pools and spas.
- When mixed with neat cement and sand, it can be used as a bonding slurry for cement-sand render over uneven concrete.

CHARACTERISTICS / ADVANTAGES

- Increased shear bond strength – when added to SikaCeram® cement-based tile adhesives
- Increased tile bedding strength – especially for heavy stones and large format tiles
- Increased flexibility of the adhesive system to cater for movement
- Improve bond strength of renders/screed to cementitious substrate – when used as a bonding slurry

PRODUCT INFORMATION

Packaging	20 L pail
Appearance / Colour	Milky white liquid
Shelf Life	12 months from date of production
Storage Conditions	Store properly in original, unopened and undamaged packaging in dry conditions. Keep away from direct sunlight.
pH-Value	9 ± 1

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety

Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations

the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Kimia Sdn. Bhd.

Lot 689, Nilai Industrial Estate,
71800 Nilai, Negeri Sembilan D.K.
Malaysia
Phone: +606-7991762
e-mail: info@my.sika.com
Website: www.sika.com.my



Product Data Sheet

SikaLatex®-98

May 2026, Version 01.01
020301010010263827

SikaLatex-98-en-MY-(05-2026)-1-1.pdf

