# SikaWall®-192 Finish Grey



SDS Number: Date of last issue: 20.04.2020 Version Revision Date: 000000606602 Date of first issue: 13.03.2015 26.08.2020 5.0

## SECTION 1: Identification of the hazardous chemical and of the supplier

**Product identifier** 

Product name SikaWall®-192 Finish Grey

Product code 000000606602

Manufacturer or supplier's details

Company : Sika Kimia Sdn. Bhd.

Lot 689 Nilai Industrial Estate

71800 Nilai

Telephone : +60 6799 1762 Telefax +60 6799 1980 E-mail address EHS@my.sika.com

Emergency telephone num-

## **SECTION 2: Hazards identification**

### Classification of the hazardous chemical

Skin corrosion/irritation Category 2

Serious eye damage/eye irri-

Category 1

tation

Skin sensitisation : Category 1

single exposure

Specific target organ toxicity - : Category 3 (Respiratory system)

#### Label elements

Hazard pictograms





Signal word Danger

Hazard statements H315 Causes skin irritation.

> H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation.

Precautionary statements Prevention:

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

# SikaWall®-192 Finish Grey



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 20.04.2020

 5.0
 26.08.2020
 00000060602
 Date of first issue: 13.03.2015

#### Response:

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with

water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER or doctor/ physician.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

#### Other hazards which do not result in classification

None known.

#### SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)	
Cement, portland, chemicals	65997-15-1	>= 30 -< 60	

## **SECTION 4: First aid measures**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms

and effects, both acute and delayed

irritant effects sensitising effects

Cough

# SikaWall®-192 Finish Grey



Date of last issue: 20.04.2020 Version Revision Date: SDS Number: 000000606602 Date of first issue: 13.03.2015 5.0 26.08.2020

> Respiratory disorder Allergic reactions **Excessive lachrymation**

**Dermatitis** 

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation.

Notes to physician Treat symptomatically.

## **SECTION 5: Firefighting measures**

Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Physicochemical hazards arising from the chemical

ucts

Hazardous combustion prod- : No hazardous combustion products are known

Special protective equipment and precautions for fire-fighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

# **SECTION 6: Accidental release measures**

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

**Environmental precautions** Do not flush into surface water or sanitary sewer system.

Methods and materials for

containment and cleaning up

Pick up and arrange disposal without creating dust. Keep in suitable, closed containers for disposal.

#### **SECTION 7: Handling and storage**

## Handling

### Precautions for safe handling

Advice on protection against : Avoid dust formation.

# SikaWall®-192 Finish Grey



Date of last issue: 20.04.2020 Version Revision Date: SDS Number: 26.08.2020 000000606602 Date of first issue: 13.03.2015 5.0

Provide appropriate exhaust ventilation at places where dust fire and explosion

is formed.

Advice on safe handling Do not breathe vapours/dust.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

### Storage

#### Conditions for safe storage, including any incompatibilities

Conditions for safe storage Store in original container.

Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

Further information on stor-

Keep in a dry place.

No decomposition if stored and applied as directed. age stability

# **SECTION 8: Exposure controls and personal protection**

## **Control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Cement, portland, chemicals	65997-15-1	TWA	10 mg/m3	MY PEL
		PEL (Respir- able dust)	5 mg/m3	MY PEL
		PEL (Total dust)	10 mg/m3	MY PEL
		TWA (Res- pirable par- ticulate mat- ter)	1 mg/m3	ACGIH

#### Individual protection measures, such as personal protective equipment

Eye/face protection Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin protection Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

# SikaWall®-192 Finish Grey



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 20.04.2020

 5.0
 26.08.2020
 00000060602
 Date of first issue: 13.03.2015

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9: Physical and chemical properties**

Appearance : powder

Colour : grey

Odour : odourless

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

oint

No data available

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : No data available

Bulk density Solubility(ies) 1,000 kg/m3

# SikaWall®-192 Finish Grey



Date of last issue: 20.04.2020 Version Revision Date: SDS Number: 26.08.2020 000000606602 Date of first issue: 13.03.2015 5.0

No data available

soluble Water solubility

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

Auto-ignition temperature

No data available

Decomposition temperature No data available

Viscosity

Viscosity, dynamic No data available

Viscosity, kinematic Not applicable

Explosive properties No data available

Oxidizing properties No data available

## **SECTION 10: Stability and reactivity**

No dangerous reaction known under conditions of normal use. Reactivity

Chemical stability The product is chemically stable.

Possibility of hazardous reac- :

tions

No hazards to be specially mentioned.

Conditions to avoid No data available

Incompatible materials No data available

No decomposition if stored and applied as directed.

# **SECTION 11: Toxicological information**

Information on likely routes of : None known.

exposure

**Acute toxicity** 

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

# SikaWall®-192 Finish Grey



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 20.04.2020

 5.0
 26.08.2020
 00000060602
 Date of first issue: 13.03.2015

#### Respiratory sensitisation

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

# Carcinogenicity

Not classified based on available information.

## Reproductive toxicity

Not classified based on available information.

## STOT - single exposure

May cause respiratory irritation.

## STOT - repeated exposure

Not classified based on available information.

#### **Aspiration toxicity**

Not classified based on available information.

#### **SECTION 12: Ecological information**

## **Ecotoxicity**

No data available

# Persistence and degradability

No data available

## Bioaccumulative potential

No data available

## Mobility in soil

No data available

# Other adverse effects

#### **Product:**

Additional ecological infor-

mation

There is no data available for this product.

## **SECTION 13: Disposal information**

#### Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

# SikaWall®-192 Finish Grey



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 20.04.2020

 5.0
 26.08.2020
 00000060602
 Date of first issue: 13.03.2015

#### **SECTION 14: Transport information**

#### International Regulations

#### **UNRTDG**

Not regulated as a dangerous good

### **IATA-DGR**

Not regulated as a dangerous good

#### **IMDG-Code**

Not regulated as a dangerous good

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

# Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

## **SECTION 16: Other information**

Date format : dd.mm.yyyy

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

MY PEL : Malaysia. Occupational Safety and Health (Use and Stand-

ards of Exposure of Chemicals Hazardous to Health) Regula-

tions 2000.

MY PEL : Malaysia. Factories and Machinery (Mineral Dust) Regulations

- Permissible Exposure Limit

ACGIH / TWA : 8-hour, time-weighted average

MY PEL / TWA : Eight-hour time-weighted average airborne concentration

MY PEL / PEL : Permissible exposure limit (PEL)

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods
LD50 : Median lethal dosis (the amount of a material, given all at

# SikaWall®-192 Finish Grey



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 20.04.2020

 5.0
 26.08.2020
 00000060602
 Date of first issue: 13.03.2015

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

MY / EN