Sikalastic®-851 Part B



SECTION 1: Identification of the hazardous chemical and of the supplier

Product name : Sikalastic®-851 Part B

Product code : 000000133703

Type of product liquid

Recommended use of the chemical and restrictions on use

Product use : Sealing system

Manufacturer or supplier's details

Company : Sika Kimia Sdn. Bhd.

Lot 689 Nilai Industrial Estate

71800 Nilai

Telephone : +60 6799 1762 Telefax : +60 6799 1980 E-mail address : EHS@my.sika.com

Emergency telephone

number

Contact point

SECTION 2: Hazards identification

Classification of the hazardous chemical

Serious eye damage/eye

irritation

: Category 2

Specific target organ toxicity -

repeated exposure (Oral)

: Category 2

Hazardous to the aquatic

environment - chronic hazard

: Category 2

Label elements

Hazard pictograms







Signal word Warning

Hazard statements H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or

repeated exposure if swallowed.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P273 Avoid release to the environment. P280 Wear eye protection/ face protection.

Response:

P314 Get medical advice/ attention if you feel unwell. P337 + P313 If eye irritation persists: Get medical advice/

attention.

Sikalastic®-851 Part B



Version 1.1 SDS Number: 000000133703 Revision Date: 03.02.2020

P391 Collect spillage.

Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (%)
diethylmethylbenzenediamine	68479-98-1	>= 10 - < 25

SECTION 4: First aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person. : irritant effects

Most important symptoms and effects, both acute and

and effects, bot delayed

Excessive lachrymation

See Section 11 for more detailed information on health effects

and symptoms.

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated

exposure if swallowed.

Notes to physician : Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Physicochemical hazards arising from the chemical

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: No hazardous combustion products are known

Special protective equipment and precautions for fire-fighters

Sikalastic®-851 Part B

Version 1.1 SDS Number: 000000133703 Revision Date: 03.02.2020

Special protective equipment

for firefighters

Specific extinguishing

methods

: In the event of fire, wear self-contained breathing apparatus.

: Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage

Handling

Precautions for safe handling

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Follow standard hygiene measures when handling chemical

products

Storage

Conditions for safe storage, including any incompatibilities

Conditions for safe storage : I

: Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with local regulations.

SECTION 8: Exposure controls and personal protection

Control parameters

Contains no substances with occupational exposure limit values.

Individual protection measures, such as personal protective equipment

Sikalastic®-851 Part B



Version 1.1 SDS Number: 000000133703 Revision Date: 03.02.2020

Eye/face protection Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin protection Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

Respiratory protection Use respiratory protection unless adequate local exhaust

> ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hygiene measures Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

liquid Appearance Colour grey Odour slight

Odour Threshold No data available

Hq 8, (20 °C (68 °F)) : No data available

Melting point/range / Freezing

point

Boiling point/boiling range : No data available

Flash point : > 101 °C (214 °F)

Method: closed cup

Evaporation rate No data available

Flammability No data available

No data available Upper explosion limit

Lower explosion limit No data available

Vapour pressure 0.01 hPa (0.01 mmHg)

Relative vapour density No data available

Density : ca. 1.03 g/cm3 (20 °C (68 °F) ())

Solubility(ies)

Water solubility : insoluble

Sikalastic®-851 Part B

Version 1.1 SDS Number: 000000133703 Revision Date: 03.02.2020

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : ca. 2,170 mPa.s Viscosity, kinematic : > 20.5 mm2/s (40 °C)

Explosive properties : No data available

Molecular weight : No data available

SECTION 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous : Stable under recommended storage conditions.

reactions

Conditions to avoid : No data available Incompatible materials : No data available No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Information on likely routes of : None known.

exposure

Acute toxicity

Not classified based on available information.

Components:

diethylmethylbenzenediamine:

Acute oral toxicity : LD50 Oral (Rat): 738 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 2,500 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Sikalastic®-851 Part B



Version 1.1 SDS Number: 000000133703 Revision Date: 03.02.2020

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if swallowed.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal information

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

SECTION 14: Transport information

International Regulations

UNRTDG

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(diethylmethylbenzenediamine)

Class : 9 Packing group : III

Sikalastic®-851 Part B



Version 1.1 SDS Number: 000000133703 Revision Date: 03.02.2020

Labels : 9

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(diethylmethylbenzenediamine)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo

aircraft)

Packing instruction : 964

(passenger aircraft)

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

964

(diethylmethylbenzenediamine)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

SECTION 16: Other information

Date format : dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!