
# Sikafloor®-80 EpoCem® Primer Part B



## SECTION 1: Identification of the hazardous chemical and of the supplier

Product name : Sikafloor®-80 EpoCem® Primer Part B

Product code : 000000020259

Type of product : liquid

#### Recommended use of the chemical and restrictions on use

Product use : Special system, Product is not intended for consumer use

## Manufacturer or supplier's details

Company : Sika Kimia Sdn. Bhd.

Lot 689 Nilai Industrial Estate

71800 Nilai

 Telephone
 : +60 6799 1762

 Telefax
 : +60 6799 1980

 E-mail address
 : EHS@my.sika.com

Emergency telephone

number

Contact point :

#### **SECTION 2: Hazards identification**

#### Classification of the hazardous chemical

Skin corrosion/irritation : Category 2

Serious eye damage/eye

irritation

: Category 2

Skin sensitisation : Category 1

Label elements

Hazard pictograms

Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

Precautionary statements : **Prevention:** 

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P280 Wear protective gloves/ eye protection/ face protection.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P362 Take off contaminated clothing and wash before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste

## Sikafloor®-80 EpoCem® Primer Part B



Version 3.1 SDS Number: 000000020259 Revision Date: 11.05.2020

disposal plant.

#### Other hazards which do not result in classification

None known.

#### SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

### **Hazardous components**

Chemical name	CAS-No.	Concentration (%)
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	>= 1 - < 2.5

#### **SECTION 4: First aid measures**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms

and effects, both acute and

delayed

: irritant effects

sensitising effects Allergic reactions

Excessive lachrymation

**Dermatitis** 

See Section 11 for more detailed information on health effects

and symptoms.
Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Notes to physician : Treat symptomatically.

#### **SECTION 5: Firefighting measures**

#### **Extinguishing media**

Suitable extinguishing media : Carbon dioxide (CO2)

Unsuitable extinguishing

: Water

media

## Physicochemical hazards arising from the chemical

Hazardous combustion

products

: No hazardous combustion products are known

# Sikafloor®-80 EpoCem® Primer Part B



Version 3.1 SDS Number: 000000020259 Revision Date: 11.05.2020

#### Special protective equipment and precautions for fire-fighters

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing

methods

: Standard procedure for chemical fires.

### **SECTION 6: Accidental release measures**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### **SECTION 7: Handling and storage**

#### Handling

#### Precautions for safe handling

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is

being used.

Smoking, eating and drinking should be prohibited in the

application area.

Follow standard hygiene measures when handling chemical

products

## **Storage**

### Conditions for safe storage, including any incompatibilities

Conditions for safe storage

: Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

## Sikafloor®-80 EpoCem® Primer Part B



Version 3.1 SDS Number: 000000020259 Revision Date: 11.05.2020

#### **SECTION 8: Exposure controls and personal protection**

#### Control parameters

Contains no substances with occupational exposure limit values.

## Individual protection measures, such as personal protective equipment

Eye/face protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin protection Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

Respiratory protection : Use respiratory protection unless adequate local exhaust

> ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the

maximum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Handle in accordance with good industrial hygiene and safety Hygiene measures

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

## **SECTION 9: Physical and chemical properties**

Appearance liquid Colour white amine-like Odour

Odour Threshold No data available

pΗ ca. 11

Melting point/range / Freezing

point

No data available

Boiling point/boiling range : No data available

: 72 °C (162 °F) Flash point

Method: closed cup

Evaporation rate : No data available

Flammability No data available

Upper explosion limit No data available

Lower explosion limit No data available

23 hPa (17 mmHg) Vapour pressure

: No data available Relative vapour density

# Sikafloor®-80 EpoCem® Primer Part B

Version 3.1 SDS Number: 000000020259 Revision Date: 11.05.2020

Density : ca. 1.03 g/cm3 (20 °C (68 °F) ())

Solubility(ies)

Water solubility : soluble

Partition coefficient: n- : No data available

octanol/water

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm2/s (40 °C)

Explosive properties : No data available

Molecular weight : No data available

#### **SECTION 10: Stability and reactivity**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous : Stable under recommended storage conditions.

reactions

Conditions to avoid : No data available Incompatible materials : No data available No decomposition if stored and applied as directed.

## **SECTION 11: Toxicological information**

Information on likely routes of : None known.

exposure

## Acute toxicity

Not classified based on available information.

#### **Components:**

## 3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : LD50 Oral (Rat): 1,030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.01 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

# Sikafloor®-80 EpoCem® Primer Part B

Sika ®

Version 3.1 SDS Number: 000000020259 Revision Date: 11.05.2020

### Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

## Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

Not classified based on available information.

#### Reproductive toxicity

Not classified based on available information.

#### STOT - single exposure

Not classified based on available information.

### STOT - repeated exposure

Not classified based on available information.

### **Aspiration toxicity**

Not classified based on available information.

#### **SECTION 12: Ecological information**

#### **Ecotoxicity**

#### Components:

## 3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100

mg/l

Exposure time: 72 h

#### Persistence and degradability

No data available

### **Bioaccumulative potential**

No data available

#### Mobility in soil

No data available

#### Other adverse effects

#### **Product:**

Additional ecological

information

: There is no data available for this product.

#### **SECTION 13: Disposal information**

#### **Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

# Sikafloor®-80 EpoCem® Primer Part B



Version 3.1 SDS Number: 000000020259 Revision Date: 11.05.2020

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14: Transport information**

#### International Regulations

#### **UNRTDG**

Not regulated as a dangerous good

#### IATA-DGR

Not regulated as a dangerous good

#### **IMDG-Code**

Not regulated as a dangerous good

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **SECTION 15: Regulatory information**

### Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

#### **SECTION 16: Other information**

Date format : dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!