Sikafloor®-80 EpoCem® Primer Part A

Revision Date: 11.05.2020

Version 5.0

SECTION 1: Identification of the hazardous chemical and of the supplier

Product name Product code Type of product	:	Sikafloor®-80 EpoCem® Primer Part A 000000600996 liquid
Manufacturer or supplier's de	eta	ills
Company	:	Sika Kimia Sdn. Bhd. Lot 689 Nilai Industrial Estate 71800 Nilai
Telephone	:	+60 6799 1762
Telefax	:	+60 6799 1980
E-mail address	:	EHS@my.sika.com
Emergency telephone number Contact point	:	-

SECTION 2: Hazards identification

Classification of the hazardous chemical Skin corrosion/irritation : Category 2

	. Outogory 2
Serious eye damage/eye irritation	: Category 2
Skin sensitisation	: Category 1
Hazardous to the aquatic environment - chronic hazard	: Category 2
Label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	 H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	 Prevention: P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P273 Avoid release to the environment. P280 Wear protective gloves/ eye protection/ face protection. Response: P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P391 Collect spillage.

Version 5.0



Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

Hazardous components


Chemical name	CAS-No.	Concentration (%)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	25068-38-6	>= 30 - < 60
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	>= 3 - < 5
Polyoxyalkylene alkylether fatty acid	72283-35-3	>= 1 - < 3

SECTION 4: First aid measures

General advice	: Move out of dangerous area. Consult a physician.
If inhaled	 Show this safety data sheet to the doctor in attendance. Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water.
In case of eye contact	 If symptoms persist, call a physician. Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing.
If swallowed	If eye irritation persists, consult a specialist.Clean mouth with water and drink afterwards plenty of water. Do not give milk or alcoholic beverages.
Most important symptoms and effects, both acute and delayed	 Never give anything by mouth to an unconscious person. Obtain medical attention. irritant effects sensitising effects Allergic reactions Excessive lachrymation
	Dermatitis See Section 11 for more detailed information on health effects and symptoms. Causes skin irritation. May cause an allergic skin reaction.
Notes to physician	Causes serious eye irritation. : Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Physicochemical hazards arising from the chemical		
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.	



protective equipment and emergency procedures	•	Deny access to unprotected persons.
Environmental precautions	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage

Handling

Precautions for safe handlin Advice on protection against fire and explosion	-	Normal measures for preventive fire protection.
Advice on safe handling	:	Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products
Storage		

Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

Control parameters

Sikafloor®-80 EpoCem® Primer Part A

Version 5.0



Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

SECTION 8: Exposure controls and personal protection

	th occupational exposure limit values.
Individual protection mea	sures, such as personal protective equipment
Eye/face protection	 Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin protection	 Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Respiratory protection	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.
Hygiene measures	 Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

Appearance Colour Odour Odour Threshold	:	liquid white odourless No data available
pH Melting point/range / Freezing point Boiling point/boiling range	::	Not applicable No data available No data available
Flash point	:	No data available
Evaporation rate	:	No data available
Flammability	:	No data available
Upper explosion limit	:	No data available
Lower explosion limit	:	No data available

Version 5.0

SDS Number: 000000600996



Vapour pressure	: 23 hPa (17 mmHg)
Relative vapour density	: No data available
Density	: 1.1 g/cm3 (20 °C (68 °F) ())
Solubility(ies) Water solubility	: No data available
Water solubility	. NO data avaliable
Solubility in other solvents	: No data available
Partition coefficient: n- octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: >7 mm2/s (40 °C)
Explosive properties	: No data available
Molecular weight	: No data available

SECTION 10: Stability and reactivity

Reactivity Chemical stability Possibility of hazardous reactions	 No dangerous reaction known under conditions of normal use. The product is chemically stable. Stable under recommended storage conditions.
Conditions to avoid	: No data available
Incompatible materials	: No data available
No decomposition if stored and	d applied as directed.

SECTION 11: Toxicological information

Information on likely routes of : None known. exposure

Acute toxicity

Not classified based on available information.

Components:

reaction product: bisphene weight < 700):	ol-A-(epichlorhydrin); epoxy resin (number average molecular
Acute oral toxicity	: LD50 Oral (Rat): > 5,000 mg/kg
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 20,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Sikafloor®-80 EpoCem® Primer Part A

Version 5.0

SDS Number: 000000600996



Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction. Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

Ecotoxicity

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 1.8 mg/l Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological	: An environmental hazard cannot be excluded in the event of
information	unprofessional handling or disposal.
	Toxic to aquatic life with long lasting effects.

6/8

Version 5.0



SECTION 13: Disposal information

Disposal methods	
Waste from residues	: The product should not be allowed to enter drains, water courses or the soil.
	Do not contaminate ponds, waterways or ditches with chemical or used container.
	Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents.
	Dispose of as unused product.
	Do not re-use empty containers.

SECTION 14: Transport information

International Regulations

UNRTDG		
UN number	:	UN 3082
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
Class	:	9
Packing group	:	III
Labels	:	9
IATA-DGR		
UN/ID No.	:	UN 3082
Proper shipping name	:	Environmentally hazardous substance, liquid, n.o.s. (epoxy resin)
Class	:	9
Packing group	:	III
Labels	:	Miscellaneous
Packing instruction (cargo aircraft)	:	964
Packing instruction (passenger aircraft)	:	964
IMDG-Code		
UN number	:	UN 3082
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
Class		9
Packing group	:	
Labels	÷	9
EmS Code	:	F-A, S-F
Marine pollutant	:	no
I I		

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

Sikafloor®-80 EpoCem® Primer Part A

Version 5.0



Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000. International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

SECTION 16: Other information

Date format

: dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !