SikaWall®-168 Plaster



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.08.2022

 4.0
 21.02.2023
 100000024090
 Date of first issue: 01.12.2018

SECTION 1: Identification of the hazardous chemical and of the supplier

Product identifier

Product name : SikaWall®-168 Plaster

Recommended use of the chemical and restrictions on use

Product use : Mortar

Manufacturer or supplier's details

Company : Sika Kimia Sdn. Bhd.

Lot 689 Nilai Industrial Estate

71800 Nilai

Telephone : +60 6799 1762

Emergency telephone number: -

E-mail address : EHS@my.sika.com

Telefax : +60 6799 1980

SECTION 2: Hazards identification

Classification of the hazardous chemical

Skin corrosion/irritation : Category 2

Serious eye damage/eye irri- : Category 1

tation

Skin sensitisation : Category 1

single exposure

Specific target organ toxicity - : Category 3 (Respiratory system)

Label elements

Hazard pictograms :

Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H335 May cause respiratory irritation.

SikaWall®-168 Plaster



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.08.2022

 4.0
 21.02.2023
 100000024090
 Date of first issue: 01.12.2018

Precautionary statements : Prevention:

P261 Avoid breathing dust.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER or doctor/ physician.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO2)	14808-60-7	>= 60 -<= 100
Cement, portland, chemicals	65997-15-1	>= 20 -< 30
calcium carbonate	471-34-1	>= 10 -< 30

SECTION 4: First aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

SikaWall®-168 Plaster



Date of last issue: 27.08.2022 Version **Revision Date:** SDS Number: 21.02.2023 100000024090 Date of first issue: 01.12.2018 4.0

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms

and effects, both acute and delayed

irritant effects sensitising effects

Cough

Respiratory disorder Allergic reactions Excessive lachrymation

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation.

Treat symptomatically. Notes to physician

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media: Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Physicochemical hazards arising from the chemical

ucts

Hazardous combustion prod- : No hazardous combustion products are known

Special protective equipment and precautions for fire-fighters

for firefighters

Special protective equipment: In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

SECTION 6: Accidental release measures

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Avoid breathing dust.

Deny access to unprotected persons.

Environmental precautions Do not flush into surface water or sanitary sewer system.

Methods and materials for

Pick up and arrange disposal without creating dust. containment and cleaning up Keep in suitable, closed containers for disposal.

SikaWall®-168 Plaster



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.08.2022

 4.0
 21.02.2023
 100000024090
 Date of first issue: 01.12.2018

SECTION 7: Handling and storage

Handling

Precautions for safe handling

Advice on protection against:

fire and explosion

Avoid dust formation.

Provide appropriate exhaust ventilation at places where dust

is formed.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Do not breathe vapours/dust.

Storage

Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place. Observe label precautions.

Store in accordance with local regulations.

Further information on stor-

age stability

Keep in a dry place.

No decomposition if stored and applied as directed.

SECTION 8: Exposure controls and personal protection

Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO2)	14808-60-7	TWA (Res- pirable frac- tion)	0.1 mg/m3	MY PEL
		PEL (Respir- able dust)	0.1 mg/m3	MY PEL
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3	ACGIH

SikaWall®-168 Plaster



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.08.2022

 4.0
 21.02.2023
 100000024090
 Date of first issue: 01.12.2018

		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH	
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3	ACGIH	
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH	
Cement, portland, chemicals	65997-15-1	TWA	10 mg/m3	MY PEL	
		PEL (Respir- able dust)	5 mg/m3	MY PEL	
		PEL (Total dust)	10 mg/m3	MY PEL	
		TWA (Res- pirable par- ticulate mat- ter)	1 mg/m3	ACGIH	
calcium carbonate	471-34-1	TWA (partic- ulate)	10 mg/m3 (Calcium car- bonate)	MY PEL	
	Further information: The value is for particulate matter containing no asbestos and <1% crystalline silica				

Individual protection measures, such as personal protective equipment

Eye/face protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink.

SikaWall®-168 Plaster



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.08.2022

 4.0
 21.02.2023
 100000024090
 Date of first issue: 01.12.2018

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

Appearance : powder

Colour : grey

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing:

point

No data available

Boiling point/boiling range : No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper :

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : ca. 1.8 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

SikaWall®-168 Plaster



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.08.2022

 4.0
 21.02.2023
 100000024090
 Date of first issue: 01.12.2018

Explosive properties : No data available

Oxidizing properties : No data available

SECTION 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

No hazards to be specially mentioned.

Conditions to avoid : No data available

Incompatible materials : No data available

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Information on likely routes of : None known.

exposure

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

SikaWall®-168 Plaster



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.08.2022

 4.0
 21.02.2023
 100000024090
 Date of first issue: 01.12.2018

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

: There is no data available for this product.

SECTION 13: Disposal information

Disposal methods

Waste from residues : Send to a licensed waste management company.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

SECTION 14: Transport information

International Regulations

UNRTDG

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

IATA-DGR

SikaWall®-168 Plaster



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.08.2022

 4.0
 21.02.2023
 100000024090
 Date of first issue: 01.12.2018

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

aircraft)

Packing instruction (passen- : Not applicable

ger aircraft)

IMDG-Code

UN number Not applicable Proper shipping name Not applicable Not applicable Class Subsidiary risk Not applicable Packing group Not applicable Not applicable Labels Not applicable EmS Code Not applicable Marine pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

Not applicable

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health)

Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

SECTION 16: Other information

Revision Date : 21.02.2023 Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

MY PEL : Malaysia. Occupational Safety and Health (Use and Stand-

ards of Exposure of Chemicals Hazardous to Health) Regula-

tions 2000.

MY PEL : Malaysia. Factories and Machinery (Mineral Dust) Regulations

- Permissible Exposure Limit

ACGIH / TWA : 8-hour, time-weighted average

MY PEL / TWA : Eight-hour time-weighted average airborne concentration

MY PEL / PEL : Permissible exposure limit (PEL)

SikaWall®-168 Plaster



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 27.08.2022

 4.0
 21.02.2023
 100000024090
 Date of first issue: 01.12.2018

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

MY/EN