

SAFETY DATA SHEET

Sikadur®-732 Part A



Version
2.1

Revision Date:
14.02.2024

SDS Number:
000000601020

Date of last issue: 21.02.2022
Date of first issue: 07.02.2020

SECTION 1: Identification of the hazardous chemical and of the supplier

Product identifier

Product name : Sikadur®-732 Part A

Manufacturer or supplier's details

Company : Sika Kimia Sdn. Bhd.
Lot 689 Nilai Industrial Estate
71800 Nilai

Telephone : +60 6799 1762

Emergency telephone number : -

E-mail address : SDS@my.sika.com

Telefax : +60 6799 1980

SECTION 2: Hazards identification

Classification of the hazardous chemical

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Hazardous to the aquatic environment - chronic hazard : Category 2

Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer.
H411 Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

Sikadur®-732 Part A



Version
2.1

Revision Date:
14.02.2024

SDS Number:
000000601020

Date of last issue: 21.02.2022
Date of first issue: 07.02.2020

Precautionary statements

:

Prevention:

P201 Obtain special instructions before use.
P261 Avoid breathing mist or vapours.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
P281 Use personal protective equipment as required.

Response:

P391 Collect spillage.

Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)	25068-38-6	\geq 30 -< 60
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	\geq 3 -< 5
Hydrocarbons, C10-C13, aromatic, >1% Naphthalene	64742-94-5	\geq 3 -< 5
naphthalene	91-20-3	\geq 0.25 -< 1

SECTION 4: First aid measures

General advice

: Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.

If inhaled

: Move to fresh air.
Consult a physician after significant exposure.

In case of skin contact

: Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.

In case of eye contact

: Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

If swallowed

: Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.

Most important symptoms

: irritant effects

SAFETY DATA SHEET

Sikadur®-732 Part A



Version
2.1

Revision Date:
14.02.2024

SDS Number:
000000601020

Date of last issue: 21.02.2022
Date of first issue: 07.02.2020

and effects, both acute and delayed

sensitising effects
Allergic reactions
Excessive lachrymation
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
Suspected of causing cancer.

Notes to physician : Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Physicochemical hazards arising from the chemical

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

Special protective equipment and precautions for fire-fighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SAFETY DATA SHEET

Sikadur®-732 Part A



Version
2.1

Revision Date:
14.02.2024

SDS Number:
000000601020

Date of last issue: 21.02.2022
Date of first issue: 07.02.2020

SECTION 7: Handling and storage

Handling

Precautions for safe handling

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

Storage

Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Store in original container.
Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Store in accordance with local regulations.

SECTION 8: Exposure controls and personal protection

Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
naphthalene	91-20-3	TWA	10 ppm 52 mg/m ³	MY PEL
		TWA	10 ppm	ACGIH

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling

SAFETY DATA SHEET

Sikadur®-732 Part A



Version
2.1

Revision Date:
14.02.2024

SDS Number:
000000601020

Date of last issue: 21.02.2022
Date of first issue: 07.02.2020

chemical products if a risk assessment indicates this is necessary.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

Appearance : paste

Colour : grey

Odour : characteristic

Odour Threshold : No data available

pH : 6

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 170 °C (338 °F)
(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : 0.01 hPa

Relative vapour density : No data available

Density : 1.4 g/cm³ (20 °C (68 °F))

SAFETY DATA SHEET

Sikadur®-732 Part A



Version
2.1

Revision Date:
14.02.2024

SDS Number:
000000601020

Date of last issue: 21.02.2022
Date of first issue: 07.02.2020

Solubility(ies)
Water solubility : No data available
Solubility in other solvents : No data available
Partition coefficient: n-octanol/water : No data available
Auto-ignition temperature : 370 °C (698 °F)
Decomposition temperature : No data available
Viscosity
Viscosity, dynamic : No data available
Viscosity, kinematic : > 7 mm²/s (40 °C (104 °F))
Explosive properties : No data available
Oxidizing properties : No data available

SECTION 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.
Chemical stability : The product is chemically stable.
Possibility of hazardous reactions : Stable under recommended storage conditions.
Conditions to avoid : No data available
Incompatible materials : No data available
No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Information on likely routes of exposure : None known.

Acute toxicity

Not classified based on available information.

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

SAFETY DATA SHEET

Sikadur®-732 Part A



Version
2.1

Revision Date:
14.02.2024

SDS Number:
000000601020

Date of last issue: 21.02.2022
Date of first issue: 07.02.2020

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

Ecotoxicity

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
aquatic invertebrates Exposure time: 48 h

naphthalene:

M-Factor (Acute aquatic tox- : 1
icity)

M-Factor (Chronic aquatic : 1
toxicity)

Persistence and degradability

No data available

SAFETY DATA SHEET

Sikadur®-732 Part A



Version
2.1

Revision Date:
14.02.2024

SDS Number:
000000601020

Date of last issue: 21.02.2022
Date of first issue: 07.02.2020

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal information

Disposal methods

Waste from residues : Send to a licensed waste management company.

The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.

Do not re-use empty containers.

SECTION 14: Transport information

International Regulations

UNRTDG

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(epoxy resin)
Class : 9
Packing group : III
Labels : 9

IATA-DGR

UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(epoxy resin)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 964
Packing instruction (passen-

SAFETY DATA SHEET

Sikadur®-732 Part A



Version
2.1

Revision Date:
14.02.2024

SDS Number:
000000601020

Date of last issue: 21.02.2022
Date of first issue: 07.02.2020

ger aircraft)

IMDG-Code

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(epoxy resin)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

SECTION 16: Other information

Revision Date : 14.02.2024
Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
MY PEL : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.
ACGIH / TWA : 8-hour, time-weighted average
MY PEL / TWA : Eight-hour time-weighted average airborne concentration
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration
GHS : Globally Harmonized System
IATA : International Air Transport Association
IMDG : International Maritime Code for Dangerous Goods

SAFETY DATA SHEET

Sikadur®-732 Part A



Version
2.1

Revision Date:
14.02.2024

SDS Number:
000000601020

Date of last issue: 21.02.2022
Date of first issue: 07.02.2020

LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

||| Changes as compared to previous version !

MY / EN