

PRODUCT DATA SHEET

Sika AnchorFix® Perforated Sleeves

AnchorFix Accessory for application in hollow bricks/masonry

DESCRIPTION


Sika AnchorFix® Perforated Sleeves are required to apply Sika AnchorFix® products in hollow masonry and hollow bricks.

USES

Perforated sleeves are used to carry out expansion-free fixing of anchors in hollow masonry and hollow bricks

CHARACTERISTICS / ADVANTAGES

- Easy to use
- Different diameters and lengths available
- Fits to several different hollow blocks / bricks
- Center ring cap attached to the sleeve



APPROVALS / STANDARDS

All Sika AnchorFix® Perforated Sleeves are referred in the corresponding approvals of each Sika AnchorFix® product

PRODUCT INFORMATION

Packaging	Packing unit: Bag of 10 /100 pieces per size
Appearance / Colour	Plastic grey sleeves
Shelf Life	5 years from date of production
Storage Conditions	The product must be stored in original, unopened and undamaged packaging in dry conditions at temperatures between +5 °C and +35 °C. Always refer to packaging.

Dimensions

Length	Diameter
50 mm	12 mm
85 mm	16 mm
85 mm	20 mm
130 mm	16 mm

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER INFORMATION

1. Method Statement No: 850 42 07 Sika AnchorFix® products.
2. Product data sheets: Sika AnchorFix® products
3. Approvals: Sika AnchorFix® products
4. Application video: Sika AnchorFix® products

IMPORTANT CONSIDERATIONS

- Only use Sika AnchorFix® anchoring adhesives with Sika AnchorFix® Perforated Sleeves
- Do not use other perforated sleeves with Sika AnchorFix® adhesives.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

APPLICATION METHOD / TOOLS

1. After cleaning dust etc. from the drill hole, the perforated sleeve is placed into the drill hole.
2. Starting from the bottom of the perforated sleeve, gradually apply the Sika AnchorFix® anchoring adhesive into the sleeve so the resin squeezes out through the perforations.
3. Close the sleeve centre ring cap to avoid resin escaping during insertion of the anchor.
4. Insert the anchor into the sleeve with a rotary motion within the adhesive open time. Some of the adhesive must flow out through the perforations into the cavity of the hollow masonry.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Kimia Sdn. Bhd.

Lot 689, Nilai Industrial Estate,
71800 Nilai, Negeri Sembilan D.K.
Malaysia
Phone: +606-7991762
e-mail: info@my.sika.com
Website: www.sika.com.my



Product Data Sheet
Sika AnchorFix® Perforated Sleeves
September 2021, Version 02.01
020205020000000002

SikaAnchorFixPerforatedSleeves-en-MY-(09-2021)-2-1.pdf