

# PRODUCT DATA SHEET

## Sikatherm® PIR AL

### PIR Aluminium Faced Thermal Insulation Board

#### DESCRIPTION

Sikatherm® PIR AL is an insulation board for flat Roofing. It is faced on both sides with an aluminium composite foil bonded to the insulation core and produces a tough, durable, light weight insulation board.

#### USES

- Thermal insulation underneath Sikaplan® and Sarnafil® roof waterproofing

#### CHARACTERISTICS / ADVANTAGES

- Produced with a blowing agent with zero Ozone Depletion Potential (ODP)
- Ideal for new construction and refurbishment
- No separation layer for PVC membranes required
- High compressive strength
- Light weight and low load on the roofing structure
- FM Approved

#### APPROVALS / STANDARDS

- Factory Mutual (FM) Certificate

#### PRODUCT INFORMATION

<b>Packaging</b>	Full length and width boards in protective wrapping
<b>Shelf Life</b>	5 years from date of production
<b>Storage Conditions</b>	Product must be stored in original unopened and undamaged sealed packaging in dry indoor conditions. If stored outside the boards must be stacked clear of the ground and covered with a polythene sheet or weatherproof tarpaulin. Boards that have become wet must be discarded. Always refer to packaging.
<b>Dimensions</b>	Board size <u>2 400 × 1 200 mm</u> Products are available with square or with rebated edges with thicknesses from 25 up to 160 mm.
<b>Density</b>	~32 kg/m <sup>3</sup>

#### TECHNICAL INFORMATION

<b>Compressive Strength</b>	> 150 kPa at 10 % deformation	(EN 826)
<b>Dimensional Stability</b>	DS(70,90)3	(EN 1604)
<b>Thermal Conductivity</b>	0.022 W/(m·K)	(EN 12667 / EN 12939)
	The λ-value quoted is in accordance with the Harmonised European Standard EN 13165: 2012 (Thermal insulation products for buildings – Factory made rigid polyurethane foam (PUR) products – Specification).	

## SYSTEM INFORMATION

### System Structure

The following products must be considered for use depending on roof design:

Roof waterproofing single ply membranes:

- Sarnafil® TS, S, G
- Sikaplan® G, VG, VGWT, S, SGmA

Fasteners and fixings:

- Sarnafast® range

Vapour control layers:

- Sarnavap® range

### Compatibility

Compatible with FPO and PVC single ply membranes Sikaplan® / Sarnafil®. No additional separation layer is required, when Sikaplan® / Sarnafil® is applied over the board surface, faced with an aluminium composite foil. Direct contact between the board core and single ply PVC membranes must be avoided.

## APPLICATION INFORMATION

### Ambient Air Temperature

Refer to roof waterproofing membrane system temperature limitations in Product Data Sheets.

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## IMPORTANT CONSIDERATIONS

Installation work must only be carried out by Sika® trained and approved contractors, experienced in this type of application.

- The product is not classified as hazardous good for transport. Local safety regulations must be observed.
- During the construction process, the construction should be protected from rain penetration during breaks in the process.
- The use of some ancillary products such as adhesives, cleaners and solvents is limited to temperatures above +5 °C. Observe temperature limitations in the appropriate Product Data Sheets.
- Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.
- Not suitable for fully bonded roof build-ups.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product

data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY

The substrate surface must be uniform, smooth and free of any sharp protrusions or burrs, etc. It must be clean, dry and free of grease and dust.

### LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

### LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recom-

mendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**Sika Kimia Sdn. Bhd.**

Lot 689, Nilai Industrial Estate,  
71800 Nilai, Negeri Sembilan D.K.  
Malaysia  
Phone: +606-7991762  
e-mail: [info@my.sika.com](mailto:info@my.sika.com)  
Website: [www.sika.com.my](http://www.sika.com.my)



**Product Data Sheet**

**Sikatherm® PIR AL**

May 2022, Version 01.01  
020935011000011101

SikathermPIRAL-en-MY-(05-2022)-1-1.pdf

