# Sikadur®-31 CF Normal Part B



SDS Number: Date of last issue: -Version **Revision Date:** 

13.08.2025 100000066878 Date of first issue: 13.08.2025 1.0

### SECTION 1: Identification of the hazardous chemical and of the supplier

**Product identifier** 

Product name Sikadur®-31 CF Normal Part B

Recommended use of the chemical and restrictions on use

Product use : Adhesive, Product is not intended for consumer use

Manufacturer or supplier's details

Company Sika Kimia Sdn. Bhd.

Lot 689 Nilai Industrial Estate

71800 Nilai

Telephone +60 6799 1762

Emergency telephone number :

E-mail address SDS@my.sika.com

+60 6799 1980 Telefax

# **SECTION 2: Hazards identification**

#### Classification of the hazardous chemical

Skin corrosion/irritation Category 1B

Serious eye damage/eye irri-

tation

Category 1

Skin sensitisation Category 1

Carcinogenicity Category 2

Specific target organ toxicity - : repeated exposure (Inhala-

tion)

Category 1 (Lungs)

Hazardous to the aquatic

environment - chronic hazard

Category 3

Label elements

Hazard pictograms





Signal word

# Sikadur®-31 CF Normal Part B



Version Revision Date: SDS Number: Date of last issue: -

1.0 13.08.2025 100000066878 Date of first issue: 13.08.2025

Hazard statements : H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H351 Suspected of causing cancer.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure if inhaled.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P260 Do not breathe mist or vapours. P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

P281 Use personal protective equipment as required.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Imme-

diately call a POISON CENTER or doctor/ physician.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER or doctor/ physician.

Other hazards which do not result in classification

None known.

### SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Substance

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Quartz RCS (respirable crystalline silica)	14808-60-7	>= 30 -< 60
benzyl alcohol	100-51-6	>= 5 -< 10
3,6-diazaoctanethylenediamin	112-24-3	>= 3 -< 5
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	>= 3 -< 5
Hydrocarbons, C10-C13, aromatic, >1% Naph-	64742-94-5	>= 2.5 -< 3
thalene		
Adduct IA (epoxy amine adduct)	68609-08-5	>= 1 -< 2.5
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	>= 1 -< 3
naphthalene	91-20-3	>= 0.25 -< 1

#### **SECTION 4: First aid measures**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

# Sikadur®-31 CF Normal Part B



Version Revision Date: SDS Number: Date of last issue: -

1.0 13.08.2025 100000066878 Date of first issue: 13.08.2025

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficul-

ty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Health injuries may be delayed.

corrosive effects sensitising effects Allergic reactions

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing cancer.

Causes damage to organs through prolonged or repeated

exposure if inhaled. Causes severe burns.

Notes to physician : Treat symptomatically.

## **SECTION 5: Firefighting measures**

#### Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

#### Physicochemical hazards arising from the chemical

Hazardous combustion prod- : No hazardous combustion products are known

ucts

# Sikadur®-31 CF Normal Part B



Revision Date: SDS Number: Version Date of last issue: -

100000066878 Date of first issue: 13.08.2025 1.0 13.08.2025

Special protective equipment and precautions for fire-fighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Hazchem Code 2X

**SECTION 6: Accidental release measures** 

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment. Deny access to unprotected persons.

**Environmental precautions** Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

## **SECTION 7: Handling and storage**

#### Handling

### Precautions for safe handling

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Avoid exceeding the given occupational exposure limits (see Advice on safe handling

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

### Storage

## Conditions for safe storage, including any incompatibilities

Conditions for safe storage Store in original container.

Keep container tightly closed in a dry and well-ventilated

place.

# Sikadur®-31 CF Normal Part B



Version Revision Date: SDS Number: Date of last issue: -

1.0 13.08.2025 100000066878 Date of first issue: 13.08.2025

Observe label precautions.

Store in accordance with local regulations.

### **SECTION 8: Exposure controls and personal protection**

### **Control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz RCS (respirable crystalline silica)	14808-60-7	TWA (Respirable fraction)	0.1 mg/m3	MY PEL
		TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3	ACGIH
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3 (Silica)	ACGIH
naphthalene	91-20-3	TWA	10 ppm 52 mg/m3	MY PEL
		TWA	10 ppm	ACGIH

#### Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

# Sikadur®-31 CF Normal Part B



Version Revision Date: SDS Number: Date of last issue: -

1.0 13.08.2025 100000066878 Date of first issue: 13.08.2025

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

### **SECTION 9: Physical and chemical properties**

Appearance : paste

Colour : dark grey

Odour : amine-like

Odour Threshold : No data available

pH : > 11

Concentration: 500 g/l 50

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range : No data available

Flash point :  $> 101 \,^{\circ}\text{C} (214 \,^{\circ}\text{F})$ 

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure :

0.07 hPa

Relative vapour density : No data available

Density : ca. 1.94 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

# Sikadur®-31 CF Normal Part B



Version Revision Date: SDS Number: Date of last issue: -

1.0 13.08.2025 100000066878 Date of first issue: 13.08.2025

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic :  $> 20.5 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$ 

Explosive properties : No data available

Oxidizing properties : No data available

**SECTION 10: Stability and reactivity** 

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition

products

No hazardous decomposition products are known.

**SECTION 11: Toxicological information** 

Information on likely routes of : None known.

exposure

**Acute toxicity** 

Not classified due to lack of data.

Components: benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,200 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

3,6-diazaoctanethylenediamin:

Acute oral toxicity : LD50 Oral (Rat): 1,716 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1,465 mg/kg

# Sikadur®-31 CF Normal Part B



Version Revision Date: SDS Number: Date of last issue: -

1.0 13.08.2025 100000066878 Date of first issue: 13.08.2025

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : LD50 Oral (Rat): 1,030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 - 5,000 mg/kg

Adduct IA (epoxy amine adduct):

Acute oral toxicity : LD50 Oral (Rat, female): 300 - 2,000 mg/kg

Method: OECD Test Guideline 423

2,4,6-tris(dimethylaminomethyl)phenol:

Acute oral toxicity : LD50 Oral (Rat): 2,169 mg/kg

Skin corrosion/irritation

Causes severe burns.

**Components:** 

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit
Assessment : Corrosive

Method : OECD Test Guideline 404

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:

Species : Rabbit

Assessment : Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Not classified due to lack of data.

# Sikadur®-31 CF Normal Part B



Version Revision Date: SDS Number: Date of last issue: -

100000066878 1.0 13.08.2025 Date of first issue: 13.08.2025

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

**Aspiration toxicity** 

Not classified due to lack of data.

**SECTION 12: Ecological information** 

**Ecotoxicity** 

**Components:** 

benzyl alcohol:

Toxicity to fish LC50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

3,6-diazaoctanethylenediamin:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): 10 - 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 10 -

100 mg/l

Exposure time: 72 h

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae/aguatic

plants

ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100

Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 1.5 mg/l

Exposure time: 72 h

Adduct IA (epoxy amine adduct):

Toxicity to algae/aquatic

: EC50 (Pseudokirchneriella subcapitata (algae)): 3.13 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic tox-

plants

LC50 (Danio rerio (zebra fish)): 1.62 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

EC50 (Daphnia magna (Water flea)): 1.75 mg/l

Exposure time: 48 h

naphthalene:

M-Factor (Acute aquatic tox- :

icity)

# Sikadur®-31 CF Normal Part B



Version Revision Date: SDS Number: Date of last issue: -

1.0 13.08.2025 100000066878 Date of first issue: 13.08.2025

M-Factor (Chronic aquatic : 1

toxicity)

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

**SECTION 13: Disposal information** 

**Disposal methods** 

Waste from residues : Send to a licensed waste management company.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

**SECTION 14: Transport information** 

**International Regulations** 

**UNRTDG** 

UN number : UN 1759

Proper shipping name : CORROSIVE SOLID, N.O.S.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, (1-

methylethyl)-1,1'-biphenyl)

Class : 8
Packing group : III
Labels : 8
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 1759

Proper shipping name : Corrosive solid, n.o.s.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, (1-

# Sikadur®-31 CF Normal Part B



Version Revision Date: SDS Number: Date of last issue: -

1.0 13.08.2025 100000066878 Date of first issue: 13.08.2025

methylethyl)-1,1'-biphenyl)

Class : 8 Packing group : III

Labels : Corrosive Packing instruction (cargo : 864

aircraft)

Packing instruction (passen- : 860

ger aircraft)

Environmentally hazardous : yes

**IMDG-Code** 

UN number : UN 1759

Proper shipping name : CORROSIVE SOLID, N.O.S.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, (1-

methylethyl)-1,1'-biphenyl)

Class : 8
Packing group : III
Labels : 8
EmS Code : F-A, S-B

Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Hazchem Code : 2X

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15: Regulatory information**

### Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

## **SECTION 16: Other information**

Revision Date : 13.08.2025 Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

MY PEL : Malaysia. Occupational Safety and Health (Use and Stand-

ards of Exposure of Chemicals Hazardous to Health) Regula-

# Sikadur®-31 CF Normal Part B



Revision Date: Date of last issue: -Version SDS Number:

13.08.2025 100000066878 Date of first issue: 13.08.2025 1.0

tions 2000.

ACGIH / TWA 8-hour, time-weighted average

MY PEL / TWA Eight-hour time-weighted average airborne concentration

**ADR** European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS Chemical Abstracts Service DNEL Derived no-effect level

EC50 Half maximal effective concentration

Globally Harmonized System GHS

International Air Transport Association IATA

International Maritime Code for Dangerous Goods **IMDG** 

Median lethal dosis (the amount of a material, given all at LD50

once, which causes the death of 50% (one half) of a group of

test animals)

Median lethal concentration (concentrations of the chemical in LC50

air that kills 50% of the test animals during the observation

period)

**MARPOL** International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

**OEL** Occupational Exposure Limit

**PBT** Persistent, bioaccumulative and toxic **PNEC** Predicted no effect concentration

Regulation (EC) No 1907/2006 of the European Parliament REACH

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

**SVHC** Substances of Very High Concern

Very persistent and very bioaccumulative vPvB

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

MY / EN