

PRODUCT DATA SHEET

SikaRoof® VersiJack® Barrel Extender

Barrel extender for adjustable screwjack system for raised flooring

DESCRIPTION

SikaRoof® VersiJack® Barrel Extender is an accessory to increase the adjustable height of SikaRoof® VersiJack® pedestals. Barrel extenders are manufactured from recycled polypropylene (PP), while fire-rated pedestals are manufactured from modified reinforced thermoplastics, and it uses a screwjack mechanism to provide precise millimetric adjustments for SikaRoof® VersiJack® from 277 mm to 1014 mm.

SikaRoof® VersiJack® Barrel Extender is used in conjunction with SikaRoof® VersiJack® and is attached between pedestal tops and bases.

USES

Barrel extender for raised paving installations on podiums, balconies, roof terraces and areas with hard-scape finishes.

PRODUCT INFORMATION

Packaging

- SikaRoof® VersiJack® CF 245E
- SikaRoof® VersiJack® CF 245E FR

Appearance / Colour

Black cylindrical extender



CHARACTERISTICS / ADVANTAGES

- Height extender for screwjack pedestal system
- Recyclable components
- Resistant to biological attack by moulds and algae
- Chemically resistant to acids, alkalis, oils and soil chemicals
- Operates within a wide service temperature range

CERTIFICATES AND TEST REPORTS

Singapore Green Building Product (Leader) Cert. No. SGBP 3254

Shelf Life	No expiration date if the product is stored in accordance to the storage conditions as stated in this Product Data Sheet.	
Storage Conditions	Product must be stored in their original packing, and under cool and dry conditions. The product must be protected from direct sunlight, rain, snow and ice, and any other elements.	
Dimensions	130 mm Ø × 265 mm	
Height	Height Extension	160–245 mm

TECHNICAL INFORMATION

Reaction to Fire	SikaRoof® VersiJack® CF 245E FR	
	Toxicity Emission	CIT < 0.75 (BS EN 45545-2)
	Smoke Density	s1 (BS EN 13501-1)
	Fire Spread	Class B _{fl} (BS EN 13501-1)
Service Temperature	-30 °C min. / +80 °C max.	

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

SikaRoof® VersiJack® Barrel Extender is not resistant to permanent weathering and UV exposure. For more information, please contact Sika Sales Personnel.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

Sika Kimia Sdn. Bhd.
 Lot 689, Nilai Industrial Estate,
 71800 Nilai, Negeri Sembilan D.K.
 Malaysia
 Phone: +606-7991762
 e-mail: info@my.sika.com
 Website: www.sika.com.my



Product Data Sheet
 SikaRoof® VersiJack® Barrel Extender
 June 2026, Version 01.01
 020945051990243572

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

Clean and sound surface shall have at least a wood float finish. All holes, joints, and cracks and honeycombs in concrete or masonry surfaces shall be filled with an approved grout and allowed to cure. High spots in concrete or masonry surfaces shall be cut off or ground down to prevent damage/puncture to the pedestal base.

APPLICATION

SikaRoof® VersiJack® Barrel Extender shall be installed with SikaRoof® VersiJack®.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SikaRoofVersiJackBarrelExtender-en-MY-(06-2026)-1-1.pdf

