

PRODUCT DATA SHEET

SikaWall®-193 Finish

WHITE CEMENTITIOUS FINISH SKIMCOAT

DESCRIPTION

SikaWall®-193 Finish is a specially formulated cementitious finishing coat for skimming on wall and ceilings. It's smooth finishing and good adhesion is suitable for internal application.

SikaWall®-193 Finish is designed to provide a smooth durable finish with excellent adhesion strength. The surface can be either brushed or troweled finished to meet stringent architectural requirements.

USES

- Patch fine surface imperfections such as pinholes and hairline cracks
- Suitable for all types of concrete substrates such as lightweight concrete slabs, ceilings, walls, columns and beams
- Excellent for application on lightweight autoclaved aerated concrete blocks

CHARACTERISTICS / ADVANTAGES

- Provide a good fine surface finish on walls, ceilings, etc.
- Non-cracking when applied at correct thickness and properly cured
- Easy to mix – just add water
- Good trowelability on application
- Adjustable consistency
- Good adhesion
- Easy to clean

PRODUCT INFORMATION

Composition	Cementitious mortar
Packaging	25 kg bag
Appearance / Colour	White powder
Shelf Life	6 months from the date of production
Storage Conditions	Store properly in original, unopened and undamaged sealed packaging in dry conditions. Protect from direct sunlight, rain and water.

APPLICATION INFORMATION

Mixing Ratio	8.0–8.5 L water per 25 kg bag
Fresh Mortar Density	~1.6 kg/l
Consumption	~1.25 kg/m ² per mm * This may only serve as a guideline. It is highly recommended to run a trial on site to determine the actual coverage.
Layer Thickness	1.0–3.0 mm

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

Remove all dust, oil or traces of foreign materials. Prepare the dry concrete, plastered surface or SikaWall® surfaces before the application.

MIXING

Add approximately 8.0–8.5 L of clean water to 25 kg of SikaWall®-193 Finish. Mix thoroughly using an electrical mixer until a smooth and creamy consistency is achieved. No standing time required and the mixed finish is ready to use.

APPLICATION

SikaWall®-193 Finish is applied either by hand using a steel trowel or spatula to a recommended thickness of 1–3 mm and cured under shaded ambient conditions. It will remain workable for approximately 60 minutes after mixing.

CLEANING OF TOOLS

Clean all tools and application equipment with water immediately after use. Hardened or cured material can only be removed mechanically.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Kimia Sdn. Bhd.

Lot 689, Nilai Industrial Estate, 71800
Nilai
Negeri Sembilan D.K., Malaysia
Phone: +606-7991762
Fax: +606-7991980
e-mail: info@my.sika.com



Product Data Sheet

SikaWall®-193 Finish
October 2019, Version 01.01
020406010030000104

SikaWall-193Finish-en-MY-(10-2019)-1-1.pdf