Sikafloor®-315 Part B



SDS Number: Date of last issue: 25.03.2019 Version **Revision Date:** 09.03.2021 000000608776 Date of first issue: 30.05.2016 1.2

SECTION 1: Identification of the hazardous chemical and of the supplier

Product identifier

Product name Sikafloor®-315 Part B

Product code 000000608776

Manufacturer or supplier's details

Company : Sika Kimia Sdn. Bhd.

Lot 689 Nilai Industrial Estate

71800 Nilai

Telephone : +60 6799 1762 Telefax : +60 6799 1980 E-mail address : EHS@my.sika.com

Emergency telephone num-

ber

SECTION 2: Hazards identification

Classification of the hazardous chemical

Skin sensitisation Category 1

Reproductive toxicity Category 1B

Hazardous to the aquatic environment - chronic hazard

Category 2

Label elements

Hazard pictograms







Signal word Danger

Hazard statements H317 May cause an allergic skin reaction.

H360FD May damage fertility. May damage the unborn child.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements Prevention:

P201 Obtain special instructions before use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P281 Use personal protective equipment as required.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/

Sikafloor®-315 Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.03.2019

 1.2
 09.03.2021
 000000608776
 Date of first issue: 30.05.2016

attention.

Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)	
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-	104810-47-1	>= 5 -< 10	
benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-			
hydroxyphenyl]-1-oxopropyl]omega[3-[3-(2H			
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-	104810-48-2	>= 5 -< 10	
benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-			
hydroxyphenyl]-1-oxopropyl]omegahydroxy-			
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	>= 2.5 -< 3	
methyl 1,2,2,6,6-pentamethyl-4-piperidyl seba-	82919-37-7	>= 0.25 -< 1	
cate			
dibutyltin dichloride	683-18-1	>= 0.3 -< 1	

SECTION 4: First aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms

and effects, both acute and

delayed

sensitising effects

toxic effects for reproduction

Allergic reactions

See Section 11 for more detailed information on health effects

and symptoms.

May cause an allergic skin reaction.

May damage fertility. May damage the unborn child.

Sikafloor®-315 Part B



Date of last issue: 25.03.2019 Version **Revision Date:** SDS Number: Date of first issue: 30.05.2016 09.03.2021 000000608776 1.2

Notes to physician Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2)

Unsuitable extinguishing

media

Water

Physicochemical hazards arising from the chemical

Specific hazards during fire-

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

ucts

Hazardous combustion prod- : No hazardous combustion products are known

Special protective equipment and precautions for fire-fighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing meth-

ods

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

Personal precautions, protec: : tive equipment and emer-

gency procedures

Use personal protective equipment.

Deny access to unprotected persons.

Environmental precautions Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage

Handling

Precautions for safe handling

Advice on protection against : Normal measures for preventive fire protection.

Sikafloor®-315 Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.03.2019

 1.2
 09.03.2021
 000000608776
 Date of first issue: 30.05.2016

fire and explosion

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Pregnant women or women of child-bearing age should not be

exposed to this product.

Follow standard hygiene measures when handling chemical

products

Storage

Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

SECTION 8: Exposure controls and personal protection

Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis		
dibutyltin dichloride	683-18-1	TWA	0.1 mg/m3 (Tin)	MY PEL		
	Further infor	Further information: Skin				
		TWA	0.1 mg/m3 (Tin)	ACGIH		
		STEL	0.2 mg/m3 (Tin)	ACGIH		

Individual protection measures, such as personal protective equipment

Eye/face protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Sikafloor®-315 Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.03.2019

 1.2
 09.03.2021
 000000608776
 Date of first issue: 30.05.2016

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

Appearance : liquid

Colour : amber

Odour : ether-like

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing :

oint

No data available

Boiling point/boiling range : No data available

Flash point : ca. 86 °C (187 °F)

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : 0.104 hPa

Relative vapour density : No data available

Density : ca. 1 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : No data available

Sikafloor®-315 Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.03.2019

 1.2
 09.03.2021
 000000608776
 Date of first issue: 30.05.2016

Solubility in other solvents : No data available

Partition coefficient: n- : No data available

octanol/water

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : $> 20.5 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$

Explosive properties : No data available

Oxidizing properties : No data available

SECTION 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Information on likely routes of : None known.

exposure

Acute toxicity

Not classified based on available information.

Components:

dibutyltin dichloride:

Acute oral toxicity : LD50 Oral (Rat): 219 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Sikafloor®-315 Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.03.2019

 1.2
 09.03.2021
 000000608776
 Date of first issue: 30.05.2016

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

May damage fertility. May damage the unborn child.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

Ecotoxicity

Components:

dibutvltin dichloride:

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 1.4 mg/l

aquatic invertebrates Exposure time: 48 h

M-Factor (Acute aquatic tox- : 10

icity)

M-Factor (Chronic aquatic

: 10

toxicity)

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

Sikafloor®-315 Part B



Version **Revision Date:** SDS Number: Date of last issue: 25.03.2019 000000608776 Date of first issue: 30.05.2016 09.03.2021 1.2

SECTION 13: Disposal information

Disposal methods

Waste from residues The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

International Regulations

UNRTDG

UN number UN 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate)

9 Class Ш Packing group Labels 9

IATA-DGR

UN/ID No. UN 3082

Proper shipping name Environmentally hazardous substance, liquid, n.o.s.

(bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate)

Class 9 Packing group Ш

Labels Miscellaneous

Packing instruction (cargo

aircraft)

Packing instruction (passen-

964

964

ger aircraft) **IMDG-Code**

UN 3082 UN number

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate)

Class 9 Ш Packing group Labels 9 **EmS Code** F-A, S-F Marine pollutant yes

Sikafloor®-315 Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.03.2019

 1.2
 09.03.2021
 000000608776
 Date of first issue: 30.05.2016

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC)

Schedules of Toxic Chemicals and Precursors

Not applicable

SECTION 16: Other information

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

MY PEL : Malaysia. Occupational Safety and Health (Use and Stand-

ards of Exposure of Chemicals Hazardous to Health) Regula-

tions 2000.

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

MY PEL / TWA : Eight-hour time-weighted average airborne concentration
ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

Sikafloor®-315 Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 25.03.2019

 1.2
 09.03.2021
 000000608776
 Date of first issue: 30.05.2016

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

MY / EN