

PRODUCT DATA SHEET

Davco® Sealer 119

Stones / tiles protector

DESCRIPTION

Davco® Sealer 119 is an organic saturated clear impregnating coating specially formulated to waterproof or protect stone, brick, walls, concrete or any porous finishes against water marks, dirt pick up, fungus and etc.

Davco® Sealer 119 gives an instant water repellency after 10 minutes. The sealer penetrates into the substrates and prevents any efflorescence from leaking out from the stone finish.

USES

- Brick walls
- Stone finishes
- Reinforced concrete
- Ceramic tiles
- Shanghai plaster
- Pebbles
- Weathered old buildings
- Plasters
- Terracotta
- Stuccos

CHARACTERISTICS / ADVANTAGES

- Outstanding water repellence
- Excellent penetration
- Anti-dirt pick-up
- Easy to clean
- Anti-efflorescence
- Maintain natural finish

PRODUCT INFORMATION

Packaging	5 L pail
Appearance / Colour	Clear liquid
Shelf Life	12 months from date of production
Storage Conditions	Store properly in original, unopened and undamaged packaging in cool, dry conditions.

APPLICATION INFORMATION

Consumption	~15–20 m ² /l per coat depending on surface porosity and roughness
-------------	-------------------------------------------------------------------------------

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

All surfaces must be structurally sound, dry, clean and free from movement, oil, grease, wax, curing compound and any other loose or contaminating materials.

APPLICATION

Apply Davco® Sealer 119 with a clean cloth that is soft and devoid of hair, or with soft brush. Apply minimum 2 coats by allowing 1 hour drying in between coat. Stone porous surfaces may require additional coat after full cure. Test a small area to determine suitability of sealer on the stone surface.

CLEANING OF TOOLS

Davco® Sealer 119 and tools can be cleaned with water while it is still wet.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Kimia Sdn. Bhd.

Lot 689, Nilai Industrial Estate,
71800 Nilai, Negeri Sembilan D.K.
Malaysia
Phone: +606-7991762
e-mail: info@my.sika.com
Website: www.sika.com.my



Product Data Sheet

Davco® Sealer 119
March 2026, Version 01.01
02189010000000062

DavcoSealer119-en-MY-(03-2026)-1-1.pdf