

PRODUCT DATA SHEET

Sikaplan® WP Control Socket 14

PVC grouting flange

DESCRIPTION

Sikaplan® WP Control Socket 14 is a flange element with a connection socket for a 14 mm diameter hose. It is based on flexible polyvinylchloride (PVC-p) and is hot air welded to Sikaplan® WP waterproofing membranes.

USES

The Product is used as a:

- Access port for cementitious grouting in basements waterproofed with loosely-laid sheet membranes
- Access port for cementitious grouting in tunnels waterproofed with loosely-laid sheet membranes

CHARACTERISTICS / ADVANTAGES

- Part of the complete waterproofing membrane system
- Proven performance over decades
- Very good workability
- Solid base plate that does not deform while placing the concrete
- No concrete underflow
- Contains no DEHP (DOP) plasticisers
- Compatible with all Sika® PVC waterproofing membranes
- Easy application

PRODUCT INFORMATION

Composition	PVC-p	
Packaging	Products packed in boxes Refer to the current price list for available packaging variations.	
Shelf Life	5 years from date of production	
Storage Conditions	The Product must be stored in original unopened and undamaged packaging in dry conditions.	
Appearance / Colour	Appearance	Round base plate with hose connection socket for attaching injection hose
	Colour	black
Diameter	~180 mm	
Unit Weight	~0.08 kg	

SYSTEM INFORMATION

System Structure	ANCILLARY PRODUCTS: <ul style="list-style-type: none"> ▪ Sikaplan® WP waterproofing membranes
-------------------------	---

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

IMPORTANT

Strictly follow installation procedures

Strictly follow installation procedures as defined in Method Statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

APPLICATION

For information on application, refer to the following Sika® method statements:

- Sikaplan® WP sheet membrane (PVC) system for waterproofing basements and other below ground structures
- Sikaplan® WP sheet membrane (PVC) system for waterproofing tunnels

IMPORTANT

Application by trained personnel

The application of this Product must only be carried out by an applicator that is trained or approved by Sika. The applicator must also be experienced in this type of application.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Kimia Sdn. Bhd.

Lot 689, Nilai Industrial Estate,
71800 Nilai, Negeri Sembilan D.K.
Malaysia
Phone: +606-7991762
e-mail: info@my.sika.com
Website: www.sika.com.my



Product Data Sheet

Sikaplan® WP Control Socket 14
December 2022, Version 04.01
020720804000000014

SikaplanWPControlSocket14-en-MY-(12-2022)-4-1.pdf