

# SAFETY DATA SHEET

## Sikafloor®-161 HC Part A



Version  
3.1

Revision Date:  
25.07.2020

SDS Number:  
000000601221

Date of last issue: 02.10.2018  
Date of first issue: 30.03.2015

### SECTION 1: Identification of the hazardous chemical and of the supplier

#### Product identifier

Product name : Sikafloor®-161 HC Part A

Product code : 000000601221

#### Manufacturer or supplier's details

Company : Sika Kimia Sdn. Bhd.  
Lot 689 Nilai Industrial Estate  
71800 Nilai  
Telephone : +60 6799 1762  
Telefax : +60 6799 1980  
E-mail address : EHS@my.sika.com  
Emergency telephone number : -

### SECTION 2: Hazards identification

#### Classification of the hazardous chemical

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 2

Skin sensitisation : Category 1

Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Lungs)

Hazardous to the aquatic environment - chronic hazard : Category 2

#### Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.  
H411 Toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET

## Sikafloor®-161 HC Part A



Version  
3.1

Revision Date:  
25.07.2020

SDS Number:  
000000601221

Date of last issue: 02.10.2018  
Date of first issue: 30.03.2015

Precautionary statements : **Prevention:**  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
P314 Get medical advice/ attention if you feel unwell.  
P391 Collect spillage.

### Other hazards which do not result in classification

None known.

## SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	25068-38-6	>= 30 -< 60
Quartz (SiO <sub>2</sub> ) <5µm	14808-60-7	>= 10 -< 30
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	>= 3 -< 5
benzyl alcohol	100-51-6	>= 1 -< 3

## SECTION 4: First aid measures

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.  
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.

Most important symptoms : irritant effects

# SAFETY DATA SHEET

## Sikafloor®-161 HC Part A



Version 3.1	Revision Date: 25.07.2020	SDS Number: 000000601221	Date of last issue: 02.10.2018 Date of first issue: 30.03.2015
----------------	------------------------------	-----------------------------	---

---

and effects, both acute and delayed

sensitising effects  
Allergic reactions  
Excessive lachrymation  
Dermatitis  
See Section 11 for more detailed information on health effects and symptoms.  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Causes damage to organs through prolonged or repeated exposure if inhaled.

Notes to physician : Treat symptomatically.

---

### SECTION 5: Firefighting measures

#### Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### Physicochemical hazards arising from the chemical

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

#### Special protective equipment and precautions for fire-fighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

### SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

---

# SAFETY DATA SHEET

## Sikafloor®-161 HC Part A



Version  
3.1

Revision Date:  
25.07.2020

SDS Number:  
000000601221

Date of last issue: 02.10.2018  
Date of first issue: 30.03.2015

### SECTION 7: Handling and storage

#### Handling

##### Precautions for safe handling

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products

#### Storage

##### Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Store in accordance with local regulations.

### SECTION 8: Exposure controls and personal protection

#### Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO <sub>2</sub> ) <5µm	14808-60-7	TWA (Respirable fraction)	0.1 mg/m <sup>3</sup>	MY PEL
		PEL (Respirable dust)	0.1 mg/m <sup>3</sup>	MY PEL
		TWA (Respirable particulate matter)	0.025 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH

# SAFETY DATA SHEET

## Sikafloor®-161 HC Part A



Version  
3.1

Revision Date:  
25.07.2020

SDS Number:  
000000601221

Date of last issue: 02.10.2018  
Date of first issue: 30.03.2015

		ter)		
		TWA (Respirable particulate matter)	0.025 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH

### Individual protection measures, such as personal protective equipment

- Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

### SECTION 9: Physical and chemical properties

- Appearance : liquid
- Colour : grey
- Odour : very faint
- Odour Threshold : No data available
- pH : Not applicable
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : > 93.3 °C (> 199.9 °F)  
(Method: closed cup)

# SAFETY DATA SHEET

## Sikafloor®-161 HC Part A



Version 3.1	Revision Date: 25.07.2020	SDS Number: 000000601221	Date of last issue: 02.10.2018 Date of first issue: 30.03.2015
----------------	------------------------------	-----------------------------	---

---

Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	0.01 hPa
Relative vapour density	:	No data available
Density	:	1.6 g/cm <sup>3</sup> (20 °C (68 °F))
Solubility(ies)	:	
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 7 mm <sup>2</sup> /s (40 °C (104 °F))
Explosive properties	:	No data available
Oxidizing properties	:	No data available

---

### SECTION 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available

No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

## Sikafloor®-161 HC Part A



Version  
3.1

Revision Date:  
25.07.2020

SDS Number:  
000000601221

Date of last issue: 02.10.2018  
Date of first issue: 30.03.2015

### SECTION 11: Toxicological information

Information on likely routes of exposure : None known.

#### Acute toxicity

Not classified based on available information.

#### Components:

**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$  700):**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

#### **benzyl alcohol:**

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

#### **Skin corrosion/irritation**

Causes skin irritation.

#### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Respiratory or skin sensitisation**

##### **Skin sensitisation**

May cause an allergic skin reaction.

##### **Respiratory sensitisation**

Not classified based on available information.

##### **Germ cell mutagenicity**

Not classified based on available information.

##### **Carcinogenicity**

Not classified based on available information.

##### **Reproductive toxicity**

Not classified based on available information.

##### **STOT - single exposure**

Not classified based on available information.

##### **STOT - repeated exposure**

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

##### **Aspiration toxicity**

Not classified based on available information.

# SAFETY DATA SHEET

## Sikafloor®-161 HC Part A



Version  
3.1

Revision Date:  
25.07.2020

SDS Number:  
000000601221

Date of last issue: 02.10.2018  
Date of first issue: 30.03.2015

---

### SECTION 12: Ecological information

#### Ecotoxicity

##### Components:

**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight  $\leq$  700):**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l  
aquatic invertebrates Exposure time: 48 h

##### **benzyl alcohol:**

Toxicity to fish : LC50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
aquatic invertebrates Exposure time: 48 h

#### Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

##### Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life with long lasting effects.

---

### SECTION 13: Disposal information

#### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.



# SAFETY DATA SHEET

## Sikafloor®-161 HC Part A



Version  
3.1

Revision Date:  
25.07.2020

SDS Number:  
000000601221

Date of last issue: 02.10.2018  
Date of first issue: 30.03.2015

---

### SECTION 14: Transport information

#### International Regulations

##### UNRTDG

UN number : UN 3082  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(epoxy resin)  
Class : 9  
Packing group : III  
Labels : 9

##### IATA-DGR

UN/ID No. : UN 3082  
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.  
(epoxy resin)  
Class : 9  
Packing group : III  
Labels : Miscellaneous  
Packing instruction (cargo aircraft) : 964  
Packing instruction (passenger aircraft) : 964

##### IMDG-Code

UN number : UN 3082  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(epoxy resin)  
Class : 9  
Packing group : III  
Labels : 9  
EmS Code : F-A, S-F  
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

### SECTION 15: Regulatory information

#### Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

# SAFETY DATA SHEET

## Sikafloor®-161 HC Part A



Version 3.1	Revision Date: 25.07.2020	SDS Number: 000000601221	Date of last issue: 02.10.2018 Date of first issue: 30.03.2015
----------------	------------------------------	-----------------------------	---

International Chemical Weapons Convention (CWC) : Not applicable  
Schedules of Toxic Chemicals and Precursors

### SECTION 16: Other information

Date format : dd.mm.yyyy

#### Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
MY PEL	: Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.
MY PEL	: Malaysia. Factories and Machinery (Mineral Dust) Regulations - Permissible Exposure Limit
ACGIH / TWA	: 8-hour, time-weighted average
MY PEL / TWA	: Eight-hour time-weighted average airborne concentration
MY PEL / PEL	: Permissible exposure limit (PEL)
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Globally Harmonized System
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

# SAFETY DATA SHEET

## Sikafloor®-161 HC Part A



Version  
3.1

Revision Date:  
25.07.2020

SDS Number:  
000000601221

Date of last issue: 02.10.2018  
Date of first issue: 30.03.2015

---

MY / EN