# Sika AnchorFix®-3001 Part A



Version 3.0 SDS Number: 100000004056 Revision Date: 20.02.2020

### SECTION 1: Identification of the hazardous chemical and of the supplier

Product name : Sika AnchorFix®-3001 Part A

Product code : 10000004056

Type of product : liquid

## Recommended use of the chemical and restrictions on use

Product use : Adhesive

## Manufacturer or supplier's details

Company : Sika Kimia Sdn. Bhd.

Lot 689 Nilai Industrial Estate

71800 Nilai

 Telephone
 : +60 6799 1762

 Telefax
 : +60 6799 1980

 E-mail address
 : EHS@my.sika.com

Emergency telephone

number

Contact point :

### **SECTION 2: Hazards identification**

### Classification of the hazardous chemical

Skin corrosion/irritation : Category 2

Serious eye damage/eye

irritation

: Category 2

Skin sensitisation : Category 1

Hazardous to the aquatic

environment - chronic hazard

: Category 2

## Label elements

Hazard pictograms





Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:** 

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical

advice/ attention.

## Sika AnchorFix®-3001 Part A



Version 3.0 SDS Number: 100000004056 Revision Date: 20.02.2020

P337 + P313 If eye irritation persists: Get medical advice/

attention.

P362 Take off contaminated clothing and wash before reuse.

#### Other hazards which do not result in classification

None known.

### SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

### **Hazardous components**

Chemical name	CAS-No.	Concentration (%)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	25068-38-6	>= 60 - <= 100
epoxy phenol novolac resin	28064-14-4	>= 25 - < 30
1,6-bis(2,3-epoxypropoxy)hexane	16096-31-4	>= 10 - < 25

#### **SECTION 4: First aid measures**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Obtain medical attention.

Most important symptoms

and effects, both acute and

delayed

: irritant effects

sensitising effects Allergic reactions

Excessive lachrymation

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.
Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Notes to physician : Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### **Extinguishing media**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

## Sika AnchorFix®-3001 Part A



Version 3.0 SDS Number: 100000004056 Revision Date: 20.02.2020

circumstances and the surrounding environment.

Physicochemical hazards arising from the chemical

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: No hazardous combustion products are known

Special protective equipment and precautions for fire-fighters

Special protective equipment

for firefighters

Specific extinguishing

methods

: In the event of fire, wear self-contained breathing apparatus.

: Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

#### **SECTION 6: Accidental release measures**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### **SECTION 7: Handling and storage**

#### Handling

### Precautions for safe handling

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours or spray mist.

Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is

being used.

Smoking, eating and drinking should be prohibited in the

application area.

Follow standard hygiene measures when handling chemical

products

## Sika AnchorFix®-3001 Part A

Jika

Version 3.0 SDS Number: 100000004056 Revision Date: 20.02.2020

### Storage

### Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with local regulations.

### **SECTION 8: Exposure controls and personal protection**

### **Control parameters**

Contains no substances with occupational exposure limit values.

### Individual protection measures, such as personal protective equipment

Eye/face protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the

maximum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

## **SECTION 9: Physical and chemical properties**

Appearance : liquid

Colour : off-white, white
Odour : characteristic
Odour Threshold : No data available

Melting point/range / Freezing

weiting point/range / Freezing

ooin

Boiling point/boiling range : > 35 °C (> 95 °F)

Flash point :  $> 100 \, ^{\circ}\text{C} (212 \, ^{\circ}\text{F})$ 

Method: closed cup

Not applicable

: No data available

Evaporation rate : No data available

# Sika AnchorFix®-3001 Part A

Version 3.0 SDS Number: 100000004056 Revision Date: 20.02.2020

Flammability : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 0.01 hPa (0.01 mmHg)

Relative vapour density : No data available

Density : ca. 1.25 g/cm3 (20 °C (68 °F) ())

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n- : No data available

octanol/water

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm2/s (40 °C)

Explosive properties : No data available

Molecular weight : No data available

### **SECTION 10: Stability and reactivity**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous : Stable under recommended storage conditions.

reactions

Conditions to avoid : No data available Incompatible materials : No data available No decomposition if stored and applied as directed.

### **SECTION 11: Toxicological information**

Information on likely routes of : None known.

exposure

**Acute toxicity** 

Not classified based on available information.

Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

weight ≤ 700):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

## Sika AnchorFix®-3001 Part A

Version 3.0 SDS Number: 100000004056 Revision Date: 20.02.2020

epoxy phenol novolac resin:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

1,6-bis(2,3-epoxypropoxy)hexane:

Acute oral toxicity : LD50 Oral (Rat): 2,900 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): > 2,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

**Aspiration toxicity** 

Not classified based on available information.

## **SECTION 12: Ecological information**

### **Ecotoxicity**

#### **Components:**

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

weight ≤ 700):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

: EC50 (Daphnia magna (Water flea)): 1.8 mg/l

aquatic invertebrates

Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

# Sika AnchorFix®-3001 Part A



SDS Number: 100000004056 Version 3.0 Revision Date: 20.02.2020

## Mobility in soil

No data available

#### Other adverse effects

**Product:** 

Additional ecological

: An environmental hazard cannot be excluded in the event of information

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

### **SECTION 13: Disposal information**

Disposal methods

Waste from residues The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

> Dispose of as unused product. Do not re-use empty containers.

### **SECTION 14: Transport information**

### International Regulations

**UNRTDG** 

**UN** number : UN 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(epoxy resin)

Class 9 Packing group Ш Labels 9

**IATA-DGR** 

UN/ID No. UN 3082

Environmentally hazardous substance, liquid, n.o.s. Proper shipping name

(epoxy resin)

Class Ш Packing group

Miscellaneous Labels

Packing instruction (cargo

aircraft)

964

Packing instruction 964

(passenger aircraft)

**IMDG-Code** 

**UN** number UN 3082

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(epoxy resin)

Class 9 Ш Packing group

# Sika AnchorFix®-3001 Part A



Version 3.0 SDS Number: 100000004056 Revision Date: 20.02.2020

Labels : 9

EmS Code : F-A, S-F Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### **SECTION 15: Regulatory information**

### Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

### **SECTION 16: Other information**

Date format : dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!