

PRODUCT DATA SHEET

Sarnafil® PVC Walkway Pad (CN)

Injection moulded PVC walkway pad

DESCRIPTION

Sarnafil® PVC Walkway Pad (CN) is made of high quality PVC by injection moulding procedure.

USES

Sarnafil® PVC Walkway Pad (CN) is used to provide a durable slip resisting walkway for roof maintenance or access on any Sarnafil® PVC or Sikaplan® PVC roofing system.

CHARACTERISTICS / ADVANTAGES

- Resistant to permanent UV irradiation
- Outstanding slip resistant surface
- Hot air welding without use of open flames
- Rainwater drainage from beneath the Sarnafil® Walkway
- Pad PVC is provided by a network of moulded channels
- Recyclable

PRODUCT INFORMATION

Composition	Polyvinyl chloride (PVC)
Packaging	20 pcs/box
Shelf Life	Sarnafil® PVC Walkway Pad does not expire during correct storage.
Storage Conditions	Sarnafil® PVC Walkway Pad shall be stored in dry conditions.
Appearance / Colour	Grey
Surface	Chevron pattern with an alternating rib height of the embossing
Length	605 mm ± 8 mm
Width	600 mm ± 10 mm (exclude welding lap)
Thickness	7 mm ± 0.2 mm including 3 mm non-slip chevron pattern embossing

SYSTEM INFORMATION

Compatibility	Compatible products: Sarnafil® PVC -types Sikaplan® PVC -types
----------------------	--

APPLICATION INFORMATION

Ambient Air Temperature	-20 °C min. / +60 °C max.
Substrate Temperature	-30 °C min. / +60 °C max.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER INFORMATION

Geographical / Climate

The use of Sarnafil® PVC Walkway Pad (CN) is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.

ECOLOGY, HEALTH AND SAFETY

APPLICATION METHOD / TOOLS

According to the valid installation instructions for Sarnafil®.

Sarnafil® PVC Walkway Pad is installed on site by hot air welding the welding tabs directly onto the Sarnafil® G/S or Sikaplan® PVC membrane.

- Mark a line (e.g. chalk line) in the direction of the installation
- Lay the walkway pads along the marked line
- If arranged in a row, move the pads against the two spacers
- Overlap the welding tabs in the running direction of the welding machine

APPLICATION

Installation works must be carried out only by Sika instructed contractors for roofing.

Installation of some ancillary products, e.g. contact adhesives / cleaners is limited to temperatures above +5 °C. Please observe information given by Product Data Sheets.

Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Kimia Sdn. Bhd.

Lot 689, Nilai Industrial Estate,
71800 Nilai, Negeri Sembilan D.K.
Malaysia
Phone: +606-7991762
e-mail: info@my.sika.com
Website: www.sika.com.my



Product Data Sheet
Sarnafil® PVC Walkway Pad (CN)
December 2022, Version 01.01
020945012150002003

SarnafilPVCWalkwayPadCN-en-MY-(12-2022)-1-1.pdf

