



BUILDING TRUST



PRODUCT DATA SHEET

SUPRACOAT SUPRALATEX-66

Multipurpose latex additive for cementitious mortars

DESCRIPTION

SUPRACOAT SUPRALATEX-66 is a synthetic latex emulsion designed for use in mortar mixtures, tile adhesives and other cementitious materials where water resistance is required.

USES

SUPRACOAT SUPRALATEX-66 is recommended for use with site mixed mortars, plasters, tile adhesives and priming slurry. SUPRACOAT SUPRALATEX-66 also improves flexibility and crack-resistance to external and internal rendering, including adhesion strength.

CHARACTERISTICS / ADVANTAGES

- Good adhesion
- Good water resistance
- Non-corrosive
- Ready for use

PRODUCT INFORMATION

Composition	SBR based polymer emulsion
Packaging	<ul style="list-style-type: none">▪ 4 L pail▪ 18 L pail
Shelf life	12 months from date of production
Storage conditions	Store properly in original, unopened and undamaged packaging in dry conditions. Protect from direct sunlight.
Appearance and colour	Milky white liquid

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

The surface should be free from dust, loose particles, oil and other contaminations. Where steel corrosion is present, it should be removed and treated. Surface should be damped with clean water before application.

APPLICATION

Add SUPRACOAT SUPRALATEX-66 directly to fresh ce-

ment to create a soft creamy bonding agent. To improve renders, plasters, repair materials, tiling adhesives, etc. add SUPRACOAT SUPRALATEX-66 directly to the mix. It is not recommended to dilute SUPRACOAT SUPRALATEX-66.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Kimia Sdn. Bhd.

Lot 689, Nilai Industrial Estate,
71800 Nilai, Negeri Sembilan D.K.
Malaysia
Phone: +606-7991762
e-mail: info@my.sika.com
Website: www.sika.com.my



Product Data Sheet
SUPRACOAT SUPRALATEX-66
December 2022, Version 01.01
020302020040000008

SUPRACOATSUPRALATEX-66-en-MYDAVCO-(12-2022)-1-1.pdf

