

PRODUCT DATA SHEET

Sika® Extender T

THICKENING AGENT FOR SIKAFLOOR® FLOORING RESINS

DESCRIPTION

Sika® Extender T is an inert, fine, white, fibrous polymer powder used as a thickening agent for Sikafloor® flooring resins.

USES

- In combination with Sikafloor® epoxy, polyurethane and PMMA resins
- Applications on horizontal surfaces to create custom surface textures
- Applications on vertical surfaces to hold the resin in place during curing
- Crack and pore filler to seal horizontal and vertical surfaces

CHARACTERISTICS / ADVANTAGES

- Allows for viscosity adjustment of Sikafloor® product applications
- Economical, easy to mix and use
- No effect on pot life or cure rate
- Low addition rate required to change resin viscosity
- Non carcinogenic
- Inert and non-reactive

PRODUCT INFORMATION

Packaging	1 kg & 5 kg container
Appearance / Colour	White powder
Shelf Life	2 years from date of production
Storage Conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +25 °C. Always refer to packaging.

APPLICATION INFORMATION

Recommended Dosage	Refer to the individual Sikafloor® resin Product Data Sheet
--------------------	---

APPLICATION INSTRUCTIONS

APPLICATION

General guide:

The required amount of Sika® Extender T is added to the Sikafloor® resin in accordance with the appropriate Product Data Sheet over a period of ~15 seconds until fully mixed without any visible lumps. Refer to the individual Sikafloor® resin Product Data Sheet for further information.

IMPORTANT CONSIDERATIONS

- Do not hand mix Sika® Extender T, mechanically mix only.
- Gloss finish maybe affected at high addition rates.
- Adhesion characteristics may be affected at high addition rates.
- Sika® Extender T maybe visible in some clear resins at high addition rates.
- Protect from contact with moisture, Sika® Extender T must be kept dry.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

Sika Kimia Sdn. Bhd.

Lot 689, Nilai Industrial Estate, 71800

Nilai

Negeri Sembilan D.K., Malaysia

Phone: +606-7991762

Fax: +606-7991980

e-mail: info@my.sika.com



Product Data Sheet

Sika® Extender T

April 2020, Version 01.01

020816020040000002

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

SikaExtenderT-en-MY-(04-2020)-1-1.pdf