Sikafloor®-161 HC Part B



Version SDS Number: Revision Date: Date of last issue: 12.08.2022 07.08.2024 10000001980 Date of first issue: 19.12.2017 4.1

SECTION 1: Identification of the hazardous chemical and of the supplier

Product identifier

Product name Sikafloor®-161 HC Part B

Recommended use of the chemical and restrictions on use

Product use : Epoxy coating, Product is not intended for consumer use

Manufacturer or supplier's details

Company Sika Kimia Sdn. Bhd.

Lot 689 Nilai Industrial Estate

71800 Nilai

Telephone +60 6799 1762

Emergency telephone number :

E-mail address SDS@my.sika.com

+60 6799 1980 Telefax

SECTION 2: Hazards identification

Classification of the hazardous chemical

Acute toxicity (Oral) Category 4

Skin corrosion/irritation Category 1B

Serious eye damage/eye irri-

tation

Category 1

Skin sensitisation Category 1

Hazardous to the aquatic

environment - chronic hazard

Category 3

Label elements

Hazard pictograms



Signal word Danger

Hazard statements H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Sikafloor®-161 HC Part B



Revision Date: Date of last issue: 12.08.2022 Version SDS Number: 07.08.2024 10000001980 Date of first issue: 19.12.2017 4.1

Precautionary statements Prevention:

> P261 Avoid breathing mist or vapours. P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P304 + P340 + P310 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Imme-

diately call a POISON CENTER or doctor/ physician.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER or doctor/ physician.

Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)	
benzyl alcohol	100-51-6	>= 30 -< 60	
Adduct IXA-P (epoxy amine adduct, polymer)	212580-83-1	>= 10 -< 25	
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	>= 10 -< 30	
m-phenylenebis(methylamine)	1477-55-0	>= 10 -< 25	
Hydrocarbons, C9, aromatics	64742-95-6	>= 5 -< 10	
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	>= 3 -< 5	

SECTION 4: First aid measures

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated

wounds from corrosion of the skin heal slowly and with difficul-

ty.

Sikafloor®-161 HC Part B



Revision Date: Date of last issue: 12.08.2022 Version SDS Number: 07.08.2024 10000001980 Date of first issue: 19.12.2017 4.1

In case of eye contact Small amounts splashed into eyes can cause irreversible tis-

sue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed Clean mouth with water and drink afterwards plenty of water.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

Health injuries may be delayed.

corrosive effects sensitising effects

Gastrointestinal discomfort

Allergic reactions

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms. Harmful if swallowed.

May cause an allergic skin reaction. Causes serious eye damage.

Causes severe burns.

Notes to physician Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2)

Unsuitable extinguishing

media

Water

Physicochemical hazards arising from the chemical

ucts

Hazardous combustion prod- : No hazardous combustion products are known

Special protective equipment and precautions for fire-fighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

for firefighters

Specific extinguishing meth-

Standard procedure for chemical fires.

SECTION 6: Accidental release measures

Sikafloor®-161 HC Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12.08.2022

 4.1
 07.08.2024
 100000001980
 Date of first issue: 19.12.2017

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage

Handling

Precautions for safe handling

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

Storage

Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Store in original container.

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

SECTION 8: Exposure controls and personal protection

Control parameters

Sikafloor®-161 HC Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12.08.2022

 4.1
 07.08.2024
 100000001980
 Date of first issue: 19.12.2017

		(Form of exposure)	ters / Permissible concentration		
m-phenylenebis(methylamine)	1477-55-0	CEIL	0.1 mg/m3	MY PEL	
	Further information: Skin				
		С	0.018 ppm	ACGIH	

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

Appearance : liquid

Colour : light yellow

Odour : amine-like

Odour Threshold : No data available

pH : ca. 11 (20 °C (68 °F))

Concentration: 50 %

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range : No data available

Flash point : ca. 68 °C (154 °F)

Sikafloor®-161 HC Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12.08.2022

 4.1
 07.08.2024
 100000001980
 Date of first issue: 19.12.2017

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 4.9996 hPa

Relative vapour density : No data available

Density : ca. 1.03 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : ca. 100 mPa.s (20 °C (68 °F))

Viscosity, kinematic : $> 20.5 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$

Explosive properties : No data available

Oxidizing properties : No data available

SECTION 10: Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

Hazardous decomposition : No decomposition if stored and applied as directed.

Sikafloor®-161 HC Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12.08.2022

 4.1
 07.08.2024
 100000001980
 Date of first issue: 19.12.2017

products

SECTION 11: Toxicological information

Information on likely routes of : None known.

exposure

Acute toxicity

Harmful if swallowed.

Components: benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,200 mg/kg

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity : LD50 Oral (Rat): 1,030 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 10 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 - 5,000 mg/kg

m-phenylenebis(methylamine):

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1.34 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: Corrosive to the respiratory tract.

Acute dermal toxicity : LD50 Dermal (Rat): > 3,100 mg/kg

Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg

2,4,6-tris(dimethylaminomethyl)phenol:

Acute oral toxicity : LD50 Oral (Rat): 2,169 mg/kg

Skin corrosion/irritation

Causes severe burns.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:
Species : Rabbit
Assessment : Corrosive

Method : OECD Test Guideline 404

Sikafloor®-161 HC Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12.08.2022

 4.1
 07.08.2024
 100000001980
 Date of first issue: 19.12.2017

Serious eye damage/eye irritation

Causes serious eye damage.

Components:

2,4,6-tris(dimethylaminomethyl)phenol:Species : Rabbit

Assessment : Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

Not classified due to lack of data.

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

Not classified due to lack of data.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12: Ecological information

Ecotoxicity

plants

Components:

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h

aquatic invertebrates

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Toxicity to algae/aquatic

ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100

mg/l

Exposure time: 72 h

NOEC (Desmodesmus subspicatus (green algae)): 1.5 mg/l

Exposure time: 72 h

Sikafloor®-161 HC Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12.08.2022

 4.1
 07.08.2024
 100000001980
 Date of first issue: 19.12.2017

m-phenylenebis(methylamine):

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l

Exposure time: 48 h

Hydrocarbons, C9, aromatics:

Toxicity to algae/aquatic

plants

(Pseudokirchneriella subcapitata (green algae)): 2.6 - 2.9

mg/l

Exposure time: 72 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal information

Disposal methods

Waste from residues : Send to a licensed waste management company.

The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

International Regulations

UNRTDG

Sikafloor®-161 HC Part B



Version Revision Date: SDS Number: Date of last issue: 12.08.2022 10000001980 07.08.2024 Date of first issue: 19.12.2017 4.1

UN number **UN 1760**

Proper shipping name CORROSIVE LIQUID, N.O.S.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-

phenylenebis(methylamine))

Class 8 Packing group Ш 8 Labels Environmentally hazardous no

IATA-DGR

UN 1760 UN/ID No.

Proper shipping name Corrosive liquid, n.o.s.

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-

phenylenebis(methylamine))

Class 8 Ш Packing group

Corrosive Labels 855

Packing instruction (cargo

aircraft)

Packing instruction (passen-

ger aircraft)

851

IMDG-Code

UN number UN 1760

CORROSIVE LIQUID, N.O.S. Proper shipping name

(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-

phenylenebis(methylamine))

Class 8 Packing group Ш Labels 8 EmS Code F-A, S-B Marine pollutant no Remarks Alkalis

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health)

Regulations 2000.

International Chemical Weapons Convention (CWC) Not applicable

Schedules of Toxic Chemicals and Precursors

Sikafloor®-161 HC Part B



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12.08.2022

 4.1
 07.08.2024
 100000001980
 Date of first issue: 19.12.2017

SECTION 16: Other information

Revision Date : 07.08.2024 Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

MY PEL : Malaysia. Occupational Safety and Health (Use and Stand-

ards of Exposure of Chemicals Hazardous to Health) Regula-

tions 2000.

ACGIH / C : Ceiling limit

MY PEL / CEIL : Ceiling limit airborne concentration

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

MY / EN