

SAFETY DATA SHEET

Sika® WT 220 PMY



Version
5.0

Revision Date:
21.02.2023

SDS Number:
100000010959

Date of last issue: 27.09.2022
Date of first issue: 10.06.2016

SECTION 1: Identification of the hazardous chemical and of the supplier

Product identifier

Product name : Sika® WT 220 PMY

Manufacturer or supplier's details

Company : Sika Kimia Sdn. Bhd.
Lot 689 Nilai Industrial Estate
71800 Nilai

Telephone : +60 6799 1762

Emergency telephone number : -

E-mail address : EHS@my.sika.com

Telefax : +60 6799 1980

SECTION 2: Hazards identification

Classification of the hazardous chemical

Serious eye damage/eye irritation : Category 1

Skin sensitisation : Category 1

Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

Precautionary statements :

Prevention:

P261 Avoid breathing dust.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
P333 + P313 If skin irritation or rash occurs: Get medical ad-

SAFETY DATA SHEET

Sika® WT 220 PMY



Version
5.0

Revision Date:
21.02.2023

SDS Number:
10000010959

Date of last issue: 27.09.2022
Date of first issue: 10.06.2016

vice/ attention.
P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
calcium carbonate	471-34-1	>= 30 -< 60
calcium distearate	1592-23-0	>= 10 -< 30
Cement, portland, chemicals	65997-15-1	>= 5 -< 10
sodium carbonate	497-19-8	>= 5 -< 10
Silica -Amorphous, Precip.	112926-00-8	>= 3 -< 5
Distillates (petroleum), solvent-refined light paraffinic; Baseoil — unspecified	64741-89-5	>= 3 -< 5

SECTION 4: First aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms : irritant effects

SAFETY DATA SHEET

Sika® WT 220 PMY



Version
5.0

Revision Date:
21.02.2023

SDS Number:
100000010959

Date of last issue: 27.09.2022
Date of first issue: 10.06.2016

and effects, both acute and
delayed

sensitising effects
Allergic reactions
Excessive lachrymation
See Section 11 for more detailed information on health effects
and symptoms.
May cause an allergic skin reaction.
Causes serious eye damage.

Notes to physician : Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Physicochemical hazards arising from the chemical

Hazardous combustion products : No hazardous combustion products are known

Special protective equipment and precautions for fire-fighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing methods : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid breathing dust.
Deny access to unprotected persons.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up : Pick up and arrange disposal without creating dust.
Keep in suitable, closed containers for disposal.

SECTION 7: Handling and storage

Handling

Precautions for safe handling

Advice on protection against fire and explosion : Avoid dust formation.
Provide appropriate exhaust ventilation at places where dust is formed.

SAFETY DATA SHEET

Sika® WT 220 PMY



Version
5.0

Revision Date:
21.02.2023

SDS Number:
100000010959

Date of last issue: 27.09.2022
Date of first issue: 10.06.2016

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

Do not breathe vapours/dust.

Storage

Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Store in accordance with local regulations.

Further information on storage stability : Keep in a dry place.
No decomposition if stored and applied as directed.

SECTION 8: Exposure controls and personal protection

Control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
calcium carbonate	471-34-1	TWA (particulate)	10 mg/m ³ (Calcium carbonate)	MY PEL
	Further information: The value is for particulate matter containing no asbestos and <1% crystalline silica			
calcium distearate	1592-23-0	TWA	10 mg/m ³	MY PEL
		TWA (Inhalable particulate matter)	10 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	3 mg/m ³	ACGIH
Cement, portland, chemicals	65997-15-1	TWA	10 mg/m ³	MY PEL
		PEL (Respirable dust)	5 mg/m ³	MY PEL
		PEL (Total dust)	10 mg/m ³	MY PEL
		TWA (Respirable par-	1 mg/m ³	ACGIH

SAFETY DATA SHEET

Sika® WT 220 PMY



Version
5.0

Revision Date:
21.02.2023

SDS Number:
100000010959

Date of last issue: 27.09.2022
Date of first issue: 10.06.2016

		ticulate matter)		
Silica -Amorphous, Precip.	112926-00-8	TWA	10 mg/m ³	MY PEL
Distillates (petroleum), solvent-refined light paraffinic; Baseoil — unspecified	64741-89-5	TWA (Mist)	5 mg/m ³	MY PEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH

Individual protection measures, such as personal protective equipment

- Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties

- Appearance : powder
- Colour : grey
- Odour : characteristic
- Odour Threshold : No data available
- pH : Not applicable
- Melting point/range / Freezing point : No data available

SAFETY DATA SHEET

Sika® WT 220 PMY



Version
5.0

Revision Date:
21.02.2023

SDS Number:
100000010959

Date of last issue: 27.09.2022
Date of first issue: 10.06.2016

Boiling point/boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Density	:	Not applicable
Bulk density	:	0.75 kg/m ³
Solubility(ies)	:	
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
		No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	Not applicable
Explosive properties	:	No data available
Oxidizing properties	:	No data available

SECTION 10: Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	No hazards to be specially mentioned.

SAFETY DATA SHEET

Sika® WT 220 PMY



Version
5.0

Revision Date:
21.02.2023

SDS Number:
100000010959

Date of last issue: 27.09.2022
Date of first issue: 10.06.2016

Conditions to avoid : No data available

Incompatible materials : No data available

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

Information on likely routes of exposure : None known.

Acute toxicity

Not classified based on available information.

Components:

Silica -Amorphous, Precip.:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
Method: Expert judgement

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg
Method: Expert judgement

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

Sika® WT 220 PMY



Version
5.0

Revision Date:
21.02.2023

SDS Number:
100000010959

Date of last issue: 27.09.2022
Date of first issue: 10.06.2016

SECTION 12: Ecological information

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal information

Disposal methods

Waste from residues : Send to a licensed waste management company.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.

Do not re-use empty containers.

SECTION 14: Transport information

International Regulations

UNRTDG

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable

SAFETY DATA SHEET

Sika® WT 220 PMY



Version
5.0

Revision Date:
21.02.2023

SDS Number:
100000010959

Date of last issue: 27.09.2022
Date of first issue: 10.06.2016

Labels : Not applicable
Packing instruction (cargo aircraft) : Not applicable
Packing instruction (passenger aircraft) : Not applicable

IMDG-Code

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
EmS Code : Not applicable
Marine pollutant : Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

Not applicable

SECTION 15: Regulatory information

Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable
Schedules of Toxic Chemicals and Precursors

SECTION 16: Other information

Revision Date : 21.02.2023
Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
MY PEL : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.
MY PEL : Malaysia. Factories and Machinery (Mineral Dust) Regulations - Permissible Exposure Limit
ACGIH / TWA : 8-hour, time-weighted average
MY PEL / TWA : Eight-hour time-weighted average airborne concentration
MY PEL / PEL : Permissible exposure limit (PEL)
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS : Chemical Abstracts Service
DNEL : Derived no-effect level
EC50 : Half maximal effective concentration

SAFETY DATA SHEET

Sika® WT 220 PMY



Version
5.0

Revision Date:
21.02.2023

SDS Number:
100000010959

Date of last issue: 27.09.2022
Date of first issue: 10.06.2016

GHS	:	Globally Harmonized System
IATA	:	International Air Transport Association
IMDG	:	International Maritime Code for Dangerous Goods
LD50	:	Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	:	Occupational Exposure Limit
PBT	:	Persistent, bioaccumulative and toxic
PNEC	:	Predicted no effect concentration
REACH	:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	:	Substances of Very High Concern
vPvB	:	Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

MY / EN