## Sikafloor<sup>®</sup>-381 Part B

Revision Date: 19.02.2019


Version 2.2

SECTION 1: Identification of t	he hazardous chemical and of the supplier
Product name	<sup>:</sup> Sikafloor <sup>®</sup> -381 Part B
Product code	: 00000206622
Type of product	: liquid
Recommended use of the	e chemical and restrictions on use
Product use	: Flooring system, Product is not intended for consumer use
Manufacturer or supplier	's details
Company	: Sika Kimia Sdn. Bhd. Lot 689 Nilai Industrial Estate 71800 Nilai
Telephone	: +60 6799 1762
Telefax	: +60 6799 1980
E-mail address	: EHS@my.sika.com
Emergency telephone	: -
number	
Contact point	

#### **SECTION 2: Hazards identification**

Classification of the hazardous chemical			
Acute toxicity (Oral)	: Category 4		
Skin corrosion/irritation	: Category 1B		
Serious eye damage/eye irritation	: Category 1		
Skin sensitisation	: Category 1		
Reproductive toxicity	: Category 2		
Hazardous to the aquatic environment - chronic hazard	: Category 3		
Label elements			
Hazard pictograms			
Signal word	: Danger		
Hazard statements	<ul> <li>H302 Harmful if swallowed.</li> <li>H314 Causes severe skin burns and eye damage.</li> <li>H317 May cause an allergic skin reaction.</li> </ul>		

## Sikafloor<sup>®</sup>-381 Part B



#### Other hazards which do not result in classification

None known.

#### **SECTION 3**: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration (%)
benzyl alcohol	100-51-6	>= 10 - < 30
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2	>= 10 - < 30
m-phenylenebis(methylamine)	1477-55-0	>= 10 - < 30
bisphenol A	80-05-7	>= 3 - < 5
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2	>= 3 - < 5
Polyoxypropylenediamine	9046-10-0	>= 1 - < 3

#### **SECTION 4: First aid measures**

General advice	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attend	lance.
If inhaled	Move to fresh air. Consult a physician after significant exposure.	
In case of skin contact	Take off contaminated clothing and shoes immedi Wash off with soap and plenty of water. Immediate medical treatment is necessary as untr wounds from corrosion of the skin heal slowly and difficulty.	reated
In case of eye contact	Small amounts splashed into eyes can cause irrev tissue damage and blindness.	versible

# Sikafloor<sup>®</sup>-381 Part B

Version 2.2	SDS Number: 000000206622	Revision Date: 19.02.2019
	In the case of contact with eyes, rinse of water and seek medical advice. Continue rinsing eyes during transpor Remove contact lenses. Keep eye wide open while rinsing.	
If swallowed	: Clean mouth with water and drink after Do NOT induce vomiting. Do not give milk or alcoholic beverage Never give anything by mouth to an u Take victim immediately to hospital.	es.
Most important symptoms and effects, both acute and delayed	<ul> <li>Health injuries may be delayed. corrosive effects sensitising effects Gastrointestinal discomfort Allergic reactions Dermatitis See Section 11 for more detailed infor and symptoms. Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye damage. Suspected of damaging fertility. Causes severe burns.</li> </ul>	rmation on health effects
Notes to physician	: Treat symptomatically.	

®

### SECTION 5: Firefighting measures

e extinguishing measures that are appropriate to local cumstances and the surrounding environment.
rom the chemical
hazardous combustion products are known
precautions for fire-fighters
the event of fire, wear self-contained breathing apparatus.
andard procedure for chemical fires.

### SECTION 6: Accidental release measures

Personal precautions,	: Use personal protective equipment.
protective equipment and	Deny access to unprotected persons.
emergency procedures	

# Sikafloor<sup>®</sup>-381 Part B

Version 2.2	SDS Number: 000000206622	Revision Date: 19.02.2019
Environmental precautions	: Do not flush into surface water or sar If the product contaminates rivers and respective authorities.	
Methods and materials for containment and cleaning up	: Soak up with inert absorbent materia acid binder, universal binder, sawdus Keep in suitable, closed containers for	st).

®

#### **SECTION 7: Handling and storage**

#### Handling

<b>Precautions for safe handling</b> Advice on protection against fire and explosion	<ul> <li>Normal measures for preventive fire protection.</li> </ul>
Advice on safe handling	<ul> <li>Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products</li> </ul>

#### Storage

#### Conditions for safe storage, including any incompatibilities

Conditions for safe storage	<ul> <li>Store in original container. Keep container tightly closed in a dry and well-ventilated place.</li> <li>Containers which are opened must be carefully resealed and kept upright to prevent leakage.</li> <li>Observe label precautions.</li> <li>Store in accordance with local regulations.</li> </ul>

### SECTION 8: Exposure controls and personal protection

#### **Control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
m-phenylenebis(methylamine)	1477-55-0	CEIL	0.1 mg/m3	MY PEL
	Further information: Skin			
		С	0.1 mg/m3	ACGIH

# Sikafloor<sup>®</sup>-381 Part B



Version 2.2

Individual protection measure	es, such as personal protective equipment
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Respiratory protection	: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.
Hygiene measures	<ul> <li>Handle in accordance with good industrial hygiene and safety practice.</li> <li>When using do not eat or drink.</li> <li>When using do not smoke.</li> <li>Wash hands before breaks and at the end of workday.</li> </ul>

### **SECTION 9: Physical and chemical properties**

Appearance	:	liquid
Colour	:	yellow
Odour	:	amine-like
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	> 101 °C (> 214 °F) Method: closed cup
Evaporation rate	:	No data available
Flammability	:	No data available
Upper explosion limit	:	No data available

## Sikafloor<sup>®</sup>-381 Part B

Version 2.2	

#### SDS Number: 000000206622



Lower explosion limit	: No data available	
Vapour pressure	: 19.9983 hPa (15.000 mmHg)	
Relative vapour density	: No data available	
Density	: ca. 1.03 g/cm3 (20 °C (68 °F) ())	
Solubility(ies) Water solubility Partition coefficient: n- octanol/water	: insoluble : No data available	
Auto-ignition temperature	: No data available	
Decomposition temperature	: No data available	
Viscosity Viscosity, dynamic Viscosity, kinematic	: No data available : > 20.5 mm2/s (40 °C)	
Explosive properties	: No data available	
Molecular weight	: No data available	

#### **SECTION 10: Stability and reactivity**

Reactivity	: No dangerous reaction known under conditions of normal use.	
Chemical stability	: The product is chemically stable.	
Possibility of hazardous reactions	: Stable under recommended storage conditions.	
Conditions to avoid	: No data available	
Incompatible materials	: No data available	
No decomposition if stored and applied as directed.		

#### **SECTION 11: Toxicological information**

Information on likely routes of : None known. exposure

#### Acute toxicity

Harmful if swallowed.

### Components:

**benzyl alcohol:** Acute oral toxicity

: LD50 Oral (Rat): 1,620 mg/kg

## Sikafloor<sup>®</sup>-381 Part B

Version 2.2



Acute inhalation toxicity	: LC50 (Rat): > 4.178 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
<b>3-aminomethyl-3,5,5-trimeth</b> Acute oral toxicity	<b>ylcyclohexylamine:</b> : LD50 Oral (Rat): 1,030 mg/kg	
Acute inhalation toxicity	: LC50 (Rat): > 5.01 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	: LD50 Dermal (Rabbit): > 2,000 mg/kg	
<b>m-phenylenebis(methylami</b> Acute oral toxicity	<b>ne):</b> : LD50 Oral (Rat): 930 mg/kg	
Acute inhalation toxicity	: LC50 (Rat): 1.34 mg/l Exposure time: 4 h Test atmosphere: dust/mist	
Acute dermal toxicity	: LD50 Dermal (Rat): > 3,100 mg/kg	
<b>2,4,6-tris(dimethylaminome</b> Acute oral toxicity	t <b>hyl)phenol:</b> : LD50 Oral (Rat): 2,169 mg/kg	
<b>Polyoxypropylenediamine:</b> Acute oral toxicity	: LD50 Oral (Rat): 2,880 mg/kg	
Skin corrosion/irritation Causes severe burns. Serious eye damage/eye irri	tation	
Causes serious eye damage.		
Respiratory or skin sensitis Skin sensitisation: May cause Respiratory sensitisation: Not		
Germ cell mutagenicity Not classified based on availa	ble information.	
<b>Carcinogenicity</b> Not classified based on availa	ble information.	
<b>Reproductive toxicity</b> Suspected of damaging fertilit	у.	
<b>STOT - single exposure</b> Not classified based on availa	ble information.	
STOT - repeated exposure Not classified based on availa		
Aspiration toxicity		
Not classified based on availa	ble information.	

## Sikafloor<sup>®</sup>-381 Part B

Version 2.2



### **SECTION 12: Ecological information**

Ecotoxicity	
Components: benzyl alcohol: Toxicity to fish	: LC50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h
<b>3-aminomethyl-3,5,5-trimethyl</b> Toxicity to algae	<b>cyclohexylamine:</b> : ErC50 (Desmodesmus subspicatus (green algae)): > 10 - 100 mg/l Exposure time: 72 h
<b>m-phenylenebis(methylamine</b> Toxicity to fish	): : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l Exposure time: 48 h
<b>2,4,6-tris(dimethylaminometh</b> y Toxicity to algae	/l)phenol: : EC50 (Scenedesmus capricornutum (fresh water algae)): > 10 - 100 mg/l Exposure time: 72 h
<b>Polyoxypropylenediamine:</b> Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (algae)): 15 mg/l Exposure time: 72 h
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: EC50 (Daphnia magna (Water flea)): 80 mg/l Exposure time: 48 h
<b>Persistence and degradability</b> No data available	
<b>Bioaccumulative potential</b> No data available	
<b>Mobility in soil</b> No data available	
Other adverse effects	
Product: Additional ecological information	: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

## Sikafloor<sup>®</sup>-381 Part B

Version 2.2



#### **SECTION 13: Disposal information**

Disposal methods	
Waste from residues	<ul> <li>The product should not be allowed to enter drains, water courses or the soil.</li> <li>Do not contaminate ponds, waterways or ditches with chemical or used container.</li> <li>Send to a licensed waste management company.</li> </ul>
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

#### **SECTION 14: Transport information**

### **International Regulations**

UNRTDG		
UN number	:	UN 1760
Proper shipping name	:	CORROSIVE LIQUID, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, m- phenylenebis(methylamine))
Class	:	8
Packing group	:	III
Labels	:	8
IATA-DGR		
UN/ID No.	:	UN 1760
Proper shipping name	:	Corrosive liquid, n.o.s.
		(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m-phenylenebis(methylamine))
Class	:	8
Packing group	:	III
Labels	:	Corrosives
Packing instruction (cargo aircraft)	:	856
Packing instruction	:	852
(passenger aircraft)		
IMDG-Code		
UN number	:	UN 1760
Proper shipping name	:	CORROSIVE LIQUID, N.O.S.
		(3-aminomethyl-3,5,5-trimethylcyclohexylamine, m- phenylenebis(methylamine))
Class	:	8
Packing group	:	
Labels	÷	8
EmS Code	:	F-A, S-B
Marine pollutant	÷	no
	-	

### **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable for product as supplied.

## Sikafloor<sup>®</sup>-381 Part B

Version 2.2



#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15: Regulatory information**

#### Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000. International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

#### **SECTION 16: Other information**

Date format

: dd.mm.yyyy

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !