## Sikadur<sup>®</sup>-42 HS Part A



Version 3.1	Revision Date: 25.08.2023		SDS Number: 000000606266	Date of last issue: 23.12.2022 Date of first issue: 12.03.2015
SECTION	1: Identification of the	haz	ardous chemical and of the sup	plier
	u <b>ct identifier</b> uct name	:	Sikadur <sup>®</sup> -42 HS Part A	
Manu	ufacturer or supplier's	detai	ils	
Com	pany	:	Sika Kimia Sdn. Bhd. Lot 689 Nilai Industrial Estate 71800 Nilai	
Telep	phone	:	+60 6799 1762	
Emei	rgency telephone numbe	er :	-	
E-ma	ail address	:	EHS@my.sika.com	
Telef	ax	:	+60 6799 1980	

### **SECTION 2: Hazards identification**

Classification of the hazardo Skin corrosion/irritation		chemical Category 2
Serious eye damage/eye irri- tation	:	Category 2
Skin sensitisation	:	Category 1
Carcinogenicity	:	Category 2
Hazardous to the aquatic environment - chronic hazard	:	Category 2
Label elements		
Hazard pictograms	:	
Signal word	:	Warning

Hazard statements:H315 Causes skin irritation.<br/>H317 May cause an allergic skin reaction.<br/>H319 Causes serious eye irritation.<br/>H351 Suspected of causing cancer.<br/>H411 Toxic to aquatic life with long lasting effects.

# Sikadur®-42 HS Part A



Version 3.1	Revision Date: 25.08.2023	SDS Number: 000000606266	Date of last issue: 23.12.2022 Date of first issue: 12.03.2015
Preca	utionary statements	Prevention:	
			or vapours.
		Response:	
		P391 Collect spillage.	

#### Other hazards which do not result in classification

None known.

#### **SECTION 3: Composition and information of the ingredients of the hazardous chemical**

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	25068-38-6	>= 60 -<= 100
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	>= 3 -< 5
Hydrocarbons, C10-C13, aromatic, >1% Naph- thalene	64742-94-5	>= 1 -< 2.5
naphthalene	91-20-3	>= 0.025 -< 0.25

#### **SECTION 4: First aid measures**

General advice :	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.			
If inhaled :	Move to fresh air. Consult a physician after significant exposure.			
In case of skin contact :	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.			
In case of eye contact :	Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.			
If swallowed :	Clean mouth with water and drink afterwards plenty of water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.			
Most important symptoms :	irritant effects			
2 / 10				

# Sikadur<sup>®</sup>-42 HS Part A



Version 3.1	Revision Date: 25.08.2023		SDS Number: 000000606266	Date of last issue: 23.12.2022 Date of first issue: 12.03.2015	
	and effects, both acute and delayed		sensitising effects Allergic reactions Excessive lachrymation Dermatitis See Section 11 for more detailed information on health effects and symptoms. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing cancer.		
Nc	Notes to physician :		Treat symptomatically.		
SECTIO	ON 5: Firefighting measure	es			
Ex	tinguishing media				
Su	Suitable extinguishing media :		Use extinguishing measures that cumstances and the surroundin		
Ph	ysicochemical hazards a	risi	ng from the chemical		
•	ecific hazards during fire- hting	:	Do not allow run-off from fire fig courses.	hting to enter drains or water	
Ha uc	•	:	No hazardous combustion prod	ucts are known	

### Special protective equipment and precautions for fire-fighters

Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.
Specific extinguishing meth- ods	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

#### **SECTION 6: Accidental release measures**

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for : containment and cleaning up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

## Sikadur<sup>®</sup>-42 HS Part A



Version 3.1	Revision Date: 25.08.2023	SDS Number: 000000606266	Date of last issue: 23.12.2022 Date of first issue: 12.03.2015
SECTION	7: Handling and storag	e	
Hand	ling		
Preca	autions for safe handlin	g	
	e on protection against nd explosion	: Normal measures for prev	ventive fire protection.
Advice	e on safe handling	section 8). Do not get in eyes, on skir For personal protection se Persons with a history of s ma, allergies, chronic or re not be employed in any pr used. Smoking, eating and drink plication area.	
Stora	ge		
Cond	itions for safe storage,	including any incompatibilit	ties
Conditions for safe storage :		Store in original container. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.	

### **SECTION 8: Exposure controls and personal protection**

### **Control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
naphthalene	91-20-3	TŴA	10 ppm 52 mg/m3	MY PEL
		TWA	10 ppm	ACGIH

Observe label precautions.

Store in accordance with local regulations.

### Individual protection measures, such as personal protective equipment

Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin protection	:	Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.

# Sikadur<sup>®</sup>-42 HS Part A



Version 3.1	Revision Date: 25.08.2023	SDS Number: 000000606266	Date of last issue: 23.12.2022 Date of first issue: 12.03.2015	
Hand	protection	approved standard should b	ous gloves complying with an e worn at all times when handling ssessment indicates this is nec-	
Respiratory protection		: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max- imum expected contaminant concentration (gas/vapour/aerosol/particulates) that may arise when han- dling the product. If this concentration is exceeded, self- contained breathing apparatus must be used.		
Hygiene measures		: Handle in accordance with g practice. When using do not eat or dr When using do not smoke. Wash hands before breaks a		

### **SECTION 9: Physical and chemical properties**

Appearance	:	liquid
Colour	:	clear
Odour	:	odourless
Odour Threshold	:	No data available
рН	:	Not applicable
Melting point/range / Freezing	:	No data available
point Boiling point/boiling range	:	No data available
Flash point	:	> 93.3 °C (> 199.9 °F) (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	0.001 hPa
Relative vapour density	:	No data available

# Sikadur<sup>®</sup>-42 HS Part A



Vers 3.1	on Revision Date: 25.08.2023		SDS Number: 000000606266	Date of last issue: 23.12.2022 Date of first issue: 12.03.2015
	Density	:	1.15 g/cm3 (20 °C (68 °F))	
	Solubility(ies) Water solubility	:	No data available	
	Solubility in other solvents	:	No data available	
	Partition coefficient: n- octanol/water	:	No data available	
	Auto-ignition temperature	:	500 °C (932 °F)	
	Decomposition temperature	:	No data available	
	Viscosity Viscosity, dynamic	:	No data available	
	Viscosity, kinematic	:	> 7 mm2/s ( 40 °C (104 °F))	
	Explosive properties	:	No data available	
	Oxidizing properties	:	No data available	

### **SECTION 10: Stability and reactivity**

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reac- tions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available

No decomposition if stored and applied as directed.

### **SECTION 11: Toxicological information**

Information on likely routes of : None known. exposure

#### Acute toxicity

\_

Not classified based on available information.

<u>Components:</u>		
reaction product: bisphenol weight ≤ 700):	-A-	(epichlorhydrin); epoxy resin (number average molecular
Acute oral toxicity	:	LD50 Oral (Rat): > 5,000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 20,000 mg/kg

# Sikadur<sup>®</sup>-42 HS Part A



ersion 1	Revision Date: 25.08.2023	SDS Numbe 0000006062	
	corrosion/irritation		
	es skin irritation.	_	
	us eye damage/eye irri	tation	
	es serious eye irritation.		
Respi	ratory or skin sensitis	ation	
	sensitisation		
May c	ause an allergic skin rea	iction.	
-	ratory sensitisation		
	assified based on availa	ble information.	
	cell mutagenicity		
	assified based on availa	ble information.	
	nogenicity ected of causing cancer.		
Repro	ductive toxicity		
Not cla	assified based on availa	ble information.	
	- single exposure assified based on availa	ble information.	
STOT	- repeated exposure		
	assified based on availa	ble information.	
Aspira	ation toxicity		
-	assified based on availa	ble information.	
ECTION <sup>·</sup>	12: Ecological informa	tion	
Facto			
Ecoto	xicity		
	onents:		
		<ul><li>-A-(epichlorhydrin);</li></ul>	epoxy resin (number average molecular
	t <b>≤ 700):</b> ty to fish	: LC50 (Oncorhyn	chus mykiss (rainbow trout)): 2 mg/l
	· <b>j</b> ··· ····	Exposure time: 9	
Tovici	ty to danhnia and other	· EC50 (Danhnia r	magna (Water flea)): 1.8 mg/l
	c invertebrates	Exposure time: 4	
neul-4	halana		
	halene: etor (Acute aquatic tox-	: 1	
icity)			
M-Fac	tor (Chronic aquatic	: 1	

No data available

Persistence and degradability

toxicity)

# Sikadur<sup>®</sup>-42 HS Part A



Version 3.1	Revision Date: 25.08.2023		SDS Number: 000000606266	Date of last issue: 23.12.2022 Date of first issue: 12.03.2015
	<b>cumulative potential</b> ta available			
Mobil	ity in soil ta available			
Other	adverse effects			
<u>Produ</u>	<u>ict:</u>			
Addition mation	onal ecological infor- า	:	An environmental hazard ca unprofessional handling or o Toxic to aquatic life with lon	

Disposal methods		
Waste from residues	:	Send to a licensed waste management company.
		The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product.
		Do not re-use empty containers.

### **SECTION 14: Transport information**

### International Regulations

<b>UNRTDG</b> UN number		UN 3082
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Class	:	9
Packing group	:	III
Labels	:	9
IATA-DGR		
UN/ID No.	:	UN 3082
Proper shipping name	:	Environmentally hazardous substance, liquid, n.o.s. (reaction product: bisphenol A-(epichlorhydrin) epoxy resin (number average molecular weight > 700), solvent naphtha)
Class	:	9
Packing group	:	III
Labels	:	Miscellaneous
Packing instruction (cargo aircraft)	:	964
Packing instruction (passen-	:	964

# Sikadur<sup>®</sup>-42 HS Part A



Version 3.1	Revision Date: 25.08.2023		SDS Number: 000000606266	Date of last issue: 23.12.2022 Date of first issue: 12.03.2015
ger ai	rcraft)			
IMDG	-Code			
UN ni	umber	:	UN 3082	
Prope	er shipping name	:	N.O.S. (reaction product: bisphene	ZARDOUS SUBSTANCE, LIQUID, ol A-(epichlorhydrin) epoxy resin ar weight > 700), solvent naphtha)
Class		:	9	<b>3</b> <i>,,</i> <b>1</b> <i>,</i>
Packi	ng group	:	111	
Label	S	:	9	
EmS	Code	:	F-A, S-F	
Marin	e pollutant	:	yes	

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15: Regulatory information**

#### Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000. International Chemical Weapons Convention (CWC) : Not applicable Schedules of Toxic Chemicals and Precursors

#### **SECTION 16: Other information**

Revision Date Date format	:	25.08.2023 dd.mm.yyyy
Full text of other abbreviatio	ons	
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
MY PEL	:	Malaysia. Occupational Safety and Health (Use and Stand- ards of Exposure of Chemicals Hazardous to Health) Regula- tions 2000.
ACGIH / TWA	:	8-hour, time-weighted average
MY PEL / TWA	:	Eight-hour time-weighted average airborne concentration
ADR	:	European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	:	Chemical Abstracts Service
DNEL	:	Derived no-effect level
EC50	:	Half maximal effective concentration
GHS	:	Globally Harmonized System
ΙΑΤΑ	:	International Air Transport Association

# Sikadur®-42 HS Part A



Version 3.1	Revision Date: 25.08.2023	SDS Number: 000000606266	Date of last issue: 23.12.2022 Date of first issue: 12.03.2015
IMDG LD50		once, which causes the de	le for Dangerous Goods mount of a material, given all at eath of 50% (one half) of a group of
LC50			on (concentrations of the chemical in animals during the observation
MARPO	DL	: International Convention for Ships, 1973 as modified b	or the Prevention of Pollution from v the Protocol of 1978
OEL		: Occupational Exposure Li	
PBT		: Persistent, bioaccumulativ	e and toxic
PNEC		: Predicted no effect concer	ntration
REACH	1	and of the Council of 18 D istration, Evaluation, Author	2006 of the European Parliament ecember 2006 concerning the Reg- prisation and Restriction of Chemi- g a European Chemicals Agency
SVHC vPvB		<ul><li>Substances of Very High (</li><li>Very persistent and very b</li></ul>	

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

MY / EN