

## PRODUCT DATA SHEET

# SikaRoof® VersiScape Spacer Tab

Spacer tab for safety panel for raised landscape finishes

## DESCRIPTION

SikaRoof® VersiScape Spacer Tab is an attachment used on top of adjustable pedestals to create precise and uniform gaps for the alignment of safety panels in raised landscape finishes. Spacer tabs are manufactured from recycled polypropylene (PP), and it supports four safety panel corners that rest on top of the adjustable pedestal.

SikaRoof® VersiScape Spacer Tab is used in conjunction with SikaRoof® VersiScape™ Panels and may be manufactured in two different thicknesses and heights to support different types of landscape finishes.

## USES

Spacer tabs are used with safety panel for raised flooring for podiums, balconies and roof terraces. The safety panel may be used to raise conventional 600 mm × 600 mm pavers, pavers of varying sizes, artificial grass, or a combination of the three.

## CHARACTERISTICS / ADVANTAGES

- Consistent paver gaps
- Promotes surface drainage
- Eliminates efflorescence
- Recyclable components
- Resistant to biological attack by moulds and algae
- Chemically resistant to acids, alkalis, oils and soil chemicals
- Operates within a wide service temperature range

## PRODUCT INFORMATION

### Packaging

- SikaRoof® VersiScape Spacer Tab 4×45
- SikaRoof® VersiScape Spacer Tab 6×20

**Appearance / Colour**

Black circular piece with four spacer tabs



<b>Shelf Life</b>	No expiration date if the product is stored in accordance to the storage conditions as stated in this Product Data Sheet.						
<b>Storage Conditions</b>	Bags must be stored in their original packing, in their original box, and under cool and dry conditions. The product must be protected from direct sunlight, rain, snow and ice, and any other elements.						
<b>Thickness</b>	<table border="1"><tr><td><b>Spacer Tab Thickness</b></td><td></td></tr><tr><td>SikaRoof® VersiScape Spacer Tab 4x45</td><td>4 mm</td></tr><tr><td>SikaRoof® VersiScape Spacer Tab 6x20</td><td>6 mm</td></tr></table>	<b>Spacer Tab Thickness</b>		SikaRoof® VersiScape Spacer Tab 4x45	4 mm	SikaRoof® VersiScape Spacer Tab 6x20	6 mm
<b>Spacer Tab Thickness</b>							
SikaRoof® VersiScape Spacer Tab 4x45	4 mm						
SikaRoof® VersiScape Spacer Tab 6x20	6 mm						
<b>Diameter</b>	82 mm						

**Height****Spacer Tab Height**SikaRoof® VersiScape Spacer Tab 45 mm  
4x45SikaRoof® VersiScape Spacer Tab 20 mm  
6x20**TECHNICAL INFORMATION****Service Temperature** -30 °C min. / +80 °C max.**BASIS OF PRODUCT DATA**

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

**IMPORTANT CONSIDERATIONS**

- SikaRoof® VersiScape Spacer Tab is not resistant to permanent weathering and UV exposure. For more information, please contact Sika Sales Personnel.

**ECOLOGY, HEALTH AND SAFETY**

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

**APPLICATION INSTRUCTIONS****SUBSTRATE PREPARATION**

Clean and sound surface shall have at least a wood float finish. All holes, joints, and cracks and honeycombs in concrete or masonry surfaces shall be filled with an approved grout and allowed to cure. High spots in concrete or masonry surfaces shall be cut off or ground down to prevent damage/puncture to the pedestal base.

**APPLICATION**

SikaRoof® VersiScape Spacer Tab shall be inserted into the top of SikaRoof® VersiJack® pedestal before placing SikaRoof® VersiScape™ Panels abutting to the spacer tab with panel corners sitting on the pedestal.

**LEGAL NOTES**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**Sika Kimia Sdn. Bhd.**

Lot 689, Nilai Industrial Estate,  
71800 Nilai, Negeri Sembilan D.K.  
Malaysia  
Phone: +606-7991762  
e-mail: info@my.sika.com  
Website: www.sika.com.my

**Product Data Sheet**

SikaRoof® VersiScape Spacer Tab  
March 2026, Version 01.01  
020945051990243807

SikaRoofVersiScapeSpacerTab-en-MY-(03-2026)-1-1.pdf

