# Sikafloor®-264 HC Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03.12.2019

 2.2
 29.12.2021
 000000606153
 Date of first issue: 30.03.2015

### SECTION 1: Identification of the hazardous chemical and of the supplier

**Product identifier** 

Product name : Sikafloor®-264 HC Part A

Product code : 000000606153

Manufacturer or supplier's details

Company : Sika Kimia Sdn. Bhd.

Lot 689 Nilai Industrial Estate

71800 Nilai

 Telephone
 : +60 6799 1762

 Telefax
 : +60 6799 1980

 E-mail address
 : EHS@my.sika.com

Emergency telephone num-

ber

### **SECTION 2: Hazards identification**

Classification of the hazardous chemical

Skin corrosion/irritation : Category 2

Serious eye damage/eye irri-

tation

Category 2

Skin sensitisation : Category 1

Specific target organ toxicity - :

repeated exposure

(Inhalation)

Category 1 (Lungs)

Hazardous to the aquatic

environment - chronic hazard

Category 2

Label elements

Hazard pictograms :







Signal word : Danger

Hazard statements : H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure if inhaled.

H411 Toxic to aquatic life with long lasting effects.

# Sikafloor®-264 HC Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03.12.2019

 2.2
 29.12.2021
 000000606153
 Date of first issue: 30.03.2015

Precautionary statements : Prevention:

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P273 Avoid release to the environment. P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

Response:

P314 Get medical advice/ attention if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical ad-

vice/ attention.

Other hazards which do not result in classification

None known.

### SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

## Components

Chemical name	CAS-No.	Concentration (% w/w)
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)	25068-38-6	>= 30 -< 60
Quartz (SiO2) <5µm	14808-60-7	>= 10 -< 30
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	>= 3 -< 5
benzyl alcohol	100-51-6	>= 1 -< 3

### **SECTION 4: First aid measures**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Immediately flush eye(s) with plenty of water.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Induce vomiting immediately and call a physician.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

# Sikafloor®-264 HC Part A



Version **Revision Date:** SDS Number: Date of last issue: 03.12.2019 000000606153 Date of first issue: 30.03.2015 2.2 29.12.2021

Most important symptoms and effects, both acute and

delayed

irritant effects sensitising effects Allergic reactions **Excessive lachrymation** 

**Dermatitis** 

See Section 11 for more detailed information on health effects

and symptoms. Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eve irritation.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

Treat symptomatically. Notes to physician

### **SECTION 5: Firefighting measures**

Extinguishing media

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Physicochemical hazards arising from the chemical

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod: :

ucts

No hazardous combustion products are known

Special protective equipment and precautions for fire-fighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing meth-

ods

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

**SECTION 6: Accidental release measures** 

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Deny access to unprotected persons.

Do not flush into surface water or sanitary sewer system. Environmental precautions

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

# Sikafloor®-264 HC Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03.12.2019

 2.2
 29.12.2021
 000000606153
 Date of first issue: 30.03.2015

Keep in suitable, closed containers for disposal.

### **SECTION 7: Handling and storage**

## Handling

### Precautions for safe handling

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Follow standard hygiene measures when handling chemical

products

## **Storage**

### Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with local regulations.

#### **SECTION 8: Exposure controls and personal protection**

### **Control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO2) <5μm	14808-60-7	TWA (Respirable fraction)	0.1 mg/m3	MY PEL
		PEL (Respir- able dust)	0.1 mg/m3	MY PEL
		TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
		TWA (Res- pirable par-	0.025 mg/m3 (Silica)	ACGIH

# Sikafloor®-264 HC Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03.12.2019

 2.2
 29.12.2021
 000000606153
 Date of first issue: 30.03.2015

ticulate mat- ter)		
TWA (Respirable particulate matter)	0.025 mg/m3	ACGIH
TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3 (Silica)	ACGIH

Individual protection measures, such as personal protective equipment

Eye/face protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hand protection : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the max-

imum expected contaminant concentration

(gas/vapour/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-

contained breathing apparatus must be used.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

### **SECTION 9: Physical and chemical properties**

Appearance : liquid

Colour : various

Odour : very faint

Odour Threshold : No data available

pH : Not applicable

Melting point/range / Freezing : No data available

# Sikafloor®-264 HC Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03.12.2019

 2.2
 29.12.2021
 000000606153
 Date of first issue: 30.03.2015

point

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Density : 1.1 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Auto-ignition temperature : Not applicable

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic :  $> 7 \text{ mm2/s} (40 ^{\circ}\text{C} (104 ^{\circ}\text{F}))$ 

Explosive properties : No data available

Oxidizing properties : No data available

#### **SECTION 10: Stability and reactivity**

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac- :

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

# Sikafloor®-264 HC Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03.12.2019

 2.2
 29.12.2021
 000000606153
 Date of first issue: 30.03.2015

Incompatible materials : No data available

No decomposition if stored and applied as directed.

### **SECTION 11: Toxicological information**

Information on likely routes of : None known.

exposure

**Acute toxicity** 

Not classified based on available information.

**Components:** 

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

weight ≤ 700):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

# Sikafloor®-264 HC Part A



SDS Number: Version **Revision Date:** Date of last issue: 03.12.2019 000000606153 Date of first issue: 30.03.2015 2.2 29.12.2021

### **Aspiration toxicity**

Not classified based on available information.

### **SECTION 12: Ecological information**

### **Ecotoxicity**

### Components:

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

weight ≤ 700):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l

Exposure time: 48 h

benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

### Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

**Product:** 

Additional ecological infor-

Toxic to aquatic life with long lasting effects.

mation

### **SECTION 13: Disposal information**

**Disposal methods** 

Waste from residues The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Send to a licensed waste management company.

Contaminated packaging Empty remaining contents.

> Dispose of as unused product. Do not re-use empty containers.

# Sikafloor®-264 HC Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03.12.2019

 2.2
 29.12.2021
 000000606153
 Date of first issue: 30.03.2015

### **SECTION 14: Transport information**

#### International Regulations

**UNRTDG** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

Class : 9
Packing group : III
Labels : 9

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo : 964

aircraft)

Packing instruction (passen-

964

ger aircraft)

**IMDG-Code** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15: Regulatory information**

### Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC) : Not applicable

Schedules of Toxic Chemicals and Precursors

# Sikafloor®-264 HC Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 03.12.2019

 2.2
 29.12.2021
 000000606153
 Date of first issue: 30.03.2015

#### **SECTION 16: Other information**

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

MY PEL : Malaysia. Occupational Safety and Health (Use and Stand-

ards of Exposure of Chemicals Hazardous to Health) Regula-

tions 2000.

MY PEL : Malaysia. Factories and Machinery (Mineral Dust) Regulations

- Permissible Exposure Limit

ACGIH / TWA : 8-hour, time-weighted average

MY PEL / TWA : Eight-hour time-weighted average airborne concentration

MY PEL / PEL : Permissible exposure limit (PEL)

ADR : European Agreement concerning the International Carriage of

Dangerous Goods by Road

CAS : Chemical Abstracts Service
DNEL : Derived no-effect level

EC50 : Half maximal effective concentration

GHS : Globally Harmonized System

IATA : International Air Transport Association

IMDG : International Maritime Code for Dangerous Goods

LD50 : Median lethal dosis (the amount of a material, given all at

once, which causes the death of 50% (one half) of a group of

test animals)

LC50 : Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation

period)

MARPOL : International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

OEL : Occupational Exposure Limit

PBT : Persistent, bioaccumulative and toxic PNEC : Predicted no effect concentration

REACH : Regulation (EC) No 1907/2006 of the European Parliament

and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

SVHC : Substances of Very High Concern

vPvB : Very persistent and very bioaccumulative

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

MY / EN