



BUILDING TRUST



## PRODUCT DATA SHEET

# SUPRACOAT PREMIUM 3 IN 1 STOPPING COMPOUND

Cementitious compound for application on interior surface of plasterboard

### DESCRIPTION

SUPRACOAT PREMIUM 3 IN 1 STOPPING COMPOUND is specially formulated as a jointing compound, finishing plaster, and bonding compound. It is easy to use and allows for smooth rendering over plasterboard joints, surface defects and cracks. It is also suitable for use as adhesive for the installation of plasterboard decorative cornices to ceilings and walls.

### USES

SUPRACOAT PREMIUM 3 IN 1 STOPPING COMPOUND can be used as jointing compound, finishing plaster and bonding compound.

### CHARACTERISTICS / ADVANTAGES

- Easy to use and gives good workability
- Provide extra smooth finishing
- Low shrinkage
- Excellent coverage and adhesion
- Minimise cracking
- Non-combustible
- Specially formulated to compliment plaster board installation

### PRODUCT INFORMATION

Packaging	18 kg bag
Shelf life	6 months from date of production
Storage conditions	Store properly in dry conditions, in undamaged and unopened, original sealed packaging. Keep away from direct sunlight, rain, water and moisture.
Appearance and colour	White powder

### APPLICATION INFORMATION

Mixing ratio	~7.2 L of water per 18 kg bag
Fresh mortar density	1600–1900 kg/mm <sup>2</sup>
Consumption	~0.9 kg/m <sup>2</sup> /mm * Dry powder * This may only serve as a guideline. It is highly recommended to carry-out trials on site to determine the actual coverage.
Layer thickness	1 mm min. / 5 mm max.
Pot Life	~60 minutes at +28 °C

Product Data Sheet  
SUPRACOAT PREMIUM 3 IN 1 STOPPING COM-  
POUND  
March 2023, Version 01.01  
021840302000000002

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## IMPORTANT CONSIDERATIONS

SUPRACOAT PREMIUM 3 IN 1 STOPPING COMPOUND sets and cure at room temperature and should be allowed to dry out thoroughly before other finishing/decorative works can commence.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY / PRE-TREATMENT

Remove any dust, dirt or loose material from the plasterboard.

Ensure that all fixings, screws or nails are seated just below the surface of plasterboard.

### MIXING

Fill a container with clean water and pour (not dumped!) SUPRACOAT PREMIUM 3 IN 1 STOPPING COMPOUND into the container. Allow SUPRACOAT PREMIUM 3 IN 1 STOPPING COMPOUND to soak for approximately 2 to 3 minutes before mixing. Mix thoroughly using a mechanical mixer until a creamy consistency and homogenous mortar paste is achieved. Do not over-mix as this may accelerate setting/hardening of the mixture. Once hardening has commenced, the material cannot be re-mixed. Ensure the mix is free from lumps before use.

### APPLICATION

All tools must be clean and free from residue of hardened compound during application. Remove excess compound from the substrate, and then apply a uniform thin coat of freshly mixed compound over the joints. Fill up uneven surfaces. Use a steel trowel to produce a smooth finished to the plasterboard. Allow the compound to thoroughly dry-out for at least 24 hours.

#### Sika Kimia Sdn. Bhd.

Lot 689, Nilai Industrial Estate,  
71800 Nilai, Negeri Sembilan D.K.  
Malaysia  
Phone: +606-7991762  
e-mail: info@my.sika.com  
Website: www.sika.com.my



Product Data Sheet  
SUPRACOAT PREMIUM 3 IN 1 STOPPING COM-  
POUND

March 2023, Version 01.01  
021840302000000002

## CLEANING OF EQUIPMENT

All tools can be cleaned with water while the compound is still fresh. Hardened compound can be removed mechanically.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

