

PRODUCT DATA SHEET

SikaRoof® VersiJack® Wall Spacer

Wall spacer for height-adjustable pedestal system for raised pavers flooring

DESCRIPTION

SikaRoof® VersiJack® Wall Spacer is an accessory to create a gap between raised pavers and the surrounding parapet wall. Wall spacers are manufactured from recycled polypropylene (PP), and it has a compressible buffer to accommodate the expansion and contraction of materials under thermal influence.

SikaRoof® VersiJack® Wall Spacer is used in conjunction with SikaRoof® VersiJack® and is installed between the top of pedestals and beneath the pavers.

USES

Wall spacer for raised paving installations on podiums, balconies, roof terraces and areas with hardscape finishes.

PRODUCT INFORMATION

Packaging

SikaRoof® VersiJack® Wall Spacer

3 × 12 G10 2 × 12 G15 3 × 12 G15 4 × 12 G15 2 × 8 G20

CHARACTERISTICS / ADVANTAGES

- Wall buffer for pedestal system
- Recyclable components
- Resistant to biological attack by moulds and algae
- Chemically resistant to acids, alkalis, oils and soil chemicals
- Operates within a wide service temperature range

CERTIFICATES AND TEST REPORTS

Singapore Green Building Product (Leader) Cert. No. SGBP 3254

Appearance / Colour

Black flat rectangular wall spacer

**Shelf Life**

No expiration date if the product is stored in accordance to the storage conditions as stated in this Product Data Sheet.

Storage Conditions

Product must be stored in their original packing, and under cool and dry conditions. The product must be protected from direct sunlight, rain, snow and ice, and any other elements.

Dimensions

250 mm × 85 mm

Thickness

	Spacer Tab Thickness	Wall Spacer Gap
3 × 12 G10	3 mm	10 mm
2 × 12 G15	2 mm	15 mm
3 × 12 G15	3 mm	15 mm
4 × 12 G15	4 mm	15 mm
2 × 8 G20	2 mm	20 mm

Height**Spacer Tab Height**

3 × 12 G10	2 × 12 G15	3 × 12 G15	4 × 12 G15	2 × 8 G20
12 mm	12 mm	12 mm	12 mm	8 mm

TECHNICAL INFORMATION**Service Temperature**

-30 °C min. / +80 °C max.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

- SikaRoof® VersiJack® Wall Spacer is not resistant to permanent weathering and UV exposure. For more information, please contact Sika Sales Personnel.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

Clean and sound surface shall have at least a wood float finish. All holes, joints, and cracks and honeycombs in concrete or masonry surfaces shall be filled with an approved grout and allowed to cure. High spots in concrete or masonry surfaces shall be cut off or ground down to prevent damage/puncture to the pedestal base.

APPLICATION

SikaRoof® VersiJack® Wall Spacer shall be installed with SikaRoof® VersiJack®. SikaRoof® VersiJack® Wall Spacer shall be placed on top of SikaRoof® VersiJack® before placing stone, concrete or porcelain pavers abut to the wall spacer for all pavers along the perimeter of the raised flooring installation.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Kimia Sdn. Bhd.

Lot 689, Nilai Industrial Estate,
71800 Nilai, Negeri Sembilan D.K.
Malaysia
Phone: +606-7991762
e-mail: info@my.sika.com
Website: www.sika.com.my



Product Data Sheet
SikaRoof® VersiJack® Wall Spacer
March 2026, Version 01.01
020945051990243226

SikaRoofVersiJackWallSpacer-en-MY-(03-2026)-1-1.pdf