

## PRODUCT DATA SHEET

# Sika® Plastiment®-500 RP

Set retarding superplasticiser

## DESCRIPTION

Formerly known as SUPRACHEM RP500.  
Sika® Plastiment®-500 RP is a ready to use set retarding water reducing admixture formulated for a wide range of ready mix concrete grades.

## USES

Sika® Plastiment®-500 RP is recommended for use in producing a wide range of ready mix concrete grades to achieve longer workability, improved the concrete quality and faster concrete placement efficiency. Its water reduction and set retardation properties is suitable for the following:

- Wide range of ready mix concrete grades
- Improved casting efficiency
- Cost optimisation - cement reduction / replacement, higher strength development

## PRODUCT INFORMATION

|                           |  |
|---------------------------|--|
| <b>Packaging</b>          | 1000 L IBC   |
| <b>Shelf Life</b>         | 12 months from date of production  |
| <b>Storage Conditions</b> | Store properly in undamaged unopened, original sealed packaging, in dry conditions at temperatures between +5 °C and +30 °C. Protect from direct sunlight and frost. |

## APPLICATION INFORMATION

|                           |  |
|---------------------------|--|
| <b>Recommended Dosage</b> | Medium workability between 0.4–1.0 % by weight of cement.  |
| <b>Compatibility</b>      | Sika® Plastiment®-500 RP may be combined with many other Sika products.<br>Important: Always conduct trials before combining products in specific mixes to determine the correct dosage of admixture required to achieve the desired fresh and hardened concrete properties. |

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

### Sika Kimia Sdn. Bhd.

Lot 689, Nilai Industrial Estate,  
71800 Nilai, Negeri Sembilan D.K.  
Malaysia  
Phone: +606-7991762  
e-mail: info@my.sika.com  
Website: www.sika.com.my



Product Data Sheet  
Sika® Plastiment®-500 RP  
June 2024, Version 01.01  
021303011000000953

SikaPlastiment-500RP-en-MY-(06-2024)-1-1.pdf