

## PRODUCT DATA SHEET

# SikaRoof® VersiJack® Bearer Holder

Bearer holder for height-adjustable pedestal system for raised decking flooring

### DESCRIPTION

SikaRoof® VersiJack® Bearer Holder is an accessory used to connect timber joists to the pedestal for receiving decking boards. Bearer holders are manufactured from recycled polypropylene (PP), and it has two wings to allow screwing into a timber joist giving it self-centering capabilities for increased stability. This bearer holder can accommodate joist widths of 35 mm to 80 mm.

SikaRoof® VersiJack® Bearer Holder is used in conjunction with SikaRoof® VersiJack® and timber joists, and is installed between the pedestal and the joists with the timber screws.

### USES

Bearer holder for raised decking installations on podiums, balconies, roof terraces and areas with hard-scape finishes.

### PRODUCT INFORMATION

#### Packaging

- SikaRoof® VersiJack® Bearer Holder Bi-axial
- SikaRoof® VersiJack® Bearer Holder Bi-axial with Clip
- SikaRoof® VersiJack® Bearer Holder Bi-axial High Wing

#### Appearance / Colour

Black circular disc with two extending wings

### CHARACTERISTICS / ADVANTAGES

- Self-centering timber joist
- Recyclable components
- Resistant to biological attack by moulds and algae
- Chemically resistant to acids, alkalis, oils and soil chemicals
- Operates within a wide service temperature range

### CERTIFICATES AND TEST REPORTS

Singapore Green Building Product (Leader) Cert. No. SGBP 3254



<b>Shelf Life</b>	No expiration date if the product is stored in accordance to the storage conditions as stated in this Product Data Sheet.		
<b>Storage Conditions</b>	Product must be stored in their original packing, and under cool and dry conditions. The product must be protected from direct sunlight, rain, snow and ice, and any other elements.		
<b>Diameter</b>	Ø 131 mm		
<b>Height</b>	<b>Wing Height</b>		
	<b>Bi-axial</b>	<b>Bi-axial with Clip</b>	<b>Bi-axial High Wing</b>
	25 mm	25 mm	45 mm

## TECHNICAL INFORMATION

<b>Service Temperature</b>	-30 °C min. / +80 °C max.
----------------------------	---------------------------

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## IMPORTANT CONSIDERATIONS

- SikaRoof® VersiJack® Bearer Holder is not resistant to permanent weathering and UV exposure. For more information, please contact Sika Sales Personnel.

## ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this

product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its

products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**Sika Kimia Sdn. Bhd.**

Lot 689, Nilai Industrial Estate,  
71800 Nilai, Negeri Sembilan D.K.  
Malaysia  
Phone: +606-7991762  
e-mail: info@my.sika.com  
Website: www.sika.com.my



**Product Data Sheet**  
**SikaRoof® VersiJack® Bearer Holder**  
March 2026, Version 01.01  
020945051990243223

SikaRoofVersiJackBearerHolder-en-MY-(03-2026)-1-1.pdf

