## Sikadur®-52 MY Part A



SDS Number: Date of last issue: 01.04.2023 Version **Revision Date:** 09.04.2025 000000605514 Date of first issue: 11.03.2015 5.0

### SECTION 1: Identification of the hazardous chemical and of the supplier

**Product identifier** 

Product name : Sikadur®-52 MY Part A

Manufacturer or supplier's details

: Sika Kimia Sdn. Bhd. Company

Lot 689 Nilai Industrial Estate

71800 Nilai

: +60 6799 1762 Telephone

Emergency telephone number : -

E-mail address SDS@my.sika.com

Telefax +60 6799 1980

#### **SECTION 2: Hazards identification**

#### Classification of the hazardous chemical

Skin corrosion/irritation Category 2

Serious eye damage/eye irri-

tation

Category 2

Skin sensitisation Category 1

Reproductive toxicity Category 1B

Aspiration hazard Category 1

Hazardous to the aquatic en-

vironment - chronic hazard

Category 2

#### Label elements

Hazard pictograms







Signal word Danger

H304 May be fatal if swallowed and enters airways. Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

## Sikadur®-52 MY Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.04.2023

 5.0
 09.04.2025
 000000605514
 Date of first issue: 11.03.2015

H360F May damage fertility.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P201 Obtain special instructions before use. P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

P281 Use personal protective equipment as required.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER or doctor/ physician.

P308 + P313 IF exposed or concerned: Get medical advice/ at-

tention.

P331 Do NOT induce vomiting.

P391 Collect spillage.

#### Other hazards which do not result in classification

None known.

#### SECTION 3: Composition and information of the ingredients of the hazardous chemical

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
, , , , , , , , , , , , , , , , , , , ,	25068-38-6	>= 60 -<= 100
epoxy resin (number average molecular weight		
≤ 700)		
oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2	>= 10 -< 30
Solvent naphtha (petroleum), heavy arom.	64742-94-5	>= 10 -< 25
naphthalene	91-20-3	>= 0.025 -< 0.25

#### **SECTION 4: First aid measures**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water. If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

## Sikadur®-52 MY Part A



Revision Date: Version SDS Number: Date of last issue: 01.04.2023 09.04.2025 000000605514 Date of first issue: 11.03.2015 5.0

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

May damage fertility.

Risk of serious damage to the lungs (by aspiration).

sensitising effects

toxic effects for reproduction

Aspiration may cause pulmonary oedema and pneumonitis.

Allergic reactions

See Section 11 for more detailed information on health effects

and symptoms.

Notes to physician Treat symptomatically.

### **SECTION 5: Firefighting measures**

Extinguishing media

Suitable extinguishing media Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Physicochemical hazards arising from the chemical

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod- :

ucts

No hazardous combustion products are known

Special protective equipment and precautions for fire-fighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing meth-

ods

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Hazchem Code •3Z

#### **SECTION 6: Accidental release measures**

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment. Deny access to unprotected persons.

3/11

## Sikadur®-52 MY Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.04.2023

 5.0
 09.04.2025
 000000605514
 Date of first issue: 11.03.2015

Environmental precautions : Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

and materials for : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### **SECTION 7: Handling and storage**

#### Handling

## Precautions for safe handling

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is

being used.

Smoking, eating and drinking should be prohibited in the appli-

cation area.

Pregnant women or women of child-bearing age should not be

exposed to this product.

Follow standard hygiene measures when handling chemical

products

### Storage

#### Conditions for safe storage, including any incompatibilities

Conditions for safe storage : Store in original container.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

#### **SECTION 8: Exposure controls and personal protection**

#### **Control parameters**

## Sikadur®-52 MY Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.04.2023

 5.0
 09.04.2025
 000000605514
 Date of first issue: 11.03.2015

Components	CAS-No.	Value type (Form of ex-	Control parameters / Permissible concentration	Basis
		posure)	concentration	
naphthalene	91-20-3	TWA	10 ppm	MY PEL
			52 mg/m3	
		TWA	10 ppm	ACGIH

### Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Hand protection : Chemical-resistant, impervious gloves complying with an ap-

proved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-

essary.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapour/aero-sol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing ap-

paratus must be used.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9: Physical and chemical properties**

Appearance : liquid

Colour : clear

Odour : odourless

Odour Threshold : No data available

pH : 7.7

Melting point/ range / Freez-

ing point

No data available

Boiling point/boiling range : No data available

Flash point :  $> 93.3 \, ^{\circ}\text{C} \, (> 199.9 \, ^{\circ}\text{F})$ 

## Sikadur®-52 MY Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.04.2023

 5.0
 09.04.2025
 000000605514
 Date of first issue: 11.03.2015

(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : 0.1 hPa

Relative vapour density : No data available

Density : 1.1 g/cm3 (20 °C (68 °F))

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-oc-

tanol/water

: No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 7 mm2/s ( 40 °C (104 °F))

Explosive properties : No data available

Oxidizing properties : No data available

**SECTION 10: Stability and reactivity** 

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous reac-

tions

Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

## Sikadur®-52 MY Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.04.2023

 5.0
 09.04.2025
 000000605514
 Date of first issue: 11.03.2015

Hazardous decomposition

products

No hazardous decomposition products are known.

#### **SECTION 11: Toxicological information**

Information on likely routes of : None known.

exposure

**Acute toxicity** 

Not classified due to lack of data.

**Components:** 

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

weight ≤ 700):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

Solvent naphtha (petroleum), heavy arom.:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 4.7 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

Reproductive toxicity

May damage fertility.

STOT - single exposure

Not classified due to lack of data.

## Sikadur®-52 MY Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.04.2023

 5.0
 09.04.2025
 000000605514
 Date of first issue: 11.03.2015

#### STOT - repeated exposure

Not classified due to lack of data.

#### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

### **SECTION 12: Ecological information**

#### **Ecotoxicity**

#### **Components:**

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular

weight ≤ 700):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

EC50 (Daphnia magna (Water flea)): 1.8 mg/l

aquatic invertebrates

Exposure time: 48 h

#### Solvent naphtha (petroleum), heavy arom.:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.1 mg/l

aquatic invertebrates

Exposure time: 48 h

(Chronic toxicity) naphthalene:

M-Factor (Acute aquatic tox- : 1

icity)

M-Factor (Chronic aquatic : 1

toxicity)

### Persistence and degradability

No data available

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

### Other adverse effects

#### **Product:**

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life with long lasting effects.

#### **SECTION 13: Disposal information**

#### **Disposal methods**

Waste from residues : Send to a licensed waste management company.

The product should not be allowed to enter drains, water

courses or the soil.

## Sikadur®-52 MY Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.04.2023

 5.0
 09.04.2025
 000000605514
 Date of first issue: 11.03.2015

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Do not re-use empty containers.

#### **SECTION 14: Transport information**

#### International Regulations

**UNRTDG** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : no

**IATA-DGR** 

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo : 964

aircraft)

Packing instruction (passen- : 964

ger aircraft)

**IMDG-Code** 

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Hazchem Code : •3Z

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## Sikadur®-52 MY Part A



**Revision Date:** SDS Number: Date of last issue: 01.04.2023 Version 09.04.2025 000000605514 Date of first issue: 11.03.2015 5.0

#### **SECTION 15: Regulatory information**

#### Safety, health, and environmental regulations specific for the hazardous chemical

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013.

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2000.

International Chemical Weapons Convention (CWC) Not applicable

Schedules of Toxic Chemicals and Precursors

#### **SECTION 16: Other information**

**Revision Date** 09.04.2025 dd.mm.yyyy Date format

Full text of other abbreviations

**ACGIH** USA. ACGIH Threshold Limit Values (TLV)

MY PEL Malaysia. Occupational Safety and Health (Use and Stand-

ards of Exposure of Chemicals Hazardous to Health) Regula-

tions 2000.

8-hour, time-weighted average ACGIH / TWA

Eight-hour time-weighted average airborne concentration MY PEL / TWA European Agreement concerning the International Carriage of ADR

Dangerous Goods by Road

CAS **Chemical Abstracts Service DNEL** Derived no-effect level

EC50 Half maximal effective concentration **GHS** Globally Harmonized System

International Air Transport Association IATA

**IMDG** International Maritime Code for Dangerous Goods

Median lethal dosis (the amount of a material, given all at

LD50 once, which causes the death of 50% (one half) of a group of

test animals)

LC50 Median lethal concentration (concentrations of the chemical in

air that kills 50% of the test animals during the observation pe-

riod)

**MARPOL** International Convention for the Prevention of Pollution from

Ships, 1973 as modified by the Protocol of 1978

Occupational Exposure Limit **OEL** 

Persistent, bioaccumulative and toxic **PBT PNEC** Predicted no effect concentration

REACH Regulation (EC) No 1907/2006 of the European Parliament

> and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency

Substances of Very High Concern SVHC

vPvB Very persistent and very bioaccumulative

# Sikadur®-52 MY Part A



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.04.2023

 5.0
 09.04.2025
 000000605514
 Date of first issue: 11.03.2015

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version!

MY / EN