

## PRODUCT DATA SHEET

# Sarnafil® Décor Profile PVC

### PVC DECOR PROFILE

#### DESCRIPTION


Sarnafil® Décor Profile PVC is an polyvinyl chloride (PVC) extruded profile made which is welded to PVC sheet waterproofing membranes to replicate standing seam metal roofing systems.

#### USES

Sarnafil® Décor Profile PVC creates an appearance of a standing seam metal roof

#### CHARACTERISTICS / ADVANTAGES

- Applicable for exposed roofing
- Easily applied
- Resistant to UV exposure.
- Suitable for any roof slope
- Hot air weldable
- Available in various colours
- Recyclable



#### PRODUCT INFORMATION

<b>Composition</b>	Polyvinyl chloride (PVC), profile extruded	
<b>Packaging</b>	Cardboard containers of 25 pieces including connector plugs.	
<b>Appearance / Colour</b>	Surface:	smooth
	Colour:	light grey (nearest RAL 7047) lead grey (Sika colour no. 9500) window grey (nearest RAL 7040) copper patina (Sika colour no. 6525) copper brown (nearest RAL 8004) traffic white (nearest RAL 9016) Other colours on request. Subject to minimum order quantities.
<b>Shelf Life</b>	5 years from date of production	

<b>Storage Conditions</b>	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Always refer to packaging.	
<b>Length</b>	3000 mm (+10 mm / -5 mm)	
<b>Width</b>	35 mm (± 1.3 mm)	
<b>Height</b>	25 mm (± 1.3 mm)	
<b>Mass per Unit Area</b>	~285 g/m	

## TECHNICAL INFORMATION

<b>Reaction to Fire</b>	Class E	(EN ISO 11925-2, classification to EN 13501-1)
-------------------------	---------	--

## SYSTEM INFORMATION

<b>System Structure</b>	The following products must be considered for use depending on roof design: <ul style="list-style-type: none"> <li>▪ Sarnamatic® 681/661 Conversion kit Decor Profile</li> <li>▪ Sarnafil® G 410 EL-types</li> <li>▪ Sarnafil® G 410 EL Felt-types</li> <li>▪ Sarnafil® S 327 EL-types</li> </ul>	
-------------------------	---	--

## APPLICATION INFORMATION

<b>Ambient Air Temperature</b>	-20 °C min. / +60 °C max.
<b>Substrate Temperature</b>	-30 °C min. / +60 °C max.

## APPLICATION INSTRUCTIONS

### APPLICATION

#### Installation procedure

Ensure the Sarnafil® Décor Profile PVC is tacked into position at the desired centres and hot air weld into place to the roof membrane. Join two or more Sarnafil® Décor Profile PVCs together, using the connector plugs supplied. Finish the end of the profile with a piece of hot air welded membrane if required.

## IMPORTANT CONSIDERATIONS

Installation work must only be carried out by Sika® trained and approved contractors, experienced in this type of application.

- Ensure Sarnafil® Décor Profile PVC is prevented from direct contact with incompatible materials (refer to compatibility section).
- The use of Sarnafil® Décor Profile PVC membrane is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.
- The use of some ancillary products such as adhesives, cleaners and solvents is limited to temperatures above +5 °C. Observe temperature limitations in the appropriate Product Data Sheets.
- Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## ECOLOGY, HEALTH AND SAFETY

Fresh air ventilation must be ensured, when working (welding) in closed rooms.

### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**Sika Kimia Sdn. Bhd.**

Lot 689, Nilai Industrial Estate, 71800  
Nilai  
Negeri Sembilan D.K., Malaysia  
Phone: +606-7991762  
Fax: +606-7991980  
e-mail: info@my.sika.com



**Product Data Sheet**  
Sarnafil® Décor Profile PVC  
March 2020, Version 01.01  
020945012150000001

SarnafilDcorProfilePVC-en-MY-(03-2020)-1-1.pdf